

DP-100 Dumps

Designing and Implementing a Data Science Solution on Azure

<https://www.certleader.com/DP-100-dumps.html>



NEW QUESTION 1

- (Exam Topic 3)

You are determining if two sets of data are significantly different from one another by using Azure Machine Learning Studio.

Estimated values in one set of data may be more than or less than reference values in the other set of data. You must produce a distribution that has a constant Type I error as a function of the correlation.

You need to produce the distribution.

Which type of distribution should you produce?

- A. Paired t-test with a two-tail option
- B. Unpaired t-test with a two tail option
- C. Paired t-test with a one-tail option
- D. Unpaired t-test with a one-tail option

Answer: A

Explanation:

Choose a one-tail or two-tail test. The default is a two-tailed test. This is the most common type of test, in which the expected distribution is symmetric around zero.

Example: Type I error of unpaired and paired two-sample t-tests as a function of the correlation. The simulated random numbers originate from a bivariate normal distribution with a variance of 1.

Reference:

<https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/test-hypothesis-using-t-test> https://en.wikipedia.org/wiki/Student%27s_t-test

NEW QUESTION 2

- (Exam Topic 3)

You are moving a large dataset from Azure Machine Learning Studio to a Weka environment. You need to format the data for the Weka environment.

Which module should you use?

- A. Convert to CSV
- B. Convert to Dataset
- C. Convert to ARFF
- D. Convert to SVMLight

Answer: C

Explanation:

Use the Convert to ARFF module in Azure Machine Learning Studio, to convert datasets and results in Azure Machine Learning to the attribute-relation file format used by the Weka toolset. This format is known as ARFF.

The ARFF data specification for Weka supports multiple machine learning tasks, including data preprocessing, classification, and feature selection. In this format, data is organized by entites and their attributes, and is contained in a single text file.

References:

<https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/convert-to-arff>

NEW QUESTION 3

- (Exam Topic 3)

You are analyzing a dataset by using Azure Machine Learning Studio.

YOU need to generate a statistical summary that contains the p value and the unique value count for each feature column.

Which two modules can you users? Each correct answer presents a complete solution. NOTE: Each correct selection is worth one point.

- A. Execute Python Script
- B. Export Count Table
- C. Convert to Indicator Values

- D. Summarize Data
- E. Compute linear Correlation

Answer: BE

Explanation:

The Export Count Table module is provided for backward compatibility with experiments that use the Build Count Table (deprecated) and Count Featurizer (deprecated) modules.

E: Summarize Data statistics are useful when you want to understand the characteristics of the complete dataset. For example, you might need to know: How many missing values are there in each column? How many unique values are there in a feature column?

What is the mean and standard deviation for each column?

The module calculates the important scores for each column, and returns a row of summary statistics for each variable (data column) provided as input.

References:

<https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/export-count-table> <https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/summarize-data>

NEW QUESTION 4

- (Exam Topic 3)

You are analyzing a dataset containing historical data from a local taxi company. You are developing a regression model.

You must predict the fare of a taxi trip.

You need to select performance metrics to correctly evaluate the regression model. Which two metrics can you use? Each correct answer presents a complete solution. NOTE: Each correct selection is worth one point.

- A. an F1 score that is high
- B. an R Squared value close to 1
- C. an R-Squared value close to 0
- D. a Root Mean Square Error value that is high
- E. a Root Mean Square Error value that is low
- F. an F1 score that is low.

Answer: DF

NEW QUESTION 5

- (Exam Topic 3)

You are creating a machine learning model. You have a dataset that contains null rows.

You need to use the Clean Missing Data module in Azure Machine Learning Studio to identify and resolve the null and missing data in the dataset. Which parameter should you use?

- A. Replace with mean
- B. Remove entire column
- C. Remove entire row
- D. Hot Deck

Answer: B

Explanation:

Remove entire row: Completely removes any row in the dataset that has one or more missing values. This is useful if the missing value can be considered randomly missing.

References:

<https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/clean-missing-data>

NEW QUESTION 6

- (Exam Topic 3)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You are a data scientist using Azure Machine Learning Studio.

You need to normalize values to produce an output column into bins to predict a target column. Solution: Apply a Quantiles normalization with a QuantileIndex normalization.

Does the solution meet the GOAL?

- A. Yes
- B. No

Answer: B

Explanation:

Use the Entropy MDL binning mode which has a target column. References:

<https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/group-data-into-bins>

NEW QUESTION 7

- (Exam Topic 3)

You are performing feature engineering on a dataset.

You must add a feature named CityName and populate the column value with the text London.

You need to add the new feature to the dataset.

Which Azure Machine Learning Studio module should you use?

- A. Edit Metadata
- B. Preprocess Text

- C. Execute Python Script
- D. Latent Dirichlet Allocation

Answer: A

Explanation:

Typical metadata changes might include marking columns as features. References:
<https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/edit-metadata>

NEW QUESTION 8

- (Exam Topic 2)

You need to select a feature extraction method. Which method should you use?

- A. Mutual information
- B. Mood's median test
- C. Kendall correlation
- D. Permutation Feature Importance

Answer: C

Explanation:

In statistics, the Kendall rank correlation coefficient, commonly referred to as Kendall's tau coefficient (after the Greek letter τ), is a statistic used to measure the ordinal association between two measured quantities.

It is a supported method of the Azure Machine Learning Feature selection.

Scenario: When you train a Linear Regression module using a property dataset that shows data for property prices for a large city, you need to determine the best features to use in a model. You can choose standard metrics provided to measure performance before and after the feature importance process completes. You must ensure that the distribution of the features across multiple training models is consistent.

References:

<https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/feature-selection-modules>

NEW QUESTION 9

- (Exam Topic 2)

You need to visually identify whether outliers exist in the Age column and quantify the outliers before the outliers are removed.

Which three Azure Machine Learning Studio modules should you use in sequence? To answer, move the appropriate modules from the list of modules to the answer area and arrange them in the correct order.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Create Scatterplot Summarize Data Clip Values

You can use the Clip Values module in Azure Machine Learning Studio, to identify and optionally replace data values that are above or below a specified threshold. This is useful when you want to remove outliers or replace them with a mean, a constant, or other substitute value.

References:

<https://blogs.msdn.microsoft.com/azuredev/2017/05/27/data-cleansing-tools-in-azure-machine-learning/> <https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/clip-values>

NEW QUESTION 10

- (Exam Topic 3)

You use Azure Machine Learning Studio to build a machine learning experiment.

You need to divide data into two distinct datasets. Which module should you use?

- A. Partition and Sample
- B. Assign Data to Clusters
- C. Group Data into Bins
- D. Test Hypothesis Using t-Test

Answer: A

Explanation:

Partition and Sample with the Stratified split option outputs multiple datasets, partitioned using the rules you specified.

References:

<https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/partition-and-sample>

NEW QUESTION 10

- (Exam Topic 3)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You are a data scientist using Azure Machine Learning Studio.

You need to normalize values to produce an output column into bins to predict a target column. Solution: Apply an Equal Width with Custom Start and Stop binning mode.

Does the solution meet the goal?

A. Yes

B. No

Answer: B

Explanation:

Use the Entropy MDL binning mode which has a target column.

References:

<https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/group-data-into-bins>

NEW QUESTION 13

- (Exam Topic 2)

You need to identify the methods for dividing the data according, to the testing requirements.

Which properties should you select? To answer, select the appropriate option-, m the answer area. NOTE: Each correct selection is worth one point.

A. Mastered

B. Not Mastered

Answer: A

Explanation:**NEW QUESTION 15**

- (Exam Topic 1)

You need to resolve the local machine learning pipeline performance issue. What should you do?

A. Increase Graphic Processing Units (GPUs).

B. Increase the learning rate.

C. Increase the training iterations,

D. Increase Central Processing Units (CPUs).

Answer: A

NEW QUESTION 20

- (Exam Topic 1)

You need to implement a scaling strategy for the local penalty detection data. Which normalization type should you use?

- A. Streaming
- B. Weight
- C. Batch
- D. Cosine

Answer: C

Explanation:

Post batch normalization statistics (PBN) is the Microsoft Cognitive Toolkit (CNTK) version of how to evaluate the population mean and variance of Batch Normalization which could be used in inference Original Paper.

In CNTK, custom networks are defined using the BrainScriptNetworkBuilder and described in the CNTK network description language "BrainScript."
Scenario:

Local penalty detection models must be written by using BrainScript. References:
<https://docs.microsoft.com/en-us/cognitive-toolkit/post-batch-normalization-statistics>

NEW QUESTION 21

- (Exam Topic 1)

You need to select an environment that will meet the business and data requirements. Which environment should you use?

- A. Azure HDInsight with Spark MLlib
- B. Azure Cognitive Services
- C. Azure Machine Learning Studio
- D. Microsoft Machine Learning Server

Answer: D

NEW QUESTION 25

- (Exam Topic 1)

You need to implement a new cost factor scenario for the ad response models as illustrated in the performance curve exhibit.
Which technique should you use?

- A. Set the threshold to 0.5 and retrain if weighted Kappa deviates +/- 5% from 0.45.
- B. Set the threshold to 0.05 and retrain if weighted Kappa deviates +/- 5% from 0.5.
- C. Set the threshold to 0.2 and retrain if weighted Kappa deviates +/- 5% from 0.6.
- D. Set the threshold to 0.75 and retrain if weighted Kappa deviates +/- 5% from 0.15.

Answer: A

Explanation:

Scenario:

Performance curves of current and proposed cost factor scenarios are shown in the following diagram:

The ad propensity model uses a cut threshold is 0.45 and retrains occur if weighted Kappa deviated from 0.1 +/- 5%.

NEW QUESTION 30

- (Exam Topic 1)

You need to modify the inputs for the global penalty event model to address the bias and variance issue.

Which three actions should you perform in sequence? To answer, move the appropriate actions from the list of actions to the answer area and arrange them in the correct order.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

NEW QUESTION 31

- (Exam Topic 1)

You need to define a process for penalty event detection.

Which three actions should you perform in sequence? To answer, move the appropriate actions from the list of actions to the answer area and arrange them in the correct order.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

NEW QUESTION 35

- (Exam Topic 3)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You are creating a new experiment in Azure Learning learning Studio.

One class has a much smaller number of observations than the other classes in the training

You need to select an appropriate data sampling strategy to compensate for the class imbalance. Solution: You use the Synthetic Minority Oversampling Technique (SMOTE) sampling mode. Does the solution meet the goal?

- A. Yes
- B. No

Answer: A

Explanation:

SMOTE is used to increase the number of underrepresented cases in a dataset used for machine learning. SMOTE is a better way of increasing the number of rare cases than simply duplicating existing cases.

References:

<https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/smote>

NEW QUESTION 36

- (Exam Topic 3)

You plan to create a speech recognition deep learning model. The model must support the latest version of Python.

You need to recommend a deep learning framework for speech recognition to include in the Data Science Virtual Machine (DSVM).

What should you recommend?

- A. Apache Drill
- B. Tensorflow
- C. Rattle
- D. Weka

Answer: B

Explanation:

TensorFlow is an open source library for numerical computation and large-scale machine learning. It uses Python to provide a convenient front-end API for building applications with the framework

TensorFlow can train and run deep neural networks for handwritten digit classification, image recognition, word embeddings, recurrent neural networks, sequence-to-sequence models for machine translation, natural language processing, and PDE (partial differential equation) based simulations.

References:

<https://www.infoworld.com/article/3278008/what-is-tensorflow-the-machine-learning-library-explained.html>

NEW QUESTION 38

- (Exam Topic 3)

You plan to use a Data Science Virtual Machine (DSVM) with the open source deep learning frameworks Caffe2 and Theano. You need to select a pre configured DSVM to support the framework.

What should you create?

- A. Data Science Virtual Machine for Linux (CentOS)
- B. Data Science Virtual Machine for Windows 2012
- C. Data Science Virtual Machine for Windows 2016
- D. Geo AI Data Science Virtual Machine with ArcGIS
- E. Data Science Virtual Machine for Linux (Ubuntu)

Answer: E

NEW QUESTION 40

- (Exam Topic 3)

You are performing sentiment analysis using a CSV file that includes 12,000 customer reviews written in a short sentence format. You add the CSV file to Azure Machine Learning Studio and configure it as the starting point dataset of an experiment. You add the Extract N-Gram Features from Text module to the experiment to extract key phrases from the customer review column in the dataset.

You must create a new n-gram dictionary from the customer review text and set the maximum n-gram size to trigrams.

What should you select? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Vocabulary mode: Create

For Vocabulary mode, select Create to indicate that you are creating a new list of n-gram features. N-Grams size: 3

For N-Grams size, type a number that indicates the maximum size of the n-grams to extract and store. For example, if you type 3, unigrams, bigrams, and trigrams will be created.

Weighting function: Leave blank

The option, Weighting function, is required only if you merge or update vocabularies. It specifies how terms in the two vocabularies and their scores should be weighted against each other.

References:

<https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/extract-n-gram-features-from>

NEW QUESTION 42

- (Exam Topic 3)

You are analyzing the asymmetry in a statistical distribution.

The following image contains two density curves that show the probability distribution of two datasets.

Use the drop-down menus to select the answer choice that answers each question based on the information presented in the graphic.

NOTE: Each correct selection is worth one point.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Box 1: Positive skew

Positive skew values means the distribution is skewed to the right. Box 2: Negative skew

Negative skewness values mean the distribution is skewed to the left. References:

<https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/compute-elementary-statistic>

NEW QUESTION 47

- (Exam Topic 3)

You use Data Science Virtual Machines (DSVMs) for Windows and Linux in Azure. You need to access the DSVMs.

Which utilities should you use? To answer, select the appropriate options in the answer area. NOTE: Each correct selection is worth one point.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

NEW QUESTION 52

- (Exam Topic 3)

You create a classification model with a dataset that contains 100 samples with Class A and 10,000 samples with Class B

The variation of Class B is very high. You need to resolve imbalances. Which method should you use?

- A. Partition and Sample
- B. Cluster Centroids
- C. Tomek links
- D. Synthetic Minority Oversampling Technique (SMOTE)

Answer: D

NEW QUESTION 53

- (Exam Topic 3)

You plan to build a team data science environment. Data for training models in machine learning pipelines will be over 20 GB in size. You have the following requirements:

Models must be built using Caffe2 or Chainer frameworks.

Data scientists must be able to use a data science environment to build the machine learning pipelines and train models on their personal devices in both connected and disconnected network environments.

Personal devices must support updating machine learning pipelines when connected to a network. You need to select a data science environment. Which environment should you use?

- A. Azure Machine Learning Service
- B. Azure Machine Learning Studio
- C. Azure Databricks
- D. Azure Kubernetes Service (AKS)

Answer: A

Explanation:

The Data Science Virtual Machine (DSVM) is a customized VM image on Microsoft's Azure cloud built specifically for doing data science. Caffe2 and Chainer are supported by DSVM.

DSVM integrates with Azure Machine Learning.

NEW QUESTION 55

- (Exam Topic 3)

You create a binary classification model using Azure Machine Learning Studio.

You must use a Receiver Operating Characteristic (ROC) curve and an F1 score to evaluate the model. You need to create the required business metrics.

How should you complete the experiment? To answer, select the appropriate options in the dialog box in the answer area.

NOTE: Each correct selection is worth one point.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

NEW QUESTION 58

- (Exam Topic 3)

You are using C-Support Vector classification to do a multi-class classification with an unbalanced training dataset. The C-Support Vector classification using Python code shown below:

You need to evaluate the C-Support Vector classification code.

Which evaluation statement should you use? To answer, select the appropriate options in the answer area. NOTE: Each correct selection is worth one point.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Box 1: Automatically adjust weights inversely proportional to class frequencies in the input data

The “balanced” mode uses the values of y to automatically adjust weights inversely proportional to class frequencies in the input data as $n_{\text{samples}} / (n_{\text{classes}} * \text{np.bincount}(y))$.

Box 2: Penalty parameter

Parameter: C : float, optional (default=1.0)

Penalty parameter C of the error term. References:

<https://scikit-learn.org/stable/modules/generated/sklearn.svm.SVC.html>

NEW QUESTION 59

- (Exam Topic 3)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You are creating a new experiment in Azure Machine Learning Studio.

One class has a much smaller number of observations than the other classes in the training set. You need to select an appropriate data sampling strategy to compensate for the class imbalance. Solution: You use the Stratified split for the sampling mode.

Does the solution meet the goal?

A. Yes

B. No

Answer: B

Explanation:

Instead use the Synthetic Minority Oversampling Technique (SMOTE) sampling mode.

Note: SMOTE is used to increase the number of underrepresented cases in a dataset used for machine learning. SMOTE is a better way of increasing the number of rare cases than simply duplicating existing cases.

References:

<https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/smote>

NEW QUESTION 60

- (Exam Topic 3)

You are creating a machine learning model. You need to identify outliers in the data.

Which two visualizations can you use? Each correct answer presents a complete solution.

NOTE: Each correct selection is worth one point. NOTE: Each correct selection is worth one point.

A. box plot

B. scatter

C. random forest diagram

D. Venn diagram

E. ROC curve

Answer: AB

Explanation:

The box-plot algorithm can be used to display outliers.

One other way to quickly identify Outliers visually is to create scatter plots. References:

<https://blogs.msdn.microsoft.com/azuredev/2017/05/27/data-cleansing-tools-in-azure-machine-learning/>

NEW QUESTION 64

- (Exam Topic 3)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You are creating a new experiment in Azure Machine Learning Studio.

One class has a much smaller number of observations than tin- other classes in the training set. You need to select an appropriate data sampling strategy to compensate for the class imbalance. Solution: You use the Principal Components Analysis (PCA) sampling mode.

Does the solution meet the goal?

A. Yes

B. No

Answer: B

NEW QUESTION 68

- (Exam Topic 3)

You are performing a filter based feature selection for a dataset 10 build a multi class classifies by using Azure Machine Learning Studio.

The dataset contains categorical features that are highly correlated to the output label column.

You need to select the appropriate feature scoring statistical method to identify the key predictors. Which method should you use?

A. Chi-squared

B. Spearman correlation

C. Kendall correlation

D. Person correlation

Answer: D

Explanation:

Pearson's correlation statistic, or Pearson's correlation coefficient, is also known in statistical models as the r value. For any two variables, it returns a value that indicates the strength of the correlation

Pearson's correlation coefficient is the test statistics that measures the statistical relationship, or association, between two continuous variables. It is known as the best method of measuring the association between variables of interest because it is based on the method of covariance. It gives information about the magnitude of the association, or correlation, as well as the direction of the relationship.

Reference:

<https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/filter-based-feature-selection> <https://www.statisticssolutions.com/pearsons->

correlation-coefficient/

NEW QUESTION 72

- (Exam Topic 3)

You have a dataset contains 2,000 rows. You are building a machine learning classification model by using Azure Machine Learning Studio. You add a Partition and Sample module to the experiment.

You need to configure the module. You must meet the following requirements:

- Divide the data into subsets.
- Assign the rows into folds using a round-robin method.
- Allow rows in the dataset to be reused.

How should you configure the module? To answer select the appropriate Options in the dialog box in the answer area.

NOTE: Each correct selection is worth one point.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

NEW QUESTION 77

- (Exam Topic 3)

You are building a recurrent neural network to perform a binary classification. You review the training loss, validation loss, training accuracy, and validation accuracy for each training epoch.

You need to analyze model performance.

Which observation indicates that the classification model is over fitted?

- A. The training loss stays constant and the validation loss stays on a constant value and close to the training loss value when training the model.
- B. The training loss increases while the validation loss decreases when training the model.
- C. The training loss decreases while the validation loss increases when training the model.
- D. The training loss stays constant and the validation loss decreases when training the model.

Answer: B

NEW QUESTION 78

- (Exam Topic 3)

You are a data scientist creating a linear regression model.

You need to determine how closely the data fits the regression line. Which metric should you review?

- A. Coefficient of determination
- B. Recall
- C. Precision
- D. Mean absolute error
- E. Root Mean Square Error

Answer: A

Explanation:

Coefficient of determination, often referred to as R², represents the predictive power of the model as a value between 0 and 1. Zero means the model is random (explains nothing); 1 means there is a perfect fit. However, caution should be used in interpreting R² values, as low values can be entirely normal and high values can be suspect.

References:

<https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/evaluate-model>

NEW QUESTION 82

- (Exam Topic 3)

You are evaluating a completed binary classification machine. You need to use the precision as the evaluation metric.

Which visualization should you use?

- A. scatter plot
- B. coefficient of determination
- C. Receiver Operating Characteristic (ROC) curve
- D. Gradient descent

Answer: C

NEW QUESTION 85

- (Exam Topic 3)

You are developing deep learning models to analyze semi-structured, unstructured, and structured data types. You have the following data available for model building:

Video recordings of sporting events

Transcripts of radio commentary about events

Logs from related social media feeds captured during sporting events

You need to select an environment for creating the model.

Which environment should you use?

- A. Azure Cognitive Services
- B. Azure Data Lake Analytics
- C. Azure HDInsight with Spark MLlib
- D. Azure Machine Learning Studio

Answer: A

Explanation:

Azure Cognitive Services expand on Microsoft's evolving portfolio of machine learning APIs and enable developers to easily add cognitive features – such as emotion and video detection; facial, speech, and vision recognition; and speech and language understanding – into their applications. The goal of Azure Cognitive Services is to help developers create applications that can see, hear, speak, understand, and even begin to reason. The catalog of services within Azure Cognitive Services can be categorized into five main pillars - Vision, Speech, Language, Search, and Knowledge.

References:

<https://docs.microsoft.com/en-us/azure/cognitive-services/welcome>

NEW QUESTION 87

- (Exam Topic 3)

You are building recurrent neural network to perform a binary classification.

The training loss, validation loss, training accuracy, and validation accuracy of each training epoch has been provided. You need to identify whether the classification model is over fitted.

Which of the following is correct?

- A. The training loss increases while the validation loss decreases when training the model.
- B. The training loss decreases while the validation loss increases when training the model.
- C. The training loss stays constant and the validation loss decreases when training the model.
- D. The training loss stays constant and the validation loss stays on a constant value and close to the training loss value when training the model.

Answer: B

Explanation:

An overfit model is one where performance on the train set is good and continues to improve, whereas performance on the validation set improves to a point and then begins to degrade.

References:

<https://machinelearningmastery.com/diagnose-overfitting-underfitting-lstm-models/>

NEW QUESTION 91

- (Exam Topic 3)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You are analyzing a numerical dataset which contains missing values in several columns.

You must clean the missing values using an appropriate operation without affecting the dimensionality of the feature set.

You need to analyze a full dataset to include all values.

Solution: Replace each missing value using the Multiple Imputation by Chained Equations (MICE) method. Does the solution meet the goal?

A. Yes

B. NO

Answer: A

Explanation:

Replace using MICE: For each missing value, this option assigns a new value, which is calculated by using a method described in the statistical literature as "Multivariate Imputation using Chained Equations" or "Multiple Imputation by Chained Equations". With a multiple imputation method, each variable with missing data is modeled conditionally using the other variables in the data before filling in the missing values.

Note: Multivariate imputation by chained equations (MICE), sometimes called “fully conditional specification” or “sequential regression multiple imputation” has emerged in the statistical literature as one principled method of addressing missing data. Creating multiple imputations, as opposed to single imputations, accounts for the statistical uncertainty in the imputations. In addition, the chained equations approach is very flexible and can handle variables of varying types (e.g., continuous or binary) as well as complexities such as bounds or survey skip patterns.

References: <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC3074241/>

<https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/clean-missing-data>

NEW QUESTION 94

- (Exam Topic 3)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You are analyzing a numerical dataset which contain missing values in several columns.

You must clean the missing values using an appropriate operation without affecting the dimensionality of the feature set.

You need to analyze a full dataset to include all values.

Solution: Use the last Observation Carried Forward (IOCF) method to impute the missing data points. Does the solution meet the goal?

A. Yes

B. No

Answer: B

Explanation:

Instead use the Multiple Imputation by Chained Equations (MICE) method.

Replace using MICE: For each missing value, this option assigns a new value, which is calculated by using a method described in the statistical literature as "Multivariate Imputation using Chained Equations" or "Multiple Imputation by Chained Equations". With a multiple imputation method, each variable with missing data is modeled conditionally using the other variables in the data before filling in the missing values.

Note: Last observation carried forward (LOCF) is a method of imputing missing data in longitudinal studies. If a person drops out of a study before it ends, then his or her last observed score on the dependent variable is used for all subsequent (i.e., missing) observation points. LOCF is used to maintain the sample size and to reduce the bias caused by the attrition of participants in a study.

References:

<https://methods.sagepub.com/reference/encyc-of-research-design/n211.xml> <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC3074241/>

NEW QUESTION 98

- (Exam Topic 3)

You create an experiment in Azure Machine Learning Studio. You add a training dataset that contains 10,000 rows. The first 9,000 rows represent class 0 (90 percent).

The remaining 1,000 rows represent class 1 (10 percent).

The training set is imbalances between two classes. You must increase the number of training examples for class 1 to 4,000 by using 5 data rows. You add the Synthetic Minority Oversampling Technique (SMOTE) module to the experiment.

You need to configure the module.

Which values should you use? To answer, select the appropriate options in the dialog box in the answer area. NOTE: Each correct selection is worth one point.

- A. Mastered
B. Not Mastered

Answer: A

Explanation:

Box 1: 300

You type 300 (%), the module triples the percentage of minority cases (3000) compared to the original dataset (1000).

Box 2: 5

We should use 5 data rows.

Use the Number of nearest neighbors option to determine the size of the feature space that the SMOTE algorithm uses when in building new cases. A nearest neighbor is a row of data (a case) that is very similar to some target case. The distance between any two cases is measured by combining the weighted vectors of all features.

By increasing the number of nearest neighbors, you get features from more cases.

By keeping the number of nearest neighbors low, you use features that are more like those in the original sample.

References:

<https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/smote>

NEW QUESTION 101

- (Exam Topic 3)

You are evaluating a Python NumPy array that contains six data points defined as follows: data = [10, 20, 30, 40, 50, 60]

You must generate the following output by using the k-fold algorithm implantation in the Python Scikit-learn machine learning library:

train: [10 40 50 60], test: [20 30]

train: [20 30 40 60], test: [10 50]

train: [10 20 30 50], test: [40 60]

You need to implement a cross-validation to generate the output.

How should you complete the code segment? To answer, select the appropriate code segment in the dialog box in the answer area.

NOTE: Each correct selection is worth one point.

- A. Mastered
B. Not Mastered

Answer: A

Explanation:

Box 1: k-fold

Box 2: 3

K-F olds cross-validator provides train/test indices to split data in train/test sets. Split dataset into k consecutive folds (without shuffling by default).

The parameter n_splits (int, default=3) is the number of folds. Must be at least 2. Box 3: data

Example: Example:

```
>>>
```

```
>>> from sklearn.model_selection import KFold
```

```
>>> X = np.array([[1, 2], [3, 4], [1, 2], [3, 4]])
```

```
>>> y = np.array([1, 2, 3, 4])
```

```
>>> kf = KFold(n_splits=2)
```

```
>>> kf.get_n_splits(X) 2
```

```
>>> print(kf)
```

```
KFold(n_splits=2, random_state=None, shuffle=False)
```

```
>>> for train_index, test_index in kf.split(X): print("TRAIN:", train_index, "TEST:", test_index) X_train, X_test = X[train_index], X[test_index] y_train, y_test =
```

```
y[train_index], y[test_index] TRAIN: [2 3] TEST: [0 1]
```

```
TRAIN: [0 1] TEST: [2 3]
```

References:

https://scikit-learn.org/stable/modules/generated/sklearn.model_selection.KFold.html

NEW QUESTION 103

- (Exam Topic 3)

You are solving a classification task.

You must evaluate your model on a limited data sample by using k-fold cross validation. You start by configuring a k parameter as the number of splits.

You need to configure the k parameter for the cross-validation. Which value should you use?

- A. k=0.5
- B. k=0
- C. k=5
- D. k=1

Answer: C

Explanation:

Leave One Out (LOO) cross-validation

Setting $K = n$ (the number of observations) yields n-fold and is called leave-one out cross-validation (LOO), a special case of the K-fold approach.

LOO CV is sometimes useful but typically doesn't shake up the data enough. The estimates from each fold are highly correlated and hence their average can have high variance.

This is why the usual choice is $K=5$ or 10. It provides a good compromise for the bias-variance tradeoff.

NEW QUESTION 106

- (Exam Topic 3)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You are analyzing a numerical dataset which contains missing values in several columns.

You must clean the missing values using an appropriate operation without affecting the dimensionality of the feature set.

You need to analyze a full dataset to include all values.

Solution: Remove the entire column that contains the missing data point. Does the solution meet the goal?

- A. Yes
- B. No

Answer: B

Explanation:

Use the Multiple Imputation by Chained Equations (MICE) method. References: <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC3074241/>

<https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/clean-missing-data>

NEW QUESTION 111

- (Exam Topic 3)

You have a model with a large difference between the training and validation error values. You must create a new model and perform cross-validation.

You need to identify a parameter set for the new model using Azure Machine Learning Studio.

Which module you should use for each step? To answer, drag the appropriate modules to the correct steps. Each module may be used once or more than once, or not at all. You may need to drag the split bar between panes or scroll to view content.

NOTE: Each correct selection is worth one point.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Box 1: Split data

Box 2: Partition and Sample

Box 3: Two-Class Boosted Decision Tree

Box 4: Tune Model Hyperparameters

Integrated train and tune: You configure a set of parameters to use, and then let the module iterate over multiple combinations, measuring accuracy until it finds a "best" model. With most learner modules, you can choose which parameters should be changed during the training process, and which should remain fixed.

We recommend that you use Cross-Validate Model to establish the goodness of the model given the specified parameters. Use Tune Model Hyperparameters to identify the optimal parameters.

References:

<https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/partition-and-sample>

NEW QUESTION 116

- (Exam Topic 3)

You create a binary classification model by using Azure Machine Learning Studio.

You must tune hyperparameters by performing a parameter sweep of the model. The parameter sweep must meet the following requirements:

iterate all possible combinations of hyperparameters

minimize computing resources required to perform the sweep

You need to perform a parameter sweep of the model.

Which parameter sweep mode should you use?

- A. Random sweep
- B. Sweep clustering
- C. Entire grid
- D. Random grid

E. Random seed

Answer: D

Explanation:

Maximum number of runs on random grid: This option also controls the number of iterations over a random sampling of parameter values, but the values are not generated randomly from the specified range; instead, a matrix is created of all possible combinations of parameter values and a random sampling is taken over the matrix. This method is more efficient and less prone to regional oversampling or undersampling.

If you are training a model that supports an integrated parameter sweep, you can also set a range of seed values to use and iterate over the random seeds as well. This is optional, but can be useful for avoiding bias introduced by seed selection.

NEW QUESTION 120

- (Exam Topic 3)

You are building a machine learning model for translating English language textual content into French language textual content.

You need to build and train the machine learning model to learn the sequence of the textual content. Which type of neural network should you use?

- A. Multilayer Perceptions (MLPs)
- B. Convolutional Neural Networks (CNNs)
- C. Recurrent Neural Networks (RNNs)
- D. Generative Adversarial Networks (GANs)

Answer: C

Explanation:

To translate a corpus of English text to French, we need to build a recurrent neural network (RNN).

Note: RNNs are designed to take sequences of text as inputs or return sequences of text as outputs, or both. They're called recurrent because the network's hidden layers have a loop in which the output and cell state from each time step become inputs at the next time step. This recurrence serves as a form of memory. It allows contextual information to flow through the network so that relevant outputs from previous time steps can be applied to network operations at the current time step.

References:

<https://towardsdatascience.com/language-translation-with-rnns-d84d43b40571>

NEW QUESTION 125

- (Exam Topic 3)

You are producing a multiple linear regression model in Azure Machine learning Studio. Several independent variables are highly correlated.

You need to select appropriate methods for conducting elective feature engineering on all the data.

Which three actions should you perform in sequence? To answer, move the appropriate Actions from the list of actions to the answer area and arrange them in the correct order.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

NEW QUESTION 127

- (Exam Topic 3)

You are creating a new experiment in Azure Machine Learning Studio. You have a small dataset that has missing values in many columns. The data does not require the application of predictors for each column. You plan to use the Clean Missing Data module to handle the missing data.

You need to select a data cleaning method. Which method should you use?

- A. Synthetic Minority Oversampling Technique (SMOTE)
- B. Replace using MICE
- C. Replace using; Probabilistic PCA
- D. Normalization

Answer: A

NEW QUESTION 128

- (Exam Topic 3)

You create an experiment in Azure Machine Learning Studio- You add a training dataset that contains 10,000 rows. The first 9,000 rows represent class 0 (90 percent). The first 1,000 rows represent class 1 (10 percent).

The training set is unbalanced between two Classes. You must increase the number of training examples for class 1 to 4,000 by using data rows. You add the Synthetic Minority Oversampling Technique (SMOTE) module to the experiment.

You need to configure the module.

Which values should you use? To answer, select the appropriate options in the dialog box in the answer area. NOTE: Each correct selection is worth one point.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

NEW QUESTION 133

- (Exam Topic 3)

You are retrieving data from a large datastore by using Azure Machine Learning Studio.

You must create a subset of the data for testing purposes using a random sampling seed based on the system clock.

You add the Partition and Sample module to your experiment. You need to select the properties for the module.

Which values should you select? To answer, select the appropriate options in the answer area. NOTE: Each correct selection is worth one point.

- A. Mastered
B. Not Mastered

Answer: A

Explanation:

Box 1: Sampling Create a sample of data

This option supports simple random sampling or stratified random sampling. This is useful if you want to create a smaller representative sample dataset for testing.

1. Add the Partition and Sample module to your experiment in Studio, and connect the dataset.

2. Partition or sample mode: Set this to Sampling.

3. Rate of sampling. See box 2 below. Box 2: 0

3. Rate of sampling. Random seed for sampling: Optionally, type an integer to use as a seed value.

This option is important if you want the rows to be divided the same way every time. The default value is 0, meaning that a starting seed is generated based on the system clock. This can lead to slightly different results each time you run the experiment.

References:

<https://docs.microsoft.com/en-us/azure/machine-learning/studio-module-reference/partition-and-sample>

NEW QUESTION 136

- (Exam Topic 3)

You are evaluating a completed binary classification machine learning model. You need to use the precision as the valuation metric.

Which visualization should you use?

- A. Binary classification confusion matrix
B. box plot
C. Gradient descent
D. coefficient of determination

Answer: A

Explanation:

References:

<https://machinelearningknowledge.ai/confusion-matrix-and-performance-metrics-machine-learning/>

NEW QUESTION 139

- (Exam Topic 3)

You are creating a machine learning model in Python. The provided dataset contains several numerical columns and one text column. The text column represents a product's category. The product category will always be one of the following:

Bikes
Cars
Vans
Boats

You are building a regression model using the scikit-learn Python package.

You need to transform the text data to be compatible with the scikit-learn Python package.

How should you complete the code segment? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

- A. Mastered
B. Not Mastered

Answer: A

Explanation:

Box 1: pandas as df

Pandas takes data (like a CSV or TSV file, or a SQL database) and creates a Python object with rows and columns called data frame that looks very similar to table in a statistical software (think Excel or SPSS for example).

Box 2: transpose[ProductCategoryMapping] Reshape the data from the pandas Series to columns. Reference:

<https://datascienceplus.com/linear-regression-in-python/>

NEW QUESTION 143

- (Exam Topic 3)

You are implementing a machine learning model to predict stock prices. The model uses a PostgreSQL database and requires GPU processing.

You need to create a virtual machine that is pre-configured with the required tools. What should you do?

- A. Create a Data Science Virtual Machine (DSVM) Windows edition.
- B. Create a Geo AI Data Science Virtual Machine (Geo-DSVM) Windows edition.
- C. Create a Deep Learning Virtual Machine (DLVM) Linux edition.
- D. Create a Deep Learning Virtual Machine (DLVM) Windows edition.
- E. Create a Data Science Virtual Machine (DSVM) Linux edition.

Answer: E

NEW QUESTION 148

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your DP-100 Exam with Our Prep Materials Via below:

<https://www.certleader.com/DP-100-dumps.html>