



Amazon

Exam Questions AWS-SysOps

Amazon AWS Certified SysOps Administrator - Associate

NEW QUESTION 1

- (Topic 1)

A media company produces new video files on-premises every day with a total size of around 100GBS after compression All files have a size of 1 -2 GB and need to be uploaded to Amazon S3 every night in a fixed time window between 3am and 5am Current upload takes almost 3 hours, although less than half of the available bandwidth is used.

What step(s) would ensure that the file uploads are able to complete in the allotted time window?

- A. Increase your network bandwidth to provide faster throughput to S3
- B. Upload the files in parallel to S3
- C. Pack all files into a single archive, upload it to S3, then extract the files in AWS
- D. Use AWS Import/Export to transfer the video files

Answer: B

Explanation:

Reference:

<http://aws.amazon.com/importexport/faqs/>

NEW QUESTION 2

- (Topic 1)

What would happen to an RDS (Relational Database Service) multi-Availability Zone deployment of the primary OB instance fails?

- A. The IP of the primary DB instance is switched to the standby OB instance
- B. The RDS (Relational Database Service) DB instance reboots
- C. A new DB instance is created in the standby availability zone
- D. The canonical name record (CNAME) is changed from primary to standby

Answer: D

NEW QUESTION 3

- (Topic 1)

Your EC2-Based Multi-tier application includes a monitoring instance that periodically makes application -level read only requests of various application components and if any of those fail more than three times 30 seconds calls CloudWatch to fire an alarm, and the alarm notifies your operations team by email and SMS of a possible application health problem. However, you also need to watch the watcher -the monitoring instance itself - and be notified if it becomes unhealthy.

Which of the following is a simple way to achieve that goal?

- A. Run another monitoring instance that pings the monitoring instance and fires a could watch alarm that notifies your operations team should the primary monitoring instance become unhealth
- B. Set a CloudWatch alarm based on EC2 system and instance status checks and have the alarm notify your operations team of any detected problem with the monitoring instanc
- C. Set a CloudWatch alarm based on the CPU utilization of the monitoring instance and have the alarm notify your operations team if C r the CPU usage exceeds 50% few more than one minute: then have your monitoring application go into a CPU-bound loop should it Detect any application problem
- D. Have the monitoring instances post messages to an SOS queue and then dequeue those messages on another instance should the queue cease to have new messages, the second instance should first terminate the original monitoring instance start anotherbackup monitoring instance and assume (he role of the previous monitoring instance and beginning adding messages to the SQSqueue

Answer: D

NEW QUESTION 4

- (Topic 1)

Which of the following statements about this S3 bucket policy is true?

```
{
  "Id": "IPAllowPolicy",
  "Statement": [
    {
      "Sid": "IPAllow",
      "Action": "s3:*",
      "Effect": "Allow",
      "Resource": "arn:aws:s3:::mybucket/*",
      "Condition": {
        "IpAddress": {
          "aws:SourceIp": "192.168.100.0/24"
        },
        "NotIpAddress": {
          "aws:SourceIp": "192.168.100.188/32"
        }
      }
    }
  ],
  "Principal": {
    "AWS": [
      "*"
    ]
  }
}
```

- A. Denies the server with the IP address 192.168.100.0 full access to the "mybucket" bucket
- B. Denies the server with the IP address 192.168.100.188 full access to the "mybucket" bucket
- C. Grants all the servers within the 192.168.100.0/24 subnet full access to the "mybucket" bucket
- D. Grants all the servers within the 192.168.100.188/32 subnet full access to the "mybucket" bucket

Answer: B

NEW QUESTION 5

- (Topic 1)

When preparing for a compliance assessment of your system built inside of AWS. what are three best-practices for you to prepare for an audit?
Choose 3 answers

- A. Gather evidence of your IT operational controls
- B. Request and obtain applicable third-party audited AWS compliance reports and certifications
- C. Request and obtain a compliance and security tour of an AWS data center for a pre-assessment security review
- D. Request and obtain approval from AWS to perform relevant network scans and in-depth penetration tests of your system's Instances and endpoints
- E. Schedule meetings with AWS's third-party auditors to provide evidence of AWS compliance that maps to your control objectives

Answer: ABD

NEW QUESTION 6

- (Topic 1)

You have a web-style application with a stateless but CPU and memory-intensive web tier running on a cc2.8xlarge EC2 instance inside of a VPC. The instance when under load is having problems returning requests within the SLA as defined by your business. The application maintains its state in a DynamoDB table, but the data tier is properly provisioned and responses are consistently fast.
How can you best resolve the issue of the application responses not meeting your SLA?

- A. Add another cc2.8xlarge application instance, and put both behind an Elastic Load Balancer
- B. Move the cc2.8xlarge to the same Availability Zone as the DynamoDB table
- C. Cache the database responses in ElastiCache for more rapid access
- D. Move the database from DynamoDB to RDS MySQL in scale-out read-replica configuration

Answer: B

Explanation:

Reference:

<http://aws.amazon.com/elasticmapreduce/faqs/>

NEW QUESTION 7

- (Topic 1)

You are managing a legacy application inside VPC with hard-coded IP addresses in its configuration.

Which two mechanisms will allow the application to failover to new instances without the need for reconfiguration? Choose 2 answers

- A. Create an ELB to reroute traffic to a failover instance
- B. Create a secondary ENI that can be moved to a failover instance
- C. Use Route53 health checks to fail traffic over to a failover instance
- D. Assign a secondary private IP address to the primary ENI that can be moved to a failover instance

Answer: AD

NEW QUESTION 8

- (Topic 1)

You have set up individual AWS accounts for each project. You have been asked to make sure your AWS Infrastructure costs do not exceed the budget set per project for each month.

Which of the following approaches can help ensure that you do not exceed the budget each month?

- A. Consolidate your accounts so you have a single bill for all accounts and projects
- B. Set up auto-scaling with CloudWatch alarms using SNS to notify you when you are running too many instances in a given account
- C. Set up CloudWatch billing alerts for all AWS resources used by each project, with a notification occurring when the amount for each resource tagged to a particular project matches the budget allocated to the project
- D. Set up CloudWatch billing alerts for all AWS resources used by each account, with email notifications when it hits 50%, 80% and 90% of its budgeted monthly spend

Answer: C

NEW QUESTION 9

- (Topic 1)

Your entire AWS infrastructure lives inside of one Amazon VPC. You have an infrastructure monitoring application running on an Amazon instance in Availability Zone (AZ) A of the region, and another application instance running in AZ B. The monitoring application needs to make use of ICMP ping to confirm network reachability of the instance hosting the application.

Can you configure the security groups for these instances to only allow the ICMP ping to pass from the monitoring instance to the application instance and nothing else? If so, how?

- A. No. Two instances in two different AZs can't talk directly to each other via ICMP ping as that protocol is not allowed across subnet (i.e. broadcast) boundaries
- B. Yes. Both the monitoring instance and the application instance have to be a part of the same security group, and that security group needs to allow inbound ICMP
- C. Yes. The security group for the monitoring instance needs to allow outbound ICMP and the application instance's security group needs to allow inbound ICMP
- D. Yes. Both the monitoring instance's security group and the application instance's security group need to allow both inbound and outbound ICMP ping packets

since ICMP is not a connection-oriented protocol

Answer: D

NEW QUESTION 10

- (Topic 1)

You are running a web-application on AWS consisting of the following components an Elastic Load Balancer (ELB) an Auto-Scaling Group of EC2 instances running Linux/PHP/Apache, and Relational DataBase Service (RDS) MySQL.
Which security measures fall into AWS's responsibility?

- A. Protect the EC2 instances against unsolicited access by enforcing the principle of least-privilege access
- B. Protect against IP spoofing or packet sniffing
- C. Assure all communication between EC2 instances and ELB is encrypted
- D. Install latest security patches on EL
- E. RDS and EC2 instances

Answer: B

NEW QUESTION 10

- (Topic 1)

When assessing an organization's use of AWS API access credentials which of the following three credentials should be evaluated?
Choose 3 answers

- A. Key pairs
- B. Console passwords
- C. Access keys
- D. Signing certificates
- E. Security Group memberships

Answer: ACD

Explanation:

Reference:

http://media.amazonwebservices.com/AWS_Operational_Checklists.pdf

NEW QUESTION 11

- (Topic 1)

You have a web application leveraging an Elastic Load Balancer (ELB) in front of the web servers deployed using an Auto Scaling Group. Your database is running on Relational Database Service (RDS). The application serves out technical articles and responses to them. In general, there are more views of an article than there are responses to the article. On occasion, an article on the site becomes extremely popular, resulting in significant traffic increases that cause the site to go down. What could you do to help alleviate the pressure on the infrastructure while maintaining availability during these events?
Choose 3 answers

- A. Leverage CloudFront for the delivery of the article
- B. Add RDS read-replicas for the read traffic going to your relational database
- C. Leverage ElastiCache for caching the most frequently used data
- D. Use SQS to queue up the requests for the technical posts and deliver them out of the queue
- E. Use Route53 health checks to fail over to an S3 bucket for an error page

Answer: ACE

NEW QUESTION 13

- (Topic 1)

You are running a database on an EC2 instance, with the data stored on Elastic Block Store (EBS) for persistence. At times throughout the day, you are seeing large variance in the response times of the database queries. Looking into the instance with the `iostat` command, you see a lot of wait time on the disk volume that the database's data is stored on. What two ways can you improve the performance of the database's storage while maintaining the current persistence of the data?
Choose 2 answers

- A. Move to an SSD backed instance
- B. Move the database to an EBS-Optimized Instance
- C. Use Provisioned IOPS EBS
- D. Use the ephemeral storage on an m2.xlarge Instance Instead

Answer: AB

NEW QUESTION 16

- (Topic 1)

What is a placement group?

- A. A collection of Auto Scaling groups in the same Region
- B. Feature that enables EC2 instances to interact with each other via high bandwidth, low latency connections
- C. A collection of Elastic Load Balancers in the same Region or Availability Zone
- D. A collection of authorized CloudFront edge locations for a distribution

Answer: B

Explanation:

Reference:

<http://aws.amazon.com/ec2/faqs/>

NEW QUESTION 20

- (Topic 1)

Which of the following requires a custom CloudWatch metric to monitor?

- A. Data transfer of an EC2 instance
- B. Disk usage activity of an EC2 instance
- C. Memory Utilization of an EC2 instance
- D. CPU Utilization of an EC2 instance

Answer: C

Explanation:

Reference:

<http://aws.amazon.com/cloudwatch/>

NEW QUESTION 24

- (Topic 1)

When an EC2 EBS-backed (EBS root) instance is stopped, what happens to the data on any ephemeral store volumes?

- A. Data will be deleted and will no longer be accessible
- B. Data is automatically saved in an EBS volume
- C. Data is automatically saved as an EBS snapshot
- D. Data is unavailable until the instance is restarted

Answer: D

NEW QUESTION 26

- (Topic 1)

Your organization's security policy requires that all privileged users either use frequently rotated passwords or one-time access credentials in addition to username/password.

Which two of the following options would allow an organization to enforce this policy for AWS users?

Choose 2 answers

- A. Configure multi-factor authentication for privileged IAM users
- B. Create IAM users for privileged accounts
- C. Implement identity federation between your organization's Identity provider leveraging the IAM Security Token Service
- D. Enable the IAM single-use password policy option for privileged users

Answer: CD

NEW QUESTION 30

- (Topic 1)

Which of the following are characteristics of Amazon VPC subnets?

Choose 2 answers

- A. Each subnet maps to a single Availability Zone
- B. A CIDR block mask of /25 is the smallest range supported
- C. Instances in a private subnet can communicate with the internet only if they have an Elastic IP
- D. By default, all subnets can route between each other, whether they are private or public
- E. Each subnet spans at least 2 Availability zones to provide a high-availability environment

Answer: CE

NEW QUESTION 35

- (Topic 1)

When an EC2 instance that is backed by an S3-based AMI is terminated, what happens to the data on the root volume?

- A. Data is automatically saved as an EBS volume
- B. Data is automatically saved as an EBS snapshot
- C. Data is automatically deleted
- D. Data is unavailable until the instance is restarted

Answer: C

Explanation:

Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ComponentsAMIs.html>

NEW QUESTION 38

- (Topic 1)

You receive a frantic call from a new DBA who accidentally dropped a table containing all your customers.

Which Amazon RDS feature will allow you to reliably restore your database to within 5 minutes of when the mistake was made?

- A. Multi-AZ RDS
- B. RDS snapshots
- C. RDS read replicas
- D. RDS automated backup

Answer: D

Explanation:

Reference:

<http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Overview.BackingUpAndRestoringAmazonRDSInstances.html>

NEW QUESTION 41

- (Topic 1)

You have started a new job and are reviewing your company's infrastructure on AWS. You notice one web application where they have an Elastic Load Balancer (&B) in front of web instances in an Auto Scaling Group. When you check the metrics for the ELB in CloudWatch, you see four healthy instances in Availability Zone (AZ) A and zero in AZ B. There are zero unhealthy instances.

What do you need to fix to balance the instances across AZs?

- A. Set the ELB to only be attached to another AZ
- B. Make sure Auto Scaling is configured to launch in both AZs
- C. Make sure your AMI is available in both AZs
- D. Make sure the maximum size of the Auto Scaling Group is greater than 4

Answer: B

NEW QUESTION 43

- (Topic 1)

You are using ElastiCache Memcached to store session state and cache database queries in your infrastructure. You notice in CloudWatch that Evictions and GetMisses are both very high.

What two actions could you take to rectify this?

Choose 2 answers

- A. Increase the number of nodes in your cluster
- B. Tweak the max_item_size parameter
- C. Shrink the number of nodes in your cluster
- D. Increase the size of the nodes in the cluster

Answer: BD

NEW QUESTION 46

- (Topic 1)

You are attempting to connect to an instance in Amazon VPC without success. You have already verified that the VPC has an Internet Gateway (IGW), the instance has an associated Elastic IP (EIP), and correct security group rules are in place.

Which VPC component should you evaluate next?

- A. The configuration of a NAT instance
- B. The configuration of the Routing Table
- C. The configuration of the Internet Gateway (IGW)
- D. The configuration of SRC/DST checking

Answer: B

Explanation:

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/UserScenariosForVPC.html>

NEW QUESTION 49

- (Topic 1)

What are characteristics of Amazon S3? Choose 2 answers

- A. Objects are directly accessible via a URL
- B. S3 should be used to host a relational database
- C. S3 allows you to store objects of virtually unlimited size
- D. S3 allows you to store virtually unlimited amounts of data
- E. S3 offers Provisioned IOPS

Answer: AD

NEW QUESTION 52

- (Topic 1)

When creation of an EBS snapshot is initiated but not completed, the EBS volume?

- A. Cannot be detached or attached to an EC2 instance until the snapshot completes
- B. Can be used in read-only mode while the snapshot is in progress
- C. Can be used while the snapshot is in progress
- D. Cannot be used until the snapshot completes

Answer: C

Explanation:

Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-copy-snapshot.html>

NEW QUESTION 57

- (Topic 1)

You have a Linux EC2 web server instance running inside a VPC. The instance is in a public subnet and has an EIP associated with it so you can connect to it over the Internet via HTTP or SSH. The instance was also fully accessible when you last logged in via SSH, and was also serving web requests on port 80.

Now you are not able to SSH into the host nor does it respond to web requests on port 80 that were working fine last time you checked. You have double-checked that all networking configuration parameters (security groups, route tables, IGW/EIP, NACLs, etc.) are properly configured (and you haven't made any changes to those anyway since you were last able to reach the instance). You look at the EC2 console and notice that system status check shows "impaired."

Which should be your next step in troubleshooting and attempting to get the instance back to a healthy state so that you can log in again?

- A. Stop and start the instance so that it will be able to be redeployed on a healthy host system that most likely will fix the "impaired" system status
- B. Reboot your instance so that the operating system will have a chance to boot in a clean healthy state that most likely will fix the "impaired" system status
- C. Add another dynamic private IP address to the instance and try to connect via that new path, since the networking stack of the OS may be locked up causing the "impaired" system status
- D. Add another Elastic Network Interface to the instance and try to connect via that new path since the networking stack of the OS may be locked up causing the "impaired" system status
- E. un-map and then re-map the EIP to the instance, since the IGW/VNAT gateway may not be working properly, causing the "impaired" system status

Answer: A

NEW QUESTION 58

- (Topic 2)

A user is trying to understand the ACL and policy for an S3 bucket. Which of the below mentioned policy permissions is equivalent to the WRITE ACL on a bucket?

- A. s3:GetObjectAcl
- B. s3:GetObjectVersion
- C. s3:ListBucketVersions
- D. s3:DeleteObject

Answer: D

Explanation:

Amazon S3 provides a set of operations to work with the Amazon S3 resources. Each AWS S3 bucket can have an ACL (Access Control List) or bucket policy associated with it. The WRITE ACL list allows the other AWS accounts to write/modify to that bucket. The equivalent S3 bucket policy permission for it is s3:DeleteObject.

NEW QUESTION 63

- (Topic 2)

A user is planning to use AWS CloudFormation. Which of the below mentioned functionalities does not help him to correctly understand CloudFormation?

- A. CloudFormation follows the DevOps model for the creation of Dev & Test
- B. AWS CloudFormation does not charge the user for its service but only charges for the AWS resources created with it
- C. CloudFormation works with a wide variety of AWS services, such as EC2, EBS, VPC, IAM, S3, RDS, ELB, etc
- D. CloudFormation provides a set of application bootstrapping scripts which enables the user to install software

Answer: A

Explanation:

AWS CloudFormation is an application management tool which provides application modelling, deployment, configuration, management and related activities. It supports a wide variety of AWS services, such as EC2, EBS, AS, ELB, RDS, VPC, etc. It also provides application bootstrapping scripts which enable the user to install software packages or create folders. It is free of the cost and only charges the user for the services created with it. The only challenge is that it does not follow any model, such as DevOps; instead customers can define templates and use them to provision and manage the AWS resources in an orderly way.

NEW QUESTION 67

- (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/16 using the wizard. The user has created a public subnet CIDR (20.0.0.0/24) and VPN only subnets CIDR (20.0.1.0/24) along with the VPN gateway (vgw-12345) to connect to the user's data centre. Which of the below mentioned options is a valid entry for the main route table in this scenario?

- A. Destination: 20.0.0.0/24 and Target: vgw-12345
- B. Destination: 20.0.0.0/16 and Target: ALL
- C. Destination: 20.0.1.0/16 and Target: vgw-12345
- D. Destination: 0.0.0.0/0 and Target: vgw-12345

Answer: D

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. When the user has configured this setup with Wizard, it will create a virtual private gateway to route all traffic of the VPN subnet. Here are the valid entries for the main route table in this scenario: Destination: 0.0.0.0/0 & Target: vgw-12345 (To route all internet traffic to the VPN gateway). Destination: 20.0.0.0/16 & Target: local (To allow local routing in VPC).

NEW QUESTION 72

- (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/16 with only a private subnet and VPN connection using the VPC wizard. The user wants to connect to the instance in a private subnet over SSH. How should the user define the security rule for SSH?

- A. Allow Inbound traffic on port 22 from the user's network
- B. The user has to create an instance in EC2 Classic with an elastic IP and configure the security group of a private subnet to allow SSH from that elastic IP
- C. The user can connect to a instance in a private subnet using the NAT instance
- D. Allow Inbound traffic on port 80 and 22 to allow the user to connect to a private subnet over the Internet

Answer: A

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, the user can setup a case with a VPN only subnet (private. which uses VPN access to connect with his data centre. When the user has configured this setup with Wizard, all network connections to the instances in the subnet will come from his data centre. The user has to configure the security group of the private subnet which allows the inbound traffic on SSH (port 22. from the data centre's network range.

NEW QUESTION 74

- (Topic 2)

A user has created an ELB with the availability zone US-East-1A. The user wants to add more zones to ELB to achieve High Availability. How can the user add more zones to the existing ELB?

- A. It is not possible to add more zones to the existing ELB
- B. The only option is to launch instances in different zones and add to ELB
- C. The user should stop the ELB and add zones and instances as required
- D. The user can add zones on the fly from the AWS console

Answer: D

Explanation:

The user has created an Elastic Load Balancer with the availability zone and wants to add more zones to the existing ELB. The user can do so in two ways: From the console or CLI, add new zones to ELB; Launch instances in a separate AZ and add instances to the existing ELB.

NEW QUESTION 78

- (Topic 2)

A user has developed an application which is required to send the data to a NoSQL database. The user wants to decouple the data sending such that the application keeps processing and sending data but does not wait for an acknowledgement of DB. Which of the below mentioned applications helps in this scenario?

- A. AWS Simple Notification Service
- B. AWS Simple Workflow
- C. AWS Simple Queue Service
- D. AWS Simple Query Service

Answer: C

Explanation:

Amazon Simple Queue Service (SQS) is a fast, reliable, scalable, and fully managed message queuing service. SQS provides a simple and cost-effective way to decouple the components of an application. In this case, the user can use AWS SQS to send messages which are received from an application and sent to DB. The application can continue processing data without waiting for any acknowledgement from DB. The user can use SQS to transmit any volume of data without losing messages or requiring other services to always be available.

NEW QUESTION 83

- (Topic 2)

A user has received a message from the support team that an issue occurred 1 week back between 3 AM to 4 AM and the EC2 server was not reachable. The user is checking the CloudWatch metrics of that instance. How can the user find the data easily using the CloudWatch console?

- A. The user can find the data by giving the exact values in the time Tab under CloudWatch metrics
- B. The user can find the data by filtering values of the last 1 week for a 1 hour period in the Relative tab under CloudWatch metrics
- C. It is not possible to find the exact time from the console
- D. The user has to use CLI to provide the specific time
- E. The user can find the data by giving the exact values in the Absolute tab under CloudWatch metrics

Answer: D

Explanation:

If the user is viewing the data inside the CloudWatch console, the console provides options to filter values either using the relative period, such as days /hours or using the Absolute tab where the user can provide data with a specific date and time. The console also provides the option to search using the local timezone under the time range caption in the console.

NEW QUESTION 87

- (Topic 2)

An organization is planning to create 5 different AWS accounts considering various security requirements. The organization wants to use a single payee account

by using the consolidated billing option. Which of the below mentioned statements is true with respect to the above information?

- A. Master (Payee)
- B. account will get only the total bill and cannot see the cost incurred by each account
- C. Master (Payee)
- D. account can view only the AWS billing details of the linked accounts
- E. It is not recommended to use consolidated billing since the payee account will have access to the linked accounts
- F. Each AWS account needs to create an AWS billing policy to provide permission to the payee account

Answer: B

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS) accounts within a single organization by making a single paying account. Consolidated billing enables the organization to see a combined view of the AWS charges incurred by each account as well as obtain a detailed cost report for each of the individual AWS accounts associated with the paying account. The payee account will not have any other access than billing data of linked accounts.

NEW QUESTION 90

- (Topic 2)

A sys admin is maintaining an application on AWS. The application is installed on EC2 and user has configured ELB and Auto Scaling. Considering future load increase, the user is planning to launch new servers proactively so that they get registered with ELB. How can the user add these instances with Auto Scaling?

- A. Increase the desired capacity of the Auto Scaling group
- B. Increase the maximum limit of the Auto Scaling group
- C. Launch an instance manually and register it with ELB on the fly
- D. Decrease the minimum limit of the Auto Scaling group

Answer: A

Explanation:

A user can increase the desired capacity of the Auto Scaling group and Auto Scaling will launch a new instance as per the new capacity. The newly launched instances will be registered with ELB if Auto Scaling group is configured with ELB. If the user decreases the minimum size the instances will be removed from Auto Scaling. Increasing the maximum size will not add instances but only set the maximum instance cap.

NEW QUESTION 94

- (Topic 2)

A sys admin has created the below mentioned policy and applied to an S3 object named aws.jpg. The aws.jpg is inside a bucket named cloudacademy. What does this policy define?

```
"Statement": [{
  "Sid": "Stmnt1388811069831",
  "Effect": "Allow",
  "Principal": { "AWS": "*" },
  "Action": [ "s3:GetObjectAcl", "s3:ListBucket", "s3:GetObject" ],
  "Resource": [ "arn:aws:s3:::cloudacademy/* .jpg" ]
}]
```

- A. It is not possible to define a policy at the object level
- B. It will make all the objects of the bucket cloudacademy as public
- C. It will make the bucket cloudacademy as public
- D. the aws.jpg object as public

Answer: A

Explanation:

A system admin can grant permission to the S3 objects or buckets to any user or make objects public using the bucket policy and user policy. Both use the JSON-based access policy language. Generally if the user is defining the ACL on the bucket, the objects in the bucket do not inherit it and vice versa. The bucket policy can be defined at the bucket level which allows the objects as well as the bucket to be public with a single policy applied to that bucket. It cannot be applied at the object level.

NEW QUESTION 97

- (Topic 2)

A user is planning to evaluate AWS for their internal use. The user does not want to incur any charge on his account during the evaluation. Which of the below mentioned AWS services would incur a charge if used?

- A. AWS S3 with 1 GB of storage
- B. AWS micro instance running 24 hours daily
- C. AWS ELB running 24 hours a day
- D. AWS PIOPS volume of 10 GB size

Answer: D

Explanation:

AWS is introducing a free usage tier for one year to help the new AWS customers get started in Cloud. The free tier can be used for anything that the user wants to run in the Cloud. AWS offers a handful of AWS services as a part of this which includes 750 hours of free micro instances and 750 hours of ELB. It includes the AWS S3 of 5 GB and AWS EBS general purpose volume upto 30 GB. PIOPS is not part of free usage tier.

NEW QUESTION 101

- (Topic 2)

A user has setup a billing alarm using CloudWatch for \$200. The usage of AWS exceeded \$200 after some days. The user wants to increase the limit from \$200 to \$400? What should the user do?

- A. Create a new alarm of \$400 and link it with the first alarm
- B. It is not possible to modify the alarm once it has crossed the usage limit
- C. Update the alarm to set the limit at \$400 instead of \$200
- D. Create a new alarm for the additional \$200 amount

Answer: C

Explanation:

AWS CloudWatch supports enabling the billing alarm on the total AWS charges. The estimated charges are calculated and sent several times daily to CloudWatch in the form of metric data. This data will be stored for 14 days. This data also includes the estimated charges for every service in AWS used by the user, as well as the estimated overall AWS charges. If the user wants to increase the limit, the user can modify the alarm and specify a new threshold.

NEW QUESTION 106

- (Topic 2)

An organization is planning to use AWS for 5 different departments. The finance department is responsible to pay for all the accounts. However, they want the cost separation for each account to map with the right cost centre. How can the finance department achieve this?

- A. Create 5 separate accounts and make them a part of one consolidate billing
- B. Create 5 separate accounts and use the IAM cross account access with the roles for better management
- C. Create 5 separate IAM users and set a different policy for their access
- D. Create 5 separate IAM groups and add users as per the department's employees

Answer: A

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS) accounts within a single organization by making a single paying account. Consolidated billing enables the organization to see a combined view of the AWS charges incurred by each account as well as obtain a detailed cost report for each of the individual AWS accounts associated with the paying account.

NEW QUESTION 107

- (Topic 2)

An organization is planning to use AWS for their production roll out. The organization wants to implement automation for deployment such that it will automatically create a LAMP stack, download the latest PHP installable from S3 and setup the ELB. Which of the below mentioned AWS services meets the requirement for making an orderly deployment of the software?

- A. AWS Elastic Beanstalk
- B. AWS Cloudfront
- C. AWS CloudFormation
- D. AWS DevOps

Answer: C

Explanation:

AWS CloudFormation is an application management tool which provides application modelling, deployment, configuration, management and related activities. CloudFormation provides an easy way to create and delete the collection of related AWS resources and provision them in an orderly way. AWS CloudFormation automates and simplifies the task of repeatedly and predictably creating groups of related resources that power the user's applications. AWS Cloudfront is a CDN; Elastic Beanstalk does quite a few of the required tasks. However, it is a PAAS which uses a ready AMI. AWS Elastic Beanstalk provides an environment to easily develop and run applications in the cloud.

NEW QUESTION 111

- (Topic 2)

A user is running one instance for only 3 hours every day. The user wants to save some cost with the instance. Which of the below mentioned Reserved Instance categories is advised in this case?

- A. The user should not use RI; instead only go with the on-demand pricing
- B. The user should use the AWS high utilized RI
- C. The user should use the AWS medium utilized RI
- D. The user should use the AWS low utilized RI

Answer: A

Explanation:

The AWS Reserved Instance provides the user with an option to save some money by paying a one-time fixed amount and then save on the hourly rate. It is advisable that if the user is having 30% or more usage of an instance per day, he should go for a RI. If the user is going to use an EC2 instance for more than 2200-2500 hours per year, RI will help the user save some cost. Here, the instance is not going to run for less than 1500 hours. Thus, it is advisable that the user should use the on-demand pricing.

NEW QUESTION 112

- (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/24. The user has created a public subnet with CIDR 20.0.0.0/25. The user is trying to create the private subnet with CIDR 20.0.0.128/25. Which of the below mentioned statements is true in this scenario?

- A. It will not allow the user to create the private subnet due to a CIDR overlap
- B. It will allow the user to create a private subnet with CIDR as 20.0.0.128/25
- C. This statement is wrong as AWS does not allow CIDR 20.0.0.0/25
- D. It will not allow the user to create a private subnet due to a wrong CIDR range

Answer: B

Explanation:

When the user creates a subnet in VPC, he specifies the CIDR block for the subnet. The CIDR block of a subnet can be the same as the CIDR block for the VPC (for a single subnet in the VPC., or a subset (to enable multiple subnets.. If the user creates more than one subnet in a VPC, the CIDR blocks of the subnets must not overlap. Thus, in this case the user has created a VPC with the CIDR block 20.0.0.0/24, which supports 256 IP addresses (20.0.0.0 to 20.0.0.255.. The user can break this CIDR block into two subnets, each supporting 128 IP addresses. One subnet uses the CIDR block 20.0.0.0/25 (for addresses 20.0.0.0 - 20.0.0.127. and the other uses the CIDR block 20.0.0.128/25 (for addresses 20.0.0.128 - 20.0.0.255..

NEW QUESTION 114

- (Topic 2)

A user has configured Elastic Load Balancing by enabling a Secure Socket Layer (SSL. negotiation configuration known as a Security Policy. Which of the below mentioned options is not part of this secure policy while negotiating the SSL connection between the user and the client?

- A. SSL Protocols
- B. Client Order Preference
- C. SSL Ciphers
- D. Server Order Preference

Answer: B

Explanation:

Elastic Load Balancing uses a Secure Socket Layer (SSL. negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL connections between a client and the load balancer. A security policy is a combination of SSL Protocols, SSL Ciphers, and the Server Order Preference option.

NEW QUESTION 116

- (Topic 2)

An organization has setup consolidated billing with 3 different AWS accounts. Which of the below mentioned advantages will organization receive in terms of the AWS pricing?

- A. The consolidated billing does not bring any cost advantage for the organization
- B. All AWS accounts will be charged for S3 storage by combining the total storage of each account
- C. The EC2 instances of each account will receive a total of 750*3 micro instance hours free
- D. The free usage tier for all the 3 accounts will be 3 years and not a single year

Answer: B

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS. accounts within a single organization by making a single paying account. For billing purposes, AWS treats all the accounts on the consolidated bill as one account. Some services, such as Amazon EC2 and Amazon S3 have volume pricing tiers across certain usage dimensions that give the user lower prices when he uses the service more.

NEW QUESTION 119

- (Topic 2)

A user has setup connection draining with ELB to allow in-flight requests to continue while the instance is being deregistered through Auto Scaling. If the user has not specified the draining time, how long will ELB allow inflight requests traffic to continue?

- A. 600 seconds
- B. 3600 seconds
- C. 300 seconds
- D. 0 seconds

Answer: C

Explanation:

The Elastic Load Balancer connection draining feature causes the load balancer to stop sending new requests to the back-end instances when the instances are deregistering or become unhealthy, while ensuring that inflight requests continue to be served. The user can specify a maximum time (3600 seconds. for the load balancer to keep the connections alive before reporting the instance as deregistered. If the user does not specify the maximum timeout period, by default, the load balancer will close the connections to the deregistering instance after 300 seconds.

NEW QUESTION 122

- (Topic 2)

A user has created an S3 bucket which is not publicly accessible. The bucket is having thirty objects which are also private. If the user wants to make the objects public, how can he configure this with minimal efforts?

- A. The user should select all objects from the console and apply a single policy to mark them public

- B. The user can write a program which programmatically makes all objects public using S3 SDK
- C. Set the AWS bucket policy which marks all objects as public
- D. Make the bucket ACL as public so it will also mark all objects as public

Answer: C

Explanation:

A system admin can grant permission of the S3 objects or buckets to any user or make the objects public using the bucket policy and user policy. Both use the JSON-based access policy language. Generally if the user is defining the ACL on the bucket, the objects in the bucket do not inherit it and vice a versa. The bucket policy can be defined at the bucket level which allows the objects as well as the bucket to be public with a single policy applied to that bucket.

NEW QUESTION 123

- (Topic 2)

A user has created a queue named "myqueue" with SQS. There are four messages published to queue which are not received by the consumer yet. If the user tries to delete the queue, what will happen?

- A. A user can never delete a queue manual
- B. AWS deletes it after 30 days of inactivity on queue
- C. It will delete the queue
- D. It will initiate the delete but wait for four days before deleting until all messages are deleted automaticall
- E. I t will ask user to delete the messages first

Answer: B

Explanation:

SQS allows the user to move data between distributed components of applications so they can perform different tasks without losing messages or requiring each component to be always available. The user can delete a queue at any time, whether it is empty or not. It is important to note that queues retain messages for a set period of time. By default, a queue retains messages for four days.

NEW QUESTION 128

- (Topic 2)

A user has configured ELB with three instances. The user wants to achieve High Availability as well as redundancy with ELB. Which of the below mentioned AWS services helps the user achieve this for ELB?

- A. Route 53
- B. AWS Mechanical Turk
- C. Auto Scaling
- D. AWS EMR

Answer: A

Explanation:

The user can provide high availability and redundancy for applications running behind Elastic Load Balancer by enabling the Amazon Route 53 Domain Name System (DNS. failover for the load balancers. Amazon Route 53 is a DNS service that provides reliable routing to the user's infrastructure.

NEW QUESTION 133

- (Topic 2)

A user has enabled the Multi AZ feature with the MS SQL RDS database server. Which of the below mentioned statements will help the user understand the Multi AZ feature better?

- A. In a Multi AZ, AWS runs two DBs in parallel and copies the data asynchronously to the replica copy
- B. In a Multi AZ, AWS runs two DBs in parallel and copies the data synchronously to the replica copy
- C. In a Multi AZ, AWS runs just one DB but copies the data synchronously to the standby replica
- D. AWS MS SQL does not support the Multi AZ feature

Answer: C

Explanation:

Amazon RDS provides high availability and failover support for DB instances using Multi-AZ deployments. In a Multi-AZ deployment, Amazon RDS automatically provisions and maintains a synchronous standby replica in a different Availability Zone. The primary DB instance is synchronously replicated across Availability Zones to a standby replica to provide data redundancy, eliminate I/O freezes, and minimize latency spikes during system backups. Running a DB instance with high availability can enhance availability during planned system maintenance, and help protect your databases against DB instance failure and Availability Zone disruption. Note that the high-availability feature is not a scaling solution for read-only scenarios; you cannot use a standby replica to serve read traffic. To service read-only traffic, you should use a read replica.

NEW QUESTION 137

- (Topic 2)

An organization is setting up programmatic billing access for their AWS account. Which of the below mentioned services is not required or enabled when the organization wants to use programmatic access?

- A. Programmatic access
- B. AWS bucket to hold the billing report
- C. AWS billing alerts
- D. Monthly Billing report

Answer: C

Explanation:

AWS provides an option to have programmatic access to billing. Programmatic Billing Access leverages the existing Amazon Simple Storage Service (Amazon S3) APIs. Thus, the user can build applications that reference his billing data from a CSV (comma-separated value) file stored in an Amazon S3 bucket. To enable programmatic access, the user has to first enable the monthly billing report. Then the user needs to provide an AWS bucket name where the billing CSV will be uploaded. The user should also enable the Programmatic access option.

NEW QUESTION 139

- (Topic 2)

A user has stored data on an encrypted EBS volume. The user wants to share the data with his friend's AWS account. How can user achieve this?

- A. Create an AMI from the volume and share the AMI
- B. Copy the data to an unencrypted volume and then share
- C. Take a snapshot and share the snapshot with a friend
- D. If both the accounts are using the same encryption key then the user can share the volume directly

Answer: B

Explanation:

AWS EBS supports encryption of the volume. It also supports creating volumes from existing snapshots provided the snapshots are created from encrypted volumes. If the user is having data on an encrypted volume and is trying to share it with others, he has to copy the data from the encrypted volume to a new unencrypted volume. Only then can the user share it as an encrypted volume data. Otherwise the snapshot cannot be shared.

NEW QUESTION 142

- (Topic 2)

A user has launched an EC2 instance. The user is planning to setup the CloudWatch alarm. Which of the below mentioned actions is not supported by the CloudWatch alarm?

- A. Notify the Auto Scaling launch config to scale up
- B. Send an SMS using SNS
- C. Notify the Auto Scaling group to scale down
- D. Stop the EC2 instance

Answer: B

Explanation:

A user can create a CloudWatch alarm that takes various actions when the alarm changes state. An alarm watches a single metric over the time period that the user has specified, and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The actions could be sending a notification to an Amazon Simple Notification Service topic (SMS, Email, and HTTP end point), notifying the Auto Scaling policy or changing the state of the instance to Stop/Terminate.

NEW QUESTION 147

- (Topic 2)

A user has configured ELB with two EBS backed EC2 instances. The user is trying to understand the DNS access and IP support for ELB. Which of the below mentioned statements may not help the user understand the IP mechanism supported by ELB?

- A. The client can connect over IPV4 or IPV6 using Dualstack
- B. ELB DNS supports both IPV4 and IPV6
- C. Communication between the load balancer and back-end instances is always through IPV4
- D. The ELB supports either IPV4 or IPV6 but not both

Answer: D

Explanation:

Elastic Load Balancing supports both Internet Protocol version 6 (IPv6) and Internet Protocol version 4 (IPv4). Clients can connect to the user's load balancer using either IPv4 or IPv6 (in EC2-Classic DNS). However, communication between the load balancer and its back-end instances uses only IPv4. The user can use the Dualstack-prefixed DNS name to enable IPv6 support for communications between the client and the load balancers. Thus, the clients are able to access the load balancer using either IPv4 or IPv6 as their individual connectivity needs dictate.

NEW QUESTION 148

- (Topic 2)

A user has setup a CloudWatch alarm on an EC2 action when the CPU utilization is above 75%. The alarm sends a notification to SNS on the alarm state. If the user wants to simulate the alarm action how can he achieve this?

- A. Run activities on the CPU such that its utilization reaches above 75%
- B. From the AWS console change the state to 'Alarm'
- C. The user can set the alarm state to 'Alarm' using CLI
- D. Run the SNS action manually

Answer: C

Explanation:

Amazon CloudWatch alarms watch a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The user can test an alarm by setting it to any state using the SetAlarmState API (mon-set-alarm-state command.. This temporary state change lasts only until the next alarm comparison occurs.

NEW QUESTION 150

- (Topic 2)

A user wants to make so that whenever the CPU utilization of the AWS EC2 instance is above 90%, the redlight of his bedroom turns on. Which of the below mentioned AWS services is helpful for this purpose?

- A. AWS CloudWatch + AWS SES
- B. AWS CloudWatch + AWS SNS
- C. Non
- D. It is not possible to configure the light with the AWS infrastructure services
- E. AWS CloudWatch and a dedicated software turning on the light

Answer: B

Explanation:

Amazon Simple Notification Service (Amazon SNS. is a fast, flexible, and fully managed push messaging service. Amazon SNS can deliver notifications by SMS text message or email to the Amazon Simple Queue Service (SQS. queues or to any HTTP endpoint. The user can configure some sensor devices at his home which receives data on the HTTP end point (REST calls. and turn on the red light. The user can configure the CloudWatch alarm to send a notification to the AWS SNS HTTP end point (the sensor device. and it will turn the light red when there is an alarm condition.

NEW QUESTION 153

- (Topic 2)

A user has created an ELB with Auto Scaling. Which of the below mentioned offerings from ELB helps the user to stop sending new requests traffic from the load balancer to the EC2 instance when the instance is being deregistered while continuing in-flight requests?

- A. ELB sticky session
- B. ELB deregistration check
- C. ELB connection draining
- D. ELB auto registration Off

Answer: C

Explanation:

The Elastic Load Balancer connection draining feature causes the load balancer to stop sending new requests to the back-end instances when the instances are deregistering or become unhealthy, while ensuring that in-flight requests continue to be served.

NEW QUESTION 157

- (Topic 2)

An organization (Account ID 123412341234. has attached the below mentioned IAM policy to a user. What does this policy statement entitle the user to perform?

```
"Statement": [
{
  "Sid": "AllowUsersAllActionsForCredentials",
  "Effect": "Allow",
  "Action": [
    "iam:*AccessKey*",
  ],
  "Resource": ["arn:aws:iam:: 123412341234:user/${aws:username}"]
}
]
```

- A. 0
- B. 0
- C. 0
- D. 0

Answer: A

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the organization (Account ID 123412341234. wants some of their users to manage keys (access and secret access keys. of all IAM users, the organization should set the below mentioned policy which entitles the IAM user to modify keys of all IAM users with CLI, SDK or API.

```
"Statement": [
{
  "Sid": "AllowUsersAllActionsForCredentials",
  "Effect": "Allow",
  "Action": [
    "iam:*AccessKey*",
  ],
  "Resource": ["arn:aws:iam:: 123412341234:user/${aws:username}"]
}
]
```

NEW QUESTION 159

- (Topic 2)

A user is trying to aggregate all the CloudWatch metric data of the last 1 week. Which of the below mentioned statistics is not available for the user as a part of data aggregation?

- A. Aggregate
- B. Sum
- C. Sample data
- D. Average

Answer: A

Explanation:

Amazon CloudWatch is basically a metrics repository. Either the user can send the custom data or an AWS product can put metrics into the repository, and the user can retrieve the statistics based on those metrics. The statistics are metric data aggregations over specified periods of time. Aggregations are made using the namespace, metric name, dimensions, and the data point unit of measure, within the time period that is specified by the user. CloudWatch supports Sum, Min, Max, Sample Data and Average statistics aggregation.

NEW QUESTION 161

- (Topic 2)

An organization has created 50 IAM users. The organization has introduced a new policy which will change the access of an IAM user. How can the organization implement this effectively so that there is no need to apply the policy at the individual user level?

- A. Use the IAM groups and add users as per their role to different groups and apply policy to group
- B. The user can create a policy and apply it to multiple users in a single go with the AWS CLI
- C. Add each user to the IAM role as per their organization role to achieve effective policy setup
- D. Use the IAM role and implement access at the role level

Answer: A

Explanation:

With AWS IAM, a group is a collection of IAM users. A group allows the user to specify permissions for a collection of users, which can make it easier to manage the permissions for those users. A group helps an organization manage access in a better way; instead of applying at the individual level, the organization can apply at the group level which is applicable to all the users who are a part of that group.

NEW QUESTION 165

- (Topic 2)

An organization, which has the AWS account ID as 999988887777, has created 50 IAM users. All the users are added to the same group cloudacademy. If the organization has enabled that each IAM user can login with the AWS console, which AWS login URL will the IAM users use?

- A. [https:// 999988887777.signin.aws.amazon.com/console/](https://999988887777.signin.aws.amazon.com/console/)
- B. [https:// signin.aws.amazon.com/cloudacademy/](https://signin.aws.amazon.com/cloudacademy/)
- C. [https:// cloudacademy.signin.aws.amazon.com/999988887777/console/](https://cloudacademy.signin.aws.amazon.com/999988887777/console/)
- D. [https:// 999988887777.aws.amazon.com/ cloudacademy/](https://999988887777.aws.amazon.com/cloudacademy/)

Answer: A

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. Once the organization has created the IAM users, they will have a separate AWS console URL to login to the AWS console. The console login URL for the IAM user will be [https:// AWS_Account_ID.signin.aws.amazon.com/console/](https://AWS_Account_ID.signin.aws.amazon.com/console/). It uses only the AWS account ID and does not depend on the group or user ID.

NEW QUESTION 168

- (Topic 2)

A user has configured an Auto Scaling group with ELB. The user has enabled detailed CloudWatch monitoring on Elastic Load balancing. Which of the below mentioned statements will help the user understand this functionality better?

- A. ELB sends data to CloudWatch every minute only and does not charge the user
- B. ELB will send data every minute and will charge the user extra
- C. ELB is not supported by CloudWatch
- D. It is not possible to setup detailed monitoring for ELB

Answer: A

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. It provides either basic or detailed monitoring for the supported AWS products. In basic monitoring, a service sends data points to CloudWatch every five minutes, while in detailed monitoring a service sends data points to CloudWatch every minute. Elastic Load Balancing includes 10 metrics and 2 dimensions, and sends data to CloudWatch every minute. This does not cost extra.

NEW QUESTION 173

- (Topic 2)

A user has setup Auto Scaling with ELB on the EC2 instances. The user wants to configure that whenever the CPU utilization is below 10%, Auto Scaling should remove one instance. How can the user configure this?

- A. The user can get an email using SNS when the CPU utilization is less than 10%. The user can use the desired capacity of Auto Scaling to remove the instance

- B. Use CloudWatch to monitor the data and Auto Scaling to remove the instances using scheduled actions
- C. Configure CloudWatch to send a notification to Auto Scaling Launch configuration when the CPU utilization is less than 10% and configure the Auto Scaling policy to remove the instance
- D. Configure CloudWatch to send a notification to the Auto Scaling group when the CPU Utilization is less than 10% and configure the Auto Scaling policy to remove the instance

Answer: D

Explanation:

Amazon CloudWatch alarms watch a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The user can setup to receive a notification on the Auto Scaling group with the CloudWatch alarm when the CPU utilization is below a certain threshold. The user can configure the Auto Scaling policy to take action for removing the instance. When the CPU utilization is below 10% CloudWatch will send an alarm to the Auto Scaling group to execute the policy.

NEW QUESTION 177

- (Topic 2)

An organization has created 50 IAM users. The organization wants that each user can change their password but cannot change their access keys. How can the organization achieve this?

- A. The organization has to create a special password policy and attach it to each user
- B. The root account owner has to use CLI which forces each IAM user to change their password on first login
- C. By default each IAM user can modify their passwords
- D. The root account owner can set the policy from the IAM console under the password policy screen

Answer: D

Explanation:

With AWS IAM, organizations can use the AWS Management Console to display, create, change or delete a password policy. As a part of managing the password policy, the user can enable all users to manage their own passwords. If the user has selected the option which allows the IAM users to modify their password, he does not need to set a separate policy for the users. This option in the AWS console allows changing only the password.

NEW QUESTION 180

- (Topic 2)

A user is launching an instance. He is on the "Tag the instance" screen. Which of the below mentioned information will not help the user understand the functionality of an AWS tag?

- A. Each tag will have a key and value
- B. The user can apply tags to the S3 bucket
- C. The maximum value of the tag key length is 64 unicode characters
- D. AWS tags are used to find the cost distribution of various resources

Answer: C

Explanation:

AWS provides cost allocation tags to categorize and track the AWS costs. When the user applies tags to his AWS resources, AWS generates a cost allocation report as a comma-separated value (CSV) file, with the usage and costs aggregated by those tags. Each tag will have a key-value and can be applied to services, such as EC2, S3, RDS, EMR, etc. The maximum size of a tag key is 128 unicode characters.

NEW QUESTION 185

- (Topic 2)

A user has a refrigerator plant. The user is measuring the temperature of the plant every 15 minutes. If the user wants to send the data to CloudWatch to view the data visually, which of the below mentioned statements is true with respect to the information given above?

- A. The user needs to use AWS CLI or API to upload the data
- B. The user can use the AWS Import Export facility to import data to CloudWatch
- C. The user will upload data from the AWS console
- D. The user cannot upload data to CloudWatch since it is not an AWS service metric

Answer: A

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. While sending the data the user has to include the metric name, namespace and timezone as part of the request.

NEW QUESTION 190

- (Topic 2)

A user has recently started using EC2. The user launched one EC2 instance in the default subnet in EC2-VPC. Which of the below mentioned options is not attached or available with the EC2 instance when it is launched?

- A. Public IP address
- B. Internet gateway
- C. Elastic IP
- D. Private IP address

Answer: C

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to a user's AWS account. A subnet is a range of IP addresses in the VPC. The user can launch the AWS resources into a subnet. There are two supported platforms into which a user can launch instances: EC2-Classic and EC2-VPC (default subnet). A default VPC has all the benefits of EC2-VPC and the ease of use of EC2-Classic. Each instance that the user launches into a default subnet has a private IP address and a public IP address. These instances can communicate with the internet through an internet gateway. An internet gateway enables the EC2 instances to connect to the internet through the Amazon EC2 network edge.

NEW QUESTION 192

- (Topic 2)

A user has setup an RDS DB with Oracle. The user wants to get notifications when someone modifies the security group of that DB. How can the user configure that?

- A. It is not possible to get the notifications on a change in the security group
- B. Configure SNS to monitor security group changes
- C. Configure event notification on the DB security group
- D. Configure the CloudWatch alarm on the DB for a change in the security group

Answer: C

Explanation:

Amazon RDS uses the Amazon Simple Notification Service to provide a notification when an Amazon RDS event occurs. These events can be configured for source categories, such as DB instance, DB security group, DB snapshot and DB parameter group. If the user is subscribed to a Configuration Change category for a DB security group, he will be notified when the DB security group is changed.

NEW QUESTION 196

- (Topic 2)

A user is publishing custom metrics to CloudWatch. Which of the below mentioned statements will help the user understand the functionality better?

- A. The user can use the CloudWatch Import tool
- B. The user should be able to see the data in the console after around 15 minutes
- C. If the user is uploading the custom data, the user must supply the namespace, timezone, and metric name as part of the command
- D. The user can view as well as upload data using the console, CLI and APIs

Answer: B

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. The user has to always include the namespace as a part of the request. However, the other parameters are optional. If the user has uploaded data using CLI, he can view it as a graph inside the console. The data will take around 2 minutes to upload but can be viewed only after around 15 minutes.

NEW QUESTION 198

- (Topic 2)

You are building an online store on AWS that uses SQS to process your customer orders. Your backend system needs those messages in the same sequence the customer orders have been put in. How can you achieve that?

- A. It is not possible to do this with SQS
- B. You can use sequencing information on each message
- C. You can do this with SQS but you also need to use SWF
- D. Messages will arrive in the same order by default

Answer: B

Explanation:

Amazon SQS is engineered to always be available and deliver messages. One of the resulting tradeoffs is that SQS does not guarantee first in, first out delivery of messages. For many distributed applications, each message can stand on its own, and as long as all messages are delivered, the order is not important. If your system requires that order be preserved, you can place sequencing information in each message, so that you can reorder the messages when the queue returns them.

NEW QUESTION 203

- (Topic 2)

A user is trying to understand AWS SNS. To which of the below mentioned end points is SNS unable to send a notification?

- A. Email JSON
- B. HTTP
- C. AWS SQS
- D. AWS SES

Answer: D

Explanation:

Amazon Simple Notification Service (Amazon SNS) is a fast, flexible, and fully managed push messaging service. Amazon SNS can deliver notifications by SMS text message or email to the Amazon Simple Queue Service (SQS) queues or to any HTTP endpoint. The user can select one of the following transports as part of the subscription requests: "HTTP", "HTTPS", "Email", "Email-JSON", "SQS", and "SMS".

NEW QUESTION 204

- (Topic 2)

An organization is using cost allocation tags to find the cost distribution of different departments and projects. One of the instances has two separate tags with the key/ value as "InstanceName/HR", "CostCenter/HR". What will AWS do in this case?

- A. InstanceName is a reserved tag for AW
- B. Thus, AWS will not allow this tag
- C. AWS will not allow the tags as the value is the same for different keys
- D. AWS will allow tags but will not show correctly in the cost allocation report due to the same value of the two separate keys
- E. AWS will allow both the tags and show properly in the cost distribution report

Answer: D

Explanation:

AWS provides cost allocation tags to categorize and track the AWS costs. When the user applies tags to his AWS resources, AWS generates a cost allocation report as a comma-separated value (CSV file. with the usage and costs aggregated by those tags. Each tag will have a key-value and can be applied to services, such as EC2, S3, RDS, EMR, etc. It is required that the key should be different for each tag. The value can be the same for different keys. In this case since the value is different, AWS will properly show the distribution report with the correct values.

NEW QUESTION 208

- (Topic 2)

A system admin is planning to setup event notifications on RDS. Which of the below mentioned services will help the admin setup notifications?

- A. AWS SES
- B. AWS Cloudtrail
- C. AWS Cloudwatch
- D. AWS SNS

Answer: D

Explanation:

Amazon RDS uses the Amazon Simple Notification Service to provide a notification when an Amazon RDS event occurs. These notifications can be in any notification form supported by Amazon SNS for an AWS region, such as an email, a text message or a call to an HTTP endpoint

NEW QUESTION 213

- (Topic 2)

A sys admin is trying to understand EBS snapshots. Which of the below mentioned statements will not be useful to the admin to understand the concepts about a snapshot?

- A. The snapshot is synchronous
- B. It is recommended to stop the instance before taking a snapshot for consistent data
- C. The snapshot is incremental
- D. The snapshot captures the data that has been written to the hard disk when the snapshot command was executed

Answer: A

Explanation:

The AWS snapshot is a point in time backup of an EBS volume. When the snapshot command is executed it will capture the current state of the data that is written on the drive and take a backup. For a better and consistent snapshot of the root EBS volume, AWS recommends stopping the instance. For additional volumes it is recommended to unmount the device. The snapshots are asynchronous and incremental.

NEW QUESTION 218

- (Topic 3)

A user has created a VPC with a public subnet. The user has terminated all the instances which are part of the subnet. Which of the below mentioned statements is true with respect to this scenario?

- A. The user cannot delete the VPC since the subnet is not deleted
- B. All network interface attached with the instances will be deleted
- C. When the user launches a new instance it cannot use the same subnet
- D. The subnet to which the instances were launched with will be deleted

Answer: B

Explanation:

A Virtual Private Cloud (VPC. is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. When an instance is launched it will have a network interface attached with it. The user cannot delete the subnet until he terminates the instance and deletes the network interface. When the user terminates the instance all the network interfaces attached with it are also deleted.

NEW QUESTION 221

- (Topic 3)

A user has deployed an application on an EBS backed EC2 instance. For a better performance of application, it requires dedicated EC2 to EBS traffic. How can the user achieve this?

- A. Launch the EC2 instance as EBS dedicated with PIOPS EBS
- B. Launch the EC2 instance as EBS enhanced with PIOPS EBS

- C. Launch the EC2 instance as EBS dedicated with PIOPS EBS
- D. Launch the EC2 instance as EBS optimized with PIOPS EBS

Answer: D

Explanation:

Any application which has performance sensitive workloads and requires minimal variability with dedicated EC2 to EBS traffic should use provisioned IOPS EBS volumes, which are attached to an EBS-optimized EC2 instance or it should use an instance with 10 Gigabit network connectivity. Launching an instance that is EBS optimized provides the user with a dedicated connection between the EC2 instance and the EBS volume.

NEW QUESTION 225

- (Topic 3)

A user has launched an EC2 instance from an instance store backed AMI. The user has attached an additional instance store volume to the instance. The user wants to create an AMI from the running instance. Will the AMI have the additional instance store volume data?

- A. Yes, the block device mapping will have information about the additional instance store volume
- B. No, since the instance store backed AMI can have only the root volume bundled
- C. It is not possible to attach an additional instance store volume to the existing instance store backed AMI instance
- D. No, since this is ephemeral storage it will not be a part of the AMI

Answer: A

Explanation:

When the user has launched an EC2 instance from an instance store backed AMI and added an instance store volume to the instance in addition to the root device volume, the block device mapping for the new AMI contains the information for these volumes as well. In addition, the block device mappings for the instances those are launched from the new AMI will automatically contain information for these volumes.

NEW QUESTION 227

- (Topic 3)

A user has configured ELB with Auto Scaling. The user suspended the Auto Scaling terminate process only for a while. What will happen to the availability zone rebalancing process (AZRebalance) during this period?

- A. Auto Scaling will not launch or terminate any instances
- B. Auto Scaling will allow the instances to grow more than the maximum size
- C. Auto Scaling will keep launching instances till the maximum instance size
- D. It is not possible to suspend the terminate process while keeping the launch active

Answer: B

Explanation:

Auto Scaling performs various processes, such as Launch, Terminate, Availability Zone Rebalance (AZRebalance) etc. The AZRebalance process type seeks to maintain a balanced number of instances across Availability Zones within a region. If the user suspends the Terminate process, the AZRebalance process can cause the Auto Scaling group to grow up to ten percent larger than the maximum size. This is because Auto Scaling allows groups to temporarily grow larger than the maximum size during rebalancing activities. If Auto Scaling cannot terminate instances, the Auto Scaling group could remain up to ten percent larger than the maximum size until the user resumes the Terminate process type.

NEW QUESTION 232

- (Topic 3)

A user is trying to understand the CloudWatch metrics for the AWS services. It is required that the user should first understand the namespace for the AWS services. Which of the below mentioned is not a valid namespace for the AWS services?

- A. AWS/StorageGateway
- B. AWS/CloudTrail
- C. AWS/ElastiCache
- D. AWS/SWF

Answer: B

Explanation:

Amazon CloudWatch is basically a metrics repository. The AWS product puts metrics into this repository, and the user can retrieve the data or statistics based on those metrics. To distinguish the data for each service, the CloudWatch metric has a namespace. Namespaces are containers for metrics. All AWS services that provide the Amazon CloudWatch data use a namespace string, beginning with "AWS/". All the services which are supported by CloudWatch will have some namespace. CloudWatch does not monitor CloudTrail. Thus, the namespace "AWS/CloudTrail" is incorrect.

NEW QUESTION 233

- (Topic 3)

An organization has created a Queue named "modularqueue" with SQS. The organization is not performing any operations such as SendMessage, ReceiveMessage, DeleteMessage, GetQueueAttributes, SetQueueAttributes, AddPermission, and RemovePermission on the queue. What can happen in this scenario?

- A. AWS SQS sends notification after 15 days for inactivity on queue
- B. AWS SQS can delete queue after 30 days without notification
- C. AWS SQS marks queue inactive after 30 days
- D. AWS SQS notifies the user after 2 weeks and deletes the queue after 3 week

Answer: B

Explanation:

Amazon SQS can delete a queue without notification if one of the following actions hasn't been performed on it for 30 consecutive days: SendMessage, ReceiveMessage, DeleteMessage, GetQueueAttributes, SetQueueAttributes, AddPermission, and RemovePermission.

NEW QUESTION 237

- (Topic 3)

The CFO of a company wants to allow one of his employees to view only the AWS usage report page. Which of the below mentioned IAM policy statements allows the user to have access to the AWS usage report page?

- A. "Effect": "Allow", "Action": ["Describe"], "Resource": "Billing"
- B. "Effect": "Allow", "Action": ["AccountUsage"], "Resource": "**"
- C. "Effect": "Allow", "Action": ["aws-portal:ViewUsage"], "Resource": "**"
- D. "Effect": "Allow", "Action": ["aws-portal:ViewBilling"], "Resource": "**"

Answer: C

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the CFO wants to allow only AWS usage report page access, the policy for that IAM user will be as given below:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "aws-portal:ViewUsage"
      ],
      "Resource": "**"
    }
  ]
}
```

NEW QUESTION 241

- (Topic 3)

A user is trying to understand the detailed CloudWatch monitoring concept. Which of the below mentioned services does not provide detailed monitoring with CloudWatch?

- A. AWS EMR
- B. AWS RDS
- C. AWS ELB
- D. AWS Route53

Answer: A

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. It provides either basic or detailed monitoring for the supported AWS products. In basic monitoring, a service sends data points to CloudWatch every five minutes, while in detailed monitoring a service sends data points to CloudWatch every minute. Services, such as RDS, EC2, Auto Scaling, ELB, and Route 53 can provide the monitoring data every minute.

NEW QUESTION 242

- (Topic 3)

A user has launched two EBS backed EC2 instances in the US-East-1a region. The user wants to change the zone of one of the instances. How can the user change it?

- A. The zone can only be modified using the AWS CLI
- B. It is not possible to change the zone of an instance after it is launched
- C. Stop one of the instances and change the availability zone
- D. From the AWS EC2 console, select the Actions - > Change zones and specify the new zone

Answer: B

Explanation:

With AWS EC2, when a user is launching an instance he can select the availability zone (AZ) at the time of launch. If the zone is not selected, AWS selects it on behalf of the user. Once the instance is launched, the user cannot change the zone of that instance unless he creates an AMI of that instance and launches a new instance from it.

NEW QUESTION 243

- (Topic 3)

A user has created a subnet in VPC and launched an EC2 instance within it. The user has not selected the option to assign the IP address while launching the instance. Which of the below mentioned statements is true with respect to this scenario?

- A. The instance will always have a public DNS attached to the instance by default

- B. The user can directly attach an elastic IP to the instance
- C. The instance will never launch if the public IP is not assigned
- D. The user would need to create an internet gateway and then attach an elastic IP to the instance to connect from internet

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. When the user is launching an instance he needs to select an option which attaches a public IP to the instance. If the user has not selected the option to attach the public IP then it will only have a private IP when launched. The user cannot connect to the instance from the internet. If the user wants an elastic IP to connect to the instance from the internet he should create an internet gateway and assign an elastic IP to instance.

NEW QUESTION 245

- (Topic 3)

Which of the following statements about this S3 bucket policy is true?

```
{
  "Id": "IPAllowPolicy",
  "Statement": [
    {
      "Sid": "IPAllow",
      "Action": "s3:*",
      "Effect": "Allow",
      "Resource": "arn:aws:s3:::mybucket/*",
      "Condition": {
        "IpAddress": {
          "aws:SourceIp": "192.168.100.0/24"
        },
        "NotIpAddress": {
          "aws:SourceIp": "192.168.100.188/32"
        }
      }
    }
  ],
  "Principal": {
    "AWS": [
      "*"
    ]
  }
}
```

- A. Denies the server with the IP address 192.166 100.0 full access to the "mybucket" bucket
- B. Denies the server with the IP address 192.166 100.188 full access to the "mybucket" bucket
- C. Grants all the servers within the 192 168 100 0/24 subnet full access to the "mybucket" bucket
- D. Grants all the servers within the 192 168 100 188/32 subnet full access to the "mybucket" bucket

Answer: C

NEW QUESTION 248

- (Topic 3)

You have a business-to-business web application running in a VPC consisting of an Elastic Load Balancer (ELB), web servers, application servers and a database. Your web application should only accept traffic from pre-defined customer IP addresses.

Which two options meet this security requirement? Choose 2 answers A. Configure web server VPC security groups to allow traffic from your customers' IPs

- A. Configure your web servers to filter traffic based on the ELB's "X-forwarded-for" header
- B. Configure ELB security groups to allow traffic from your customers' IPs and deny all outbound traffic
- C. Configure a VPC NACL to allow web traffic from your customers' IPs and deny all outbound traffic

Answer: AB

NEW QUESTION 253

- (Topic 3)

A user has launched an RDS MySQL DB with the Multi AZ feature. The user has scheduled the scaling of instance storage during maintenance window. What is the correct order of events during maintenance window?

- 1. Perform maintenance on standby
- 2. Promote standby to primary
- 3. Perform maintenance on original primary
- 4. Promote original master back as primary

- A. 1, 2, 3, 4
- B. 1, 2, 3
- C. 2, 3, 1, 4

Answer: B

Explanation:

Running MySQL on the RDS DB instance as a Multi-AZ deployment can help the user reduce the impact of a maintenance event, as the Amazon will conduct maintenance by following the steps in the below mentioned order: Perform maintenance on standby Promote standby to primary Perform maintenance on original primary, which becomes the new standby.

NEW QUESTION 254

- (Topic 3)

A user is planning to scale up an application by 8 AM and scale down by 7 PM daily using Auto Scaling. What should the user do in this case?

- A. Setup the scaling policy to scale up and down based on the CloudWatch alarms
- B. The user should increase the desired capacity at 8 AM and decrease it by 7 PM manually
- C. The user should setup a batch process which launches the EC2 instance at a specific time
- D. Setup scheduled actions to scale up or down at a specific time

Answer: A

Explanation:

Auto Scaling based on a schedule allows the user to scale the application in response to predictable load changes. To configure the Auto Scaling group to scale based on a schedule, the user needs to create scheduled actions. A scheduled action tells Auto Scaling to perform a scaling action at a certain time in the future.

NEW QUESTION 258

- (Topic 3)

A user has created a VPC with the public and private subnets using the VPC wizard. The VPC has CIDR 20.0.0.0/16. The public subnet uses CIDR 20.0.1.0/24. The user is planning to host a web server in the public subnet (port 80) and a DB server in the private subnet (port 3306). The user is configuring a security group for the public subnet (WebSecGrp) and the private subnet (DBSecGrp). Which of the below mentioned entries is required in the private subnet database security group (DBSecGrp)?

- A. Allow Inbound on port 3306 for Source Web Server Security Group (WebSecGr)
- B. Allow Inbound on port 3306 from source 20.0.0.0/16
- C. Allow Outbound on port 3306 for Destination Web Server Security Group (WebSecGr)
- D. Allow Outbound on port 80 for Destination NAT Instance IP

Answer: A

Explanation:

A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet to host the web server and DB server respectively, the user should configure that the instances in the private subnet can receive inbound traffic from the public subnet on the DB port. Thus, configure port 3306 in Inbound with the source as the Web Server Security Group (WebSecGrp). The user should configure ports 80 and 443 for Destination 0.0.0.0/0 as the route table directs traffic to the NAT instance from the private subnet.

NEW QUESTION 261

- (Topic 3)

An organization has setup Auto Scaling with ELB. Due to some manual error, one of the instances got rebooted. Thus, it failed the Auto Scaling health check. Auto Scaling has marked it for replacement. How can the system admin ensure that the instance does not get terminated?

- A. Update the Auto Scaling group to ignore the instance reboot event
- B. It is not possible to change the status once it is marked for replacement
- C. Manually add that instance to the Auto Scaling group after reboot to avoid replacement
- D. Change the health of the instance to healthy using the Auto Scaling commands

Answer: D

Explanation:

After an instance has been marked unhealthy by Auto Scaling, as a result of an Amazon EC2 or ELB health check, it is almost immediately scheduled for replacement as it will never automatically recover its health. If the user knows that the instance is healthy then he can manually call the SetInstanceHealth action (or the as-setinstance-health command from CLI) to set the instance's health status back to healthy. Auto Scaling will throw an error if the instance is already terminating or else it will mark it healthy.

NEW QUESTION 262

- (Topic 3)

A user has created a VPC with CIDR 20.0.0.0/16. The user has created one subnet with CIDR 20.0.0.0/16 in this VPC. The user is trying to create another subnet with the same VPC for CIDR 20.0.0.1/24. What will happen in this scenario?

- A. The VPC will modify the first subnet CIDR automatically to allow the second subnet IP range
- B. It is not possible to create a subnet with the same CIDR as VPC
- C. The second subnet will be created
- D. It will throw a CIDR overlaps error

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. The user can create a subnet with the same size of VPC. However, he cannot create any other subnet since the CIDR of the second subnet will conflict with the first subnet.

NEW QUESTION 265

- (Topic 3)

A user wants to find the particular error that occurred on a certain date in the AWS MySQL RDS DB. Which of the below mentioned activities may help the user to get the data easily?

- A. It is not possible to get the log files for MySQL RDS
- B. Find all the transaction logs and query on those records
- C. Direct the logs to the DB table and then query that table
- D. Download the log file to DynamoDB and search for the record

Answer: C

Explanation:

The user can view, download, and watch the database logs using the Amazon RDS console, the Command Line Interface (CLI) or the Amazon RDS API. For the MySQL RDS, the user can view the error log, slow query log, and general logs. The user can also view the MySQL logs easily by directing the logs to a database table in the main database and querying that table.

NEW QUESTION 267

- (Topic 3)

You have a proprietary data store on-premises that must be backed up daily by dumping the data store contents to a single compressed 50GB file and sending the file to AWS. Your SLAs state that any dump file backed up within the past 7 days can be retrieved within 2 hours. Your compliance department has stated that all data must be held indefinitely. The time required to restore the data store from a backup is approximately 1 hour. Your on-premise network connection is capable of sustaining 1gbps to AWS.

Which backup methods to AWS would be most cost-effective while still meeting all of your requirements?

- A. Send the daily backup files to Glacier immediately after being generated
- B. Transfer the daily backup files to an EBS volume in AWS and take daily snapshots of the volume
- C. Transfer the daily backup files to S3 and use appropriate bucket lifecycle policies to send to Glacier
- D. Host the backup files on a Storage Gateway with Gateway-Cached Volumes and take daily snapshots

Answer: D

Explanation:

Reference:

<http://aws.amazon.com/storagegateway/faqs/>

NEW QUESTION 270

- (Topic 3)

A user is collecting 1000 records per second. The user wants to send the data to CloudWatch using the custom namespace. Which of the below mentioned options is recommended for this activity?

- A. Aggregate the data with statistics, such as Min, max, Average, Sum and Sample data and send the data to CloudWatch
- B. Send all the data values to CloudWatch in a single command by separating them with a comm
- C. CloudWatch will parse automatically
- D. Create one csv file of all the data and send a single file to CloudWatch
- E. It is not possible to send all the data in one call
- F. Thus, it should be sent one by one
- G. CloudWatch will aggregate the data automatically

Answer: A

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. The user can publish data to CloudWatch as single data points or as an aggregated set of data points called a statistic set using the command `put-metric-data`. It is recommended that when the user is having multiple data points per minute, he should aggregate the data so that it will minimize the number of calls to `put-metric-data`. In this case it will be single call to CloudWatch instead of 1000 calls if the data is aggregated.

NEW QUESTION 271

- (Topic 3)

How can an EBS volume that is currently attached to an EC2 instance be migrated from one Availability Zone to another?

- A. Simply create a new volume in the other AZ and specify the original volume as the source
- B. Detach the volume, then use the `ec2-migrate-volume` command to move it to another AZ
- C. Create a snapshot of the volume, and create a new volume from the snapshot in the other AZ
- D. Detach the volume and attach it to another EC2 instance in the other AZ

Answer: D

Explanation:

Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumes.html>

NEW QUESTION 274

- (Topic 3)

A user has configured ELB with Auto Scaling. The user suspended the Auto Scaling AlarmNotification (which notifies Auto Scaling for CloudWatch alarms) for a while. What will Auto Scaling do during this period?

- A. AWS will not receive the alarms from CloudWatch
- B. AWS will receive the alarms but will not execute the Auto Scaling policy
- C. Auto Scaling will execute the policy but it will not launch the instances until the process is resumed
- D. It is not possible to suspend the AlarmNotification process

Answer: B

Explanation:

Auto Scaling performs various processes, such as Launch, Terminate Alarm Notification etc. The user can also suspend individual process. The AlarmNotification process type accepts notifications from the Amazon CloudWatch alarms that are associated with the Auto Scaling group. If the user suspends this process type, Auto Scaling will not automatically execute the scaling policies that would be triggered by the alarms.

NEW QUESTION 277

- (Topic 3)

A user has created a VPC with public and private subnets using the VPC wizard. The user has not launched any instance manually and is trying to delete the VPC. What will happen in this scenario?

- A. It will not allow to delete the VPC as it has subnets with route tables
- B. It will not allow to delete the VPC since it has a running route instance
- C. It will terminate the VPC along with all the instances launched by the wizard
- D. It will not allow to delete the VPC since it has a running NAT instance

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet, the instances in the public subnet can receive inbound traffic directly from the Internet, whereas the instances in the private subnet cannot. If these subnets are created with Wizard, AWS will create a NAT instance with an elastic IP. If the user is trying to delete the VPC it will not allow as the NAT instance is still running.

NEW QUESTION 278

- (Topic 3)

A user runs the command "dd if=/dev/zero of=/dev/xvdfbs=1M" on a fresh blank EBS volume attached to a Linux instance. Which of the below mentioned activities is the user performing with the command given above?

- A. Creating a file system on the EBS volume
- B. Mounting the device to the instance
- C. Pre warming the EBS volume
- D. Formatting the EBS volume

Answer: C

Explanation:

When the user creates a new EBS volume and is trying to access it for the first time it will encounter reduced IOPS due to wiping or initiating of the block storage. To avoid this as well as achieve the best performance it is required to pre warm the EBS volume. For a blank volume attached with a Linux OS, the "dd" command is used to write to all the blocks on the device. In the command "dd if=/dev/zero of=/dev/xvdfbs=1M" the parameter "if =import file" should be set to one of the Linux virtual devices, such as /dev/zero. The "of=output file" parameter should be set to the drive that the user wishes to warm. The "bs" parameter sets the block size of the write operation; for optimal performance, this should be set to 1 MB.

NEW QUESTION 281

- (Topic 3)

An organization (Account ID 123412341234. has attached the below mentioned IAM policy to a user. What does this policy statement entitle the user to perform?

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Sid": "AllowUsersAllActionsForCredentials",
    "Effect": "Allow",
    "Action": [
      "iam:*LoginProfile",
      "iam:*AccessKey*",
      "iam:*SigningCertificate*"
    ],
    "Resource": ["arn:aws:iam:: 123412341234:user/${aws:username}"]
  }]
}
```

- A. The policy allows the IAM user to modify all IAM user's credentials using the console, SDK, CLI or APIs
- B. The policy will give an invalid resource error
- C. The policy allows the IAM user to modify all credentials using only the console
- D. The policy allows the user to modify all IAM user's password, sign in certificates and access keys using only CLI, SDK or APIs

Answer: D

Explanation:

WS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the organization (Account ID 123412341234. wants some of their users to manage credentials (access keys, password, and sign in certificates. of all IAM users, they

should set an applicable policy to that user or group of users. The below mentioned policy allows the IAM user to modify the credentials of all IAM user's using only CLI, SDK or APIs. The user cannot use the AWS console for this activity since he does not have list permission for the IAM users.

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Sid": "AllowUsersAllActionsForCredentials",
    "Effect": "Allow"
    "Action": [
      "iam:*LoginProfile",
      "iam:*AccessKey*",
      "iam:*SigningCertificate*"
    ],
    "Resource": ["arn:aws:iam::123412341234:user:${aws:username}"]
  }]
}
```

NEW QUESTION 285

- (Topic 3)

An organization has applied the below mentioned policy on an IAM group which has selected the IAM users. What entitlements do the IAM users avail with this policy?

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "*",
      "Resource": "*"
    }
  ]
}
```

- A. The policy is not created correctl
- B. It will throw an error for wrong resource name
- C. The policy is for the grou
- D. Thus, the IAM user cannot have any entitlement to this
- E. It allows full access to all AWS services for the IAM users who are a part of this group
- F. If this policy is applied to the EC2 resource, the users of the group will have full access to the EC2 Resources

Answer: C

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. The IAM group allows the organization to specify permissions for a collection of users. With the below mentioned policy, it will allow the group full access (Admin. to all AWS services.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "*",
      "Resource": "*"
    }
  ]
}
```

NEW QUESTION 287

- (Topic 3)

A user is observing the EC2 CPU utilization metric on CloudWatch. The user has observed some interesting patterns while filtering over the 1 week period for a particular hour. The user wants to zoom that data point to a more granular period. How can the user do that easily with CloudWatch?

- A. The user can zoom a particular period by selecting that period with the mouse and then releasing the mouse
- B. The user can zoom a particular period by double clicking on that period with the mouse
- C. The user can zoom a particular period by specifying the aggregation data for that period
- D. The user can zoom a particular period by specifying the period in the Time Range

Answer: A

NEW QUESTION 290

- (Topic 3)

A user is planning to set up the Multi AZ feature of RDS. Which of the below mentioned conditions won't take advantage of the Multi AZ feature?

- A. Availability zone outage
- B. A manual failover of the DB instance using Reboot with failover option
- C. Region outage
- D. When the user changes the DB instance's server type

Answer: C

Explanation:

Amazon RDS when enabled with Multi AZ will handle failovers automatically. Thus, the user can resume database operations as quickly as possible without administrative intervention. The primary DB instance switches over automatically to the standby replica if any of the following conditions occur: An Availability Zone outage The primary DB instance fails The DB instance's server type is changed The DB instance is undergoing software patching A manual failover of the DB instance was initiated using Reboot with failover

NEW QUESTION 295

- (Topic 3)

The compliance department within your multi-national organization requires that all data for your customers that reside in the European Union (EU) must not leave the EU and also

data for customers that reside in the US must not leave the US without explicit authorization.

What must you do to comply with this requirement for a web based profile management application running on EC2?

- A. Run EC2 instances in multiple AWS Availability Zones in single Region and leverage an Elastic Load Balancer with session stickiness to route traffic to the appropriate zone to create their profile
- B. Run EC2 instances in multiple Regions and leverage Route 53's Latency Based Routing capabilities to route traffic to the appropriate region to create their profile
- C. Run EC2 instances in multiple Regions and leverage a third party data provider to determine if a user needs to be redirect to the appropriate region to create their profile
- D. Run EC2 instances in multiple AWS Availability Zones in a single Region and leverage a third party data provider to determine if a user needs to be redirect to the appropriate zone to create their profile

Answer: C

NEW QUESTION 299

- (Topic 3)

An organization has configured Auto Scaling for hosting their application. The system admin wants to understand the Auto Scaling health check process. If the instance is unhealthy, Auto Scaling launches an instance and terminates the unhealthy instance. What is the order execution?

- A. Auto Scaling launches a new instance first and then terminates the unhealthy instance
- B. Auto Scaling performs the launch and terminate processes in a random order
- C. Auto Scaling launches and terminates the instances simultaneously
- D. Auto Scaling terminates the instance first and then launches a new instance

Answer: D

Explanation:

Auto Scaling keeps checking the health of the instances at regular intervals and marks the instance for replacement when it is unhealthy. The ReplaceUnhealthy process terminates instances which are marked as unhealthy and subsequently creates new instances to replace them. This process first terminates the instance and then launches a new instance.

NEW QUESTION 303

- (Topic 3)

An organization is planning to create a user with IAM. They are trying to understand the limitations of IAM so that they can plan accordingly. Which of the below mentioned statements is not true with respect to the limitations of IAM?

- A. One IAM user can be a part of a maximum of 5 groups
- B. The organization can create 100 groups per AWS account
- C. One AWS account can have a maximum of 5000 IAM users
- D. One AWS account can have 250 roles

Answer: A

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. The default maximums for each of the IAM entities is given below: Groups per AWS account: 100 Users per AWS account: 5000 Roles per AWS account: 250 Number of groups per user: 10 (that is, one user can be part of these many groups).

NEW QUESTION 305

- (Topic 3)

A user has launched an EC2 instance from an instance store backed AMI. If the user restarts the instance, what will happen to the ephemeral storage data?

- A. All the data will be erased but the ephemeral storage will stay connected
- B. All data will be erased and the ephemeral storage is released
- C. It is not possible to restart an instance launched from an instance store backed AMI
- D. The data is preserved

Answer: D

Explanation:

A user can reboot an EC2 instance using the AWS console, the Amazon EC2 CLI or the Amazon EC2 API. Rebooting an instance is equivalent to rebooting an operating system. However, it is recommended that the user use Amazon EC2 to reboot the instance instead of running the operating system reboot command from the instance. When an instance launched from an instance store backed AMI is rebooted all the ephemeral storage data is still preserved.

NEW QUESTION 308

- (Topic 3)

A user has configured Auto Scaling with the minimum capacity as 2 and the desired capacity as 2. The user is trying to terminate one of the existing instance with the command:

```
as-terminate-instance-in-auto-scaling-group<Instance ID> --decrement-desired-capacity
```

What will Auto Scaling do in this scenario?

- A. Terminates the instance and does not launch a new instance
- B. Terminates the instance and updates the desired capacity to 1
- C. Terminates the instance and updates the desired capacity and minimum size to 1
- D. Throws an error

Answer: D

Explanation:

The Auto Scaling command `as-terminate-instance-in-auto-scaling-group <Instance ID>` will terminate the specific instance ID. The user is required to specify the parameter `--decrement-desired-capacity`. Then Auto Scaling will terminate the instance and decrease the desired capacity by 1. In this case since the minimum size is 2, Auto Scaling will not allow the desired capacity to go below 2. Thus, it will throw an error.

NEW QUESTION 309

- (Topic 3)

A root account owner is trying to understand the S3 bucket ACL. Which of the below mentioned options cannot be used to grant ACL on the object using the authorized predefined group?

- A. Authenticated user group
- B. All users group
- C. Log Delivery Group
- D. Canonical user group

Answer: D

Explanation:

An S3 bucket ACL grantee can be an AWS account or one of the predefined Amazon S3 groups. Amazon S3 has a set of predefined groups. When granting account access to a group, the user can specify one of the URLs of that group instead of a canonical user ID. AWS S3 has the following predefined groups: Authenticated Users group: It represents all AWS accounts. All Users group: Access permission to this group allows anyone to access the resource. Log Delivery group: WRITE permission on a bucket enables this group to write server access logs to the bucket.

NEW QUESTION 310

- (Topic 3)

An organization has created 10 IAM users. The organization wants each of the IAM users to have access to a separate DynamoDB table. All the users are added to the same group and the organization wants to setup a group level policy for this. How can the organization achieve this?

- A. Define the group policy and add a condition which allows the access based on the IAM name
- B. Create a DynamoDB table with the same name as the IAM user name and define the policy rule which grants access based on the DynamoDB ARN using a variable
- C. Create a separate DynamoDB database for each user and configure a policy in the group based on the DB variable
- D. It is not possible to have a group level policy which allows different IAM users to different DynamoDB Tables

Answer: D

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. AWS DynamoDB has only tables and the organization cannot make separate databases. The organization should create a table with the same name as the IAM user name and use the ARN of DynamoDB as part of the group policy. The sample policy is shown below:

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Effect": "Allow",
    "Action": ["dynamodb:*"],
    "Resource": "arn:aws:dynamodb:region:account-number-without-hyphens:table/${aws:username}"
  }]
}
```

NEW QUESTION 314

- (Topic 3)

A user has created a VPC with the public and private subnets using the VPC wizard. The VPC has CIDR 20.0.0.0/16. The public subnet uses CIDR 20.0.1.0/24. The user is planning to host a web server in the public subnet (port 80) and a DB server in the private subnet (port 3306). The user is configuring a security group for the public subnet (WebSecGrp) and the private subnet (DBSecGrp). Which of the below mentioned entries is required in the web server security group (WebSecGrp)?

- A. Configure Destination as DB Security group ID (DbSecGr)
- B. for port 3306 Outbound
- C. 80 for Destination 0.0.0.0/0 Outbound
- D. Configure port 3306 for source 20.0.0.0/24 InBound
- E. Configure port 80 InBound for source 20.0.0.0/16

Answer: A

Explanation:

A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet to host the web server and DB server respectively, the user should configure that the instances in the public subnet can receive inbound traffic directly from the internet. Thus, the user should configure port 80 with source 0.0.0.0/0 in InBound. The user should configure that the instance in the public subnet can send traffic to the private subnet instances on the DB port. Thus, the user should configure the DB Amazon AWS-SysOps : Practice Test security group of the private subnet (DbSecGrp. as the destination for port 3306 in Outbound.

NEW QUESTION 315

- (Topic 3)

An organization has launched 5 instances: 2 for production and 3 for testing. The organization wants that one particular group of IAM users should only access the test instances and not the production ones. How can the organization set that as a part of the policy?

- A. Launch the test and production instances in separate regions and allow region wise access to the group
- B. Define the IAM policy which allows access based on the instance ID
- C. Create an IAM policy with a condition which allows access to only small instances
- D. Define the tags on the test and production servers and add a condition to the IAM policy which allows access to specific tags

Answer: D

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. The user can add conditions as a part of the IAM policies. The condition can be set on AWS Tags, Time, and Client IP as well as on various parameters. If the organization wants the user to access only specific instances he should define proper tags and add to the IAM policy condition.

The sample policy is shown below.

```
"Statement": [  
{  
  "Action": "ec2:*",  
  "Effect": "Allow",  
  "Resource": "*",  
  "Condition": {  
    "StringEquals": {  
      "ec2:ResourceTag/InstanceType": "Production"  
    }  
  }  
}]
```

NEW QUESTION 318

- (Topic 3)

A user had aggregated the CloudWatch metric data on the AMI ID. The user observed some abnormal behaviour of the CPU utilization metric while viewing the last 2 weeks of data. The user wants to share that data with his manager. How can the user achieve this easily with the AWS console?

- A. The user can use the copy URL functionality of CloudWatch to share the exact details
- B. The user can use the export data option from the CloudWatch console to export the current data point
- C. The user has to find the period and data and provide all the aggregation information to the manager
- D. The user can use the CloudWatch data copy functionality to copy the current data points

Answer: A

Explanation:

Amazon CloudWatch provides the functionality to graph the metric data generated either by the AWS services or the custom metric to make it easier for the user to analyse. The console provides the option to save the URL or bookmark it so that it can be used in the future by typing the same URL. The Copy URL functionality is available under the console when the user selects any metric to view.

NEW QUESTION 321

- (Topic 3)

A user has provisioned 2000 IOPS to the EBS volume. The application hosted on that EBS is experiencing less IOPS than provisioned. Which of the below mentioned options does not affect the IOPS of the volume?

- A. The application does not have enough IO for the volume
- B. The instance is EBS optimized
- C. The EC2 instance has 10 Gigabit Network connectivity
- D. The volume size is too large

Answer: D

Explanation:

When the application does not experience the expected IOPS or throughput of the PIOPS EBS volume that was provisioned, the possible root cause could be that the EC2 bandwidth is the limiting factor and the instance might not be either EBS-optimized or might not have 10 Gigabit network connectivity. Another possible cause for not experiencing the expected IOPS could also be that the user is not driving enough I/O to the EBS volumes. The size of the volume may not affect IOPS.

NEW QUESTION 322

- (Topic 3)

A user has configured an HTTPS listener on an ELB. The user has not configured any security policy which can help to negotiate SSL between the client and ELB. What will ELB do in this scenario?

- A. By default ELB will select the first version of the security policy
- B. By default ELB will select the latest version of the policy
- C. ELB creation will fail without a security policy
- D. It is not required to have a security policy since SSL is already installed

Answer: B

Explanation:

Elastic Load Balancing uses a Secure Socket Layer (SSL) negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL connections between a client and the load balancer. If the user has created an HTTPS/SSL listener without associating any security policy, Elastic Load Balancing will, by default, associate the latest version of the ELBSecurityPolicy-YYYY-MM with the load balancer.

NEW QUESTION 326

- (Topic 3)

A user runs the command "dd if=/dev/xvdf of=/dev/null bs=1M" on an EBS volume created from a snapshot and attached to a Linux instance. Which of the below mentioned activities is the user performing with the step given above?

- A. Pre warming the EBS volume
- B. Initiating the device to mount on the EBS volume
- C. Formatting the volume
- D. Copying the data from a snapshot to the device

Answer: A

Explanation:

When the user creates an EBS volume and is trying to access it for the first time it will encounter reduced IOPS due to wiping or initiating of the block storage. To avoid this as well as achieve the best performance it is required to pre warm the EBS volume. For a volume created from a snapshot and attached with a Linux OS, the "dd" command pre warms the existing data on EBS and any restored snapshots of volumes that have been previously fully pre warmed. This command maintains incremental snapshots; however, because this operation is read-only, it does not pre warm unused space that has never been written to on the original volume. In the command "dd if=/dev/xvdf of=/dev/null bs=1M", the parameter "if=input file" should be set to the drive that the user wishes to warm. The "of=output file" parameter should be set to the Linux null virtual device, /dev/null. The "bs" parameter sets the block size of the read operation; for optimal performance, this should be set to 1 MB.

NEW QUESTION 327

- (Topic 3)

A sysadmin has created the below mentioned policy on an S3 bucket named cloudacademy. The bucket has both AWS.jpg and index.html objects. What does this policy define?

```
"Statement": [{
  "Sid": "Stmnt1388811069831",
  "Effect": "Allow",
  "Principal": { "AWS": "*" },
  "Action": [ "s3:GetObjectAcl", "s3:ListBucket", "s3:GetObject" ],
  "Resource": [ "arn:aws:s3:::cloudacademy/* .jpg" ]
}]
```

- A. It will make all the objects as well as the bucket public
- B. It will throw an error for the wrong action and does not allow to save the policy
- C. It will make the AWS.jpg object as public
- D. It will make the AWS.jpg as well as the cloudacademy bucket as public

Answer: B

NEW QUESTION 330

- (Topic 3)

A user is planning to schedule a backup for an EBS volume. The user wants security of the snapshot data. How can the user achieve data encryption with a snapshot?

- A. Use encrypted EBS volumes so that the snapshot will be encrypted by AWS
- B. While creating a snapshot select the snapshot with encryption
- C. By default the snapshot is encrypted by AWS
- D. Enable server side encryption for the snapshot using S3

Answer: A

Explanation:

AWS EBS supports encryption of the volume. It also supports creating volumes from existing snapshots provided the snapshots are created from encrypted volumes. The data at rest, the I/O as well as all the snapshots of the encrypted EBS will also be encrypted. EBS encryption is based on the AES-256 cryptographic algorithm, which is the industry standard.

NEW QUESTION 335

- (Topic 3)

A user has setup an EBS backed instance and attached 2 EBS volumes to it. The user has setup a CloudWatch alarm on each volume for the disk data. The user has stopped the EC2 instance and detached the EBS volumes. What will be the status of the alarms on the EBS volume?

- A. OK
- B. Insufficient Data
- C. Alarm
- D. The EBS cannot be detached until all the alarms are removed

Answer: B

Explanation:

Amazon CloudWatch alarm watches a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. Alarms invoke actions only for sustained state changes. There are three states of the alarm: OK, Alarm and Insufficient data. In this case since the EBS is detached and inactive the state will be Insufficient.

NEW QUESTION 339

- (Topic 3)

An organization has configured Auto Scaling with ELB. There is a memory issue in the application which is causing CPU utilization to go above 90%. The higher CPU usage triggers an event for Auto Scaling as per the scaling policy. If the user wants to find the root cause inside the application without triggering a scaling activity, how can he achieve this?

- A. Stop the scaling process until research is completed
- B. It is not possible to find the root cause from that instance without triggering scaling
- C. Delete Auto Scaling until research is completed
- D. Suspend the scaling process until research is completed

Answer: D

Explanation:

Auto Scaling allows the user to suspend and then resume one or more of the Auto Scaling processes in the Auto Scaling group. This is very useful when the user wants to investigate a configuration problem or some other issue, such as a memory leak with the web application and then make changes to the application, without triggering the Auto Scaling process.

NEW QUESTION 341

- (Topic 3)

George has launched three EC2 instances inside the US-East-1a zone with his AWS account. Ray has launched two EC2 instances in the US-East-1a zone with his AWS account. Which of the below mentioned statements will help George and Ray understand the availability zone (AZ) concept better?

- A. The instances of George and Ray will be running in the same data centre
- B. All the instances of George and Ray can communicate over a private IP with a minimal cost
- C. All the instances of George and Ray can communicate over a private IP without any cost
- D. The US-East-1a region of George and Ray can be different availability zones

Answer: D

Explanation:

Each AWS region has multiple, isolated locations known as Availability Zones. To ensure that the AWS resources are distributed across the Availability Zones for a region, AWS independently maps the Availability Zones to identifiers for each account. In this case the Availability Zone US-East-1a where George's EC2 instances are running might not be the same location as the US-East-1a zone of Ray's EC2 instances. There is no way for the user to coordinate the Availability Zones between accounts.

NEW QUESTION 342

- (Topic 3)

A user has launched an EC2 instance. However, due to some reason the instance was terminated. If the user wants to find out the reason for termination, where can he find the details?

- A. It is not possible to find the details after the instance is terminated
- B. The user can get information from the AWS console, by checking the Instance description under the State transition reason label
- C. The user can get information from the AWS console, by checking the Instance description under the Instance Status Change reason label
- D. The user can get information from the AWS console, by checking the Instance description under the Instance Termination reason label

Answer: D

Explanation:

An EC2 instance, once terminated, may be available in the AWS console for a while after termination. The user can find the details about the termination from the description tab under the label State transition reason. If the instance is still running, there will be no reason listed. If the user has explicitly stopped or terminated the instance, the reason will be "User initiated shutdown".

NEW QUESTION 345

- (Topic 3)

A user is running a batch process on EBS backed EC2 instances. The batch process starts a few instances to process hadoop Map reduce jobs which can run between 50 – 600 minutes or sometimes for more time. The user wants to configure that the instance gets terminated only when the process is completed. How can the user configure this with CloudWatch?

- A. Setup the CloudWatch action to terminate the instance when the CPU utilization is less than 5%
- B. Setup the CloudWatch with Auto Scaling to terminate all the instances
- C. Setup a job which terminates all instances after 600 minutes
- D. It is not possible to terminate instances automatically

Answer: D

Explanation:

Amazon CloudWatch alarm watches a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The user can setup an action which terminates the instances when their CPU utilization is below a certain threshold for a certain period of time. The EC2 action can either terminate or stop the instance as part of the EC2 action.

NEW QUESTION 350

- (Topic 3)

A user has created a VPC with two subnets: one public and one private. The user is planning to run the patch update for the instances in the private subnet. How can the instances in the private subnet connect to the internet?

- A. Use the internet gateway with a private IP
- B. Allow outbound traffic in the security group for port 80 to allow internet updates
- C. The private subnet can never connect to the internet
- D. Use NAT with an elastic IP

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. If the user has created two subnets (one private and one public), he would need a Network Address Translation (NAT) instance with the elastic IP address. This enables the instances in the private subnet to send requests to the internet (for example, to perform software updates..

NEW QUESTION 354

- (Topic 3)

A user has launched multiple EC2 instances for the purpose of development and testing in the same region. The user wants to find the separate cost for the production and development instances. How can the user find the cost distribution?

- A. The user should download the activity report of the EC2 services as it has the instance ID wise data
- B. It is not possible to get the AWS cost usage data of single region instances separately
- C. The user should use Cost Distribution Metadata and AWS detailed billing
- D. The user should use Cost Allocation Tags and AWS billing reports

Answer: D

Explanation:

AWS provides cost allocation tags to categorize and track the AWS costs. When the user applies tags to his AWS resources (such as Amazon EC2 instances or Amazon S3 buckets), AWS generates a cost allocation report as a comma-separated value (CSV) file, with the usage and costs aggregated by those tags. The user can apply tags which represent business categories (such as cost centres, application names, or instance type – Production/Dev. to organize usage costs across multiple services.

NEW QUESTION 355

- (Topic 3)

A user has configured ELB with SSL using a security policy for secure negotiation between the client and load balancer. Which of the below mentioned SSL protocols is not supported by the security policy?

- A. TLS 1.3
- B. TLS 1.2
- C. SSL 2.0
- D. SSL 3.0

Answer: A

Explanation:

Elastic Load Balancing uses a Secure Socket Layer (SSL) negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL connections between a client and the load balancer. Elastic Load Balancing supports the following versions of the SSL protocol: TLS 1.2 TLS 1.1 TLS 1.0 SSL 3.0 SSL 2.0

NEW QUESTION 356

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

AWS-SysOps Practice Exam Features:

- * AWS-SysOps Questions and Answers Updated Frequently
- * AWS-SysOps Practice Questions Verified by Expert Senior Certified Staff
- * AWS-SysOps Most Realistic Questions that Guarantee you a Pass on Your First Try
- * AWS-SysOps Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The AWS-SysOps Practice Test Here](#)