

Google

Exam Questions Professional-Cloud-Architect

Google Certified Professional - Cloud Architect (GCP)



NEW QUESTION 1

- (Exam Topic 1)

For this question, refer to the Mountkirk Games case study

Mountkirk Games needs to create a repeatable and configurable mechanism for deploying isolated application environments. Developers and testers can access each other's environments and resources, but they cannot access staging or production resources. The staging environment needs access to some services from production.

What should you do to isolate development environments from staging and production?

- A. Create a project for development and test and another for staging and production.
- B. Create a network for development and test and another for staging and production.
- C. Create one subnetwork for development and another for staging and production.
- D. Create one project for development, a second for staging and a third for production.

Answer: D

NEW QUESTION 2

- (Exam Topic 1)

For this question, refer to the Mountkirk Games case study.

Mountkirk Games wants to set up a continuous delivery pipeline. Their architecture includes many small services that they want to be able to update and roll back quickly. Mountkirk Games has the following requirements:

- Services are deployed redundantly across multiple regions in the US and Europe.
- Only frontend services are exposed on the public internet.
- They can provide a single frontend IP for their fleet of services.
- Deployment artifacts are immutable. Which set of products should they use?

- A. Google Cloud Storage, Google Cloud Dataflow, Google Compute Engine
- B. Google Cloud Storage, Google App Engine, Google Network Load Balancer
- C. Google Kubernetes Registry, Google Container Engine, Google HTTP(S) Load Balancer
- D. Google Cloud Functions, Google Cloud Pub/Sub, Google Cloud Deployment Manager

Answer: C

NEW QUESTION 3

- (Exam Topic 1)

For this question, refer to the Mountkirk Games case study.

Mountkirk Games has deployed their new backend on Google Cloud Platform (GCP). You want to create a thorough testing process for new versions of the backend before they are released to the public. You want the testing environment to scale in an economical way. How should you design the process?

- A. Create a scalable environment in GCP for simulating production load.
- B. Use the existing infrastructure to test the GCP-based backend at scale.
- C. Build stress tests into each component of your application using resources internal to GCP to simulate load.
- D. Create a set of static environments in GCP to test different levels of load — for example, high, medium, and low.

Answer: A

Explanation:

From scenario: Requirements for Game Backend Platform

- Dynamically scale up or down based on game activity
- Connect to a managed NoSQL database service
- Run customize Linux distro

NEW QUESTION 4

- (Exam Topic 2)

For this question, refer to the TerramEarth case study.

The TerramEarth development team wants to create an API to meet the company's business requirements. You want the development team to focus their development effort on business value versus creating a custom framework. Which method should they use?

- A. Use Google App Engine with Google Cloud Endpoint
- B. Focus on an API for dealers and partners.
- C. Use Google App Engine with a JAX-RS Jersey Java-based framework
- D. Focus on an API for the public.
- E. Use Google App Engine with the Swagger (open API Specification) framework
- F. Focus on an API for the public.
- G. Use Google Container Engine with a Django Python container
- H. Focus on an API for the public.
- I. Use Google Container Engine with a Tomcat container with the Swagger (Open API Specification) framework
- J. Focus on an API for dealers and partners.

Answer: A

Explanation:

https://cloud.google.com/endpoints/docs/openapi/about-cloud-endpoints?hl=en_US&_ga=2.21787131.-1712523

<https://cloud.google.com/endpoints/docs/openapi/architecture-overview> <https://cloud.google.com/storage/docs/gsutil/commands/test>

Develop, deploy, protect and monitor your APIs with Google Cloud Endpoints. Using an Open API Specification or one of our API frameworks, Cloud Endpoints gives you the tools you need for every phase of API development.

From scenario: Business Requirements

Decrease unplanned vehicle downtime to less than 1 week, without increasing the cost of carrying surplus inventory

Support the dealer network with more data on how their customers use their equipment to better position new products and services
Have the ability to partner with different companies – especially with seed and fertilizer suppliers in the fast-growing agricultural business – to create compelling joint offerings for their customers.
Reference: <https://cloud.google.com/certification/guides/cloud-architect/casestudy-terramearth>

NEW QUESTION 5

- (Exam Topic 2)

For this question, refer to the TerramEarth case study.

TerramEarth has equipped unconnected trucks with servers and sensors to collect telemetry data. Next year they want to use the data to train machine learning models. They want to store this data in the cloud while reducing costs. What should they do?

- A. Have the vehicle's computer compress the data in hourly snapshots, and store it in a Google Cloud storage (GCS) Nearline bucket.
- B. Push the telemetry data in Real-time to a streaming dataflow job that compresses the data, and store it in Google BigQuery.
- C. Push the telemetry data in real-time to a streaming dataflow job that compresses the data, and store it in Cloud Bigtable.
- D. Have the vehicle's computer compress the data in hourly snapshots, and store it in a GCS Coldline bucket.

Answer: D

Explanation:

Coldline Storage is the best choice for data that you plan to access at most once a year, due to its slightly lower availability, 90-day minimum storage duration, costs for data access, and higher per-operation costs. For example:

Cold Data Storage - Infrequently accessed data, such as data stored for legal or regulatory reasons, can be stored at low cost as Coldline Storage, and be available when you need it.

Disaster recovery - In the event of a disaster recovery event, recovery time is key. Cloud Storage provides low latency access to data stored as Coldline Storage.

References: <https://cloud.google.com/storage/docs/storage-classes>

NEW QUESTION 6

- (Exam Topic 2)

For this question, refer to the TerramEarth case study

You analyzed TerramEarth's business requirement to reduce downtime, and found that they can achieve a majority of time saving by reducing customers' wait time for parts. You decided to focus on reduction of the 3 weeks aggregate reporting time. Which modifications to the company's processes should you recommend?

- A. Migrate from CSV to binary format, migrate from FTP to SFTP transport, and develop machine learning analysis of metrics.
- B. Migrate from FTP to streaming transport, migrate from CSV to binary format, and develop machine learning analysis of metrics.
- C. Increase fleet cellular connectivity to 80%, migrate from FTP to streaming transport, and develop machine learning analysis of metrics.
- D. Migrate from FTP to SFTP transport, develop machine learning analysis of metrics, and increase dealer local inventory by a fixed factor.

Answer: C

Explanation:

The Avro binary format is the preferred format for loading compressed data. Avro data is faster to load because the data can be read in parallel, even when the data blocks are compressed.

Cloud Storage supports streaming transfers with the gsutil tool or boto library, based on HTTP chunked transfer encoding. Streaming data lets you stream data to and from your Cloud Storage account as soon as it becomes available without requiring that the data be first saved to a separate file. Streaming transfers are useful if you have a process that generates data and you do not want to buffer it locally before uploading it, or if you want to send the result from a computational pipeline directly into Cloud Storage.

References: <https://cloud.google.com/storage/docs/streaming> <https://cloud.google.com/bigquery/docs/loading-data>

NEW QUESTION 7

- (Exam Topic 3)

For this question, refer to the JencoMart case study

A few days after JencoMart migrates the user credentials database to Google Cloud Platform and shuts down the old server, the new database server stops responding to SSH connections. It is still serving database requests to the application servers correctly. What three steps should you take to diagnose the problem? Choose 3 answers

- A. Delete the virtual machine (VM) and disks and create a new one.
- B. Delete the instance, attach the disk to a new VM, and investigate.
- C. Take a snapshot of the disk and connect to a new machine to investigate.
- D. Check inbound firewall rules for the network the machine is connected to.
- E. Connect the machine to another network with very simple firewall rules and investigate.
- F. Print the Serial Console output for the instance for troubleshooting, activate the interactive console, and investigate.

Answer: CDF

Explanation:

<https://cloud.google.com/compute/docs/troubleshooting/troubleshooting-ssh> D: Handling "Unable to connect on port 22" error message

Possible causes include:

There is no firewall rule allowing SSH access on the port. SSH access on port 22 is enabled on all Compute Engine instances by default. If you have disabled access, SSH from the Browser will not work. If you run sshd on a port other than 22, you need to enable the access to that port with a custom firewall rule.

The firewall rule allowing SSH access is enabled, but is not configured to allow connections from GCP Console services. Source IP addresses for browser-based SSH sessions are dynamically allocated by GCP Console and can vary from session to session.

References:

<https://cloud.google.com/compute/docs/ssh-in-browser> <https://cloud.google.com/compute/docs/ssh-in-browser>

NEW QUESTION 8

- (Exam Topic 3)

For this question, refer to the JencoMart case study.

The JencoMart security team requires that all Google Cloud Platform infrastructure is deployed using a least privilege model with separation of duties for administration between production and development resources. What Google domain and project structure should you recommend?

- A. Create two G Suite accounts to manage users: one for development/test/staging and one for production. Each account should contain one project for every application.
- B. Create two G Suite accounts to manage users: one with a single project for all development applications and one with a single project for all production applications.
- C. Create a single G Suite account to manage users with each stage of each application in its own project.
- D. Create a single G Suite account to manage users with one project for the development/test/staging environment and one project for the production environment.

Answer: D

Explanation:

Note: The principle of least privilege and separation of duties are concepts that, although semantically different, are intrinsically related from the standpoint of security. The intent behind both is to prevent people from having higher privilege levels than they actually need

➤ Principle of Least Privilege: Users should only have the least amount of privileges required to perform their job and no more. This reduces authorization exploitation by limiting access to resources such as targets, jobs, or monitoring templates for which they are not authorized.

➤ Separation of Duties: Beyond limiting user privilege level, you also limit user duties, or the specific jobs they can perform. No user should be given responsibility for more than one related function. This limits the ability of a user to perform a malicious action and then cover up that action.

References: <https://cloud.google.com/kms/docs/separation-of-duties>

NEW QUESTION 9

- (Exam Topic 3)

For this question, refer to the JencoMart case study.

JencoMart has built a version of their application on Google Cloud Platform that serves traffic to Asia. You want to measure success against their business and technical goals. Which metrics should you track?

- A. Error rates for requests from Asia
- B. Latency difference between US and Asia
- C. Total visits, error rates, and latency from Asia
- D. Total visits and average latency for users in Asia
- E. The number of character sets present in the database

Answer: D

NEW QUESTION 10

- (Exam Topic 3)

For this question, refer to the JencoMart case study.

JencoMart has decided to migrate user profile storage to Google Cloud Datastore and the application servers to Google Compute Engine (GCE). During the migration, the existing infrastructure will need access to Datastore to upload the data. What service account key-management strategy should you recommend?

- A. Provision service account keys for the on-premises infrastructure and for the GCE virtual machines (VMs).
- B. Authenticate the on-premises infrastructure with a user account and provision service account keys for the VMs.
- C. Provision service account keys for the on-premises infrastructure and use Google Cloud Platform (GCP) managed keys for the VMs
- D. Deploy a custom authentication service on GCE/Google Container Engine (GKE) for the on-premises infrastructure and use GCP managed keys for the VMs.

Answer: A

Explanation:

<https://cloud.google.com/iam/docs/understanding-service-accounts>

Migrating data to Google Cloud Platform

Let's say that you have some data processing that happens on another cloud provider and you want to transfer the processed data to Google Cloud Platform. You can use a service account from the virtual machines on the external cloud to push the data to Google Cloud Platform. To do this, you must create and download a service account key when you create the service account and then use that key from the external process to call the Cloud Platform APIs.

References:

https://cloud.google.com/iam/docs/understanding-service-accounts#migrating_data_to_google_cloud_platform

NEW QUESTION 10

- (Exam Topic 4)

For this question, refer to the Dress4Win case study.

Dress4Win has asked you to recommend machine types they should deploy their application servers to. How should you proceed?

- A. Perform a mapping of the on-premises physical hardware cores and RAM to the nearest machine types in the cloud.
- B. Recommend that Dress4Win deploy application servers to machine types that offer the highest RAM to CPU ratio available.
- C. Recommend that Dress4Win deploy into production with the smallest instances available, monitor them over time, and scale the machine type up until the desired performance is reached.
- D. Identify the number of virtual cores and RAM associated with the application server virtual machines align them to a custom machine type in the cloud, monitor performance, and scale the machine types up until the desired performance is reached.

Answer: C

NEW QUESTION 14

- (Exam Topic 4)

For this question, refer to the Dress4Win case study.

Dress4Win has end-to-end tests covering 100% of their endpoints. They want to ensure that the move to the cloud does not introduce any new bugs. Which additional testing methods should the developers employ to prevent an outage?

- A. They should enable Google Stackdriver Debugger on the application code to show errors in the code.
- B. They should add additional unit tests and production scale load tests on their cloud staging environment.
- C. They should run the end-to-end tests in the cloud staging environment to determine if the code is working as intended.
- D. They should add canary tests so developers can measure how much of an impact the new release causes to latency.

Answer: B

NEW QUESTION 18

- (Exam Topic 4)

For this question, refer to the Dress4Win case study.

As part of Dress4Win's plans to migrate to the cloud, they want to be able to set up a managed logging and monitoring system so they can handle spikes in their traffic load. They want to ensure that:

- The infrastructure can be notified when it needs to scale up and down to handle the ebb and flow of usage throughout the day
- Their administrators are notified automatically when their application reports errors.
- They can filter their aggregated logs down in order to debug one piece of the application across many hosts Which Google StackDriver features should they use?

- A. Logging, Alerts, Insights, Debug
- B. Monitoring, Trace, Debug, Logging
- C. Monitoring, Logging, Alerts, Error Reporting
- D. Monitoring, Logging, Debug, Error Report

Answer: D

NEW QUESTION 21

- (Exam Topic 5)

As part of implementing their disaster recovery plan, your company is trying to replicate their production MySQL database from their private data center to their GCP project using a Google Cloud VPN connection. They are experiencing latency issues and a small amount of packet loss that is disrupting the replication.

What should they do?

- A. Configure their replication to use UDP.
- B. Configure a Google Cloud Dedicated Interconnect.
- C. Restore their database daily using Google Cloud SQL.
- D. Add additional VPN connections and load balance them.
- E. Send the replicated transaction to Google Cloud Pub/Sub.

Answer: B

NEW QUESTION 22

- (Exam Topic 5)

Your company has successfully migrated to the cloud and wants to analyze their data stream to optimize operations. They do not have any existing code for this analysis, so they are exploring all their options. These options include a mix of batch and stream processing, as they are running some hourly jobs and live-processing some data as it comes in. Which technology should they use for this?

- A. Google Cloud Dataproc
- B. Google Cloud Dataflow
- C. Google Container Engine with Bigtable
- D. Google Compute Engine with Google BigQuery

Answer: B

Explanation:

Dataflow is for processing both the Batch and Stream.

Cloud Dataflow is a fully-managed service for transforming and enriching data in stream (real time) and batch (historical) modes with equal reliability and expressiveness -- no more complex workarounds or compromises needed.

References: <https://cloud.google.com/dataflow/>

NEW QUESTION 24

- (Exam Topic 5)

Your company has an enterprise application running on Compute Engine that requires high availability and high performance. The application has been deployed on two instances in two zones in the same region in active/passive mode. The application writes data to a persistent disk in the case of a single zone outage that data should be immediately made available to the other instance in the other zone. You want to maximize performance while minimizing downtime and data loss. What should you do?

- A. * 1. Attach a persistent SSD disk to the first instance* 2. Create a snapshot every hour* 3. In case of a zone outage, recreate a persistent SSD disk in the second instance where data is coming from the created snapshot
- B. * 1 Create a Cloud Storage bucket* 2. Mount the bucket into the first instance with gcs-fuse* 3. In case of a zone outage, mount the Cloud Storage bucket to the second instance with gcs-fuse
- C. * 1 Attach a local SSD to the first instance disk* 2. Execute an rsync command every hour where the target is a persistent SSD disk attached to the second instance* 3. In case of a zone outage, use the second instance
- D. * 1. Attach a regional SSD persistent disk to the first instance* 2. In case of a zone outage, force-attach the disk to the other instance

Answer: D

NEW QUESTION 25

- (Exam Topic 5)

You are using Cloud SQL as the database backend for a large CRM deployment. You want to scale as usage increases and ensure that you don't run out of storage, maintain 75% CPU usage, and keep replication lag below 60 seconds. What are the correct steps to meet your requirements?

- A. 1) Enable automatic storage increase for the instance.2) Create a Stackdriver alert when CPU usage exceeds 75%, and change the instance type to reduce CPU usage.3) Create a Stackdriver alert for replication lag, and shard the database to reduce replication time.
- B. 1) Enable automatic storage increase for the instance.2) Change the instance type to a 32-core machine type to keep CPU usage below 75%.3) Create a Stackdriver alert for replication lag, and shard the database to reduce replication time.

C. 1) Create a Stackdriver alert when storage exceeds 75%, and increase the available storage on the instance to create more space.2) Deploy memcached to reduce CPU load.3) Change the instance type to a 32-core machine type to reduce replication lag.
D. 1) Create a Stackdriver alert when storage exceeds 75%, and increase the available storage on the instance to create more space.2) Deploy memcached to reduce CPU load.3) Create a Stackdriver alert for replication lag, and change the instance type to a 32-core machine type to reduce replication lag.

Answer: A

NEW QUESTION 26

- (Exam Topic 5)

You have developed an application using Cloud ML Engine that recognizes famous paintings from uploaded images. You want to test the application and allow specific people to upload images for the next 24 hours. Not all users have a Google Account. How should you have users upload images?

- A. Have users upload the images to Cloud Storage
- B. Protect the bucket with a password that expires after 24 hours.
- C. Have users upload the images to Cloud Storage using a signed URL that expires after 24 hours.
- D. Create an App Engine web application where users can upload image
- E. Configure App Engine to disable the application after 24 hour
- F. Authenticate users via Cloud Identity.
- G. Create an App Engine web application where users can upload images for the next 24 hours. Authenticate users via Cloud Identity.

Answer: A

Explanation:

<https://cloud.google.com/blog/products/storage-data-transfer/uploading-images-directly-to-cloud-storage-by-usi>

NEW QUESTION 27

- (Exam Topic 5)

Your company creates rendering software which users can download from the company website. Your company has customers all over the world. You want to minimize latency for all your customers. You want to follow Google-recommended practices. How should you store the files?

- A. Save the files in a Multi-Regional Cloud Storage bucket.
- B. Save the files in a Regional Cloud Storage bucket, one bucket per zone of the region.
- C. Save the files in multiple Regional Cloud Storage buckets, one bucket per zone per region.
- D. Save the files in multiple Multi-Regional Cloud Storage buckets, one bucket per multi-region.

Answer: A

Explanation:

<https://cloud.google.com/storage/docs/locations#location-mr>

NEW QUESTION 32

- (Exam Topic 5)

You set up an autoscaling instance group to serve web traffic for an upcoming launch. After configuring the instance group as a backend service to an HTTP(S) load balancer, you notice that virtual machine (VM) instances are being terminated and re-launched every minute. The instances do not have a public IP address. You have verified the appropriate web response is coming from each instance using the curl command. You want to ensure the backend is configured correctly. What should you do?

- A. Ensure that a firewall rule exists to allow source traffic on HTTP/HTTPS to reach the load balancer.
- B. Assign a public IP to each instance and configure a firewall rule to allow the load balancer to reach the instance public IP.
- C. Ensure that a firewall rule exists to allow load balancer health checks to reach the instances in the instance group.
- D. Create a tag on each instance with the name of the load balance
- E. Configure a firewall rule with the name of the load balancer as the source and the instance tag as the destination.

Answer: C

Explanation:

<https://cloud.google.com/vpc/docs/using-firewalls>

The best practice when configuration a health check is to check health and serve traffic on the same port. However, it is possible to perform health checks on one port, but serve traffic on another. If you do use two different ports, ensure that firewall rules and services running on instances are configured appropriately. If you run health checks and serve traffic on the same port, but decide to switch ports at some point, be sure to update both the backend service and the health check. Backend services that do not have a valid global forwarding rule referencing it will not be health checked and will have no health status.

References: <https://cloud.google.com/compute/docs/load-balancing/http/backend-service>

NEW QUESTION 37

- (Exam Topic 5)

Your company has multiple on-premises systems that serve as sources for reporting. The data has not been maintained well and has become degraded over time. You want to use Google-recommended practices to detect anomalies in your company data. What should you do?

- A. Upload your files into Cloud Storage
- B. Use Cloud Datalab to explore and clean your data.
- C. Upload your files into Cloud Storage
- D. Use Cloud Dataprep to explore and clean your data.
- E. Connect Cloud Datalab to your on-premises system
- F. Use Cloud Datalab to explore and clean your data.
- G. Connect Cloud Dataprep to your on-premises system
- H. Use Cloud Dataprep to explore and clean your data.

Answer: B

Explanation:

<https://cloud.google.com/dataprep/>

NEW QUESTION 42

- (Exam Topic 5)

Your company has sensitive data in Cloud Storage buckets. Data analysts have Identity Access Management (IAM) permissions to read the buckets. You want to prevent data analysts from retrieving the data in the buckets from outside the office network. What should you do?

- A. * 1. Create a VPC Service Controls perimeter that includes the projects with the buckets.* 2. Create an access level with the CIDR of the office network.
- B. * 1. Create a firewall rule for all instances in the Virtual Private Cloud (VPC) network for source range.* 2. Use the Classless Inter-domain Routing (CIDR) of the office network.
- C. * 1. Create a Cloud Function to remove IAM permissions from the buckets, and another Cloud Function to add IAM permissions to the buckets.* 2. Schedule the Cloud Functions with Cloud Scheduler to add permissions at the start of business and remove permissions at the end of business.
- D. * 1. Create a Cloud VPN to the office network.* 2. Configure Private Google Access for on-premises hosts.

Answer: A

Explanation:

For all Google Cloud services secured with VPC Service Controls, you can ensure that: Resources within a perimeter are accessed only from clients within authorized VPC networks using Private Google Access with either Google Cloud or on-premises. <https://cloud.google.com/vpc-service-controls/docs/overview>
<https://cloud.google.com/vpc-service-controls/docs/overview>. You create a service control across your VPC and any cloud bucket or any project resource to restrict access. Anything outside of it can't access the resources within service control perimeter

NEW QUESTION 44

- (Exam Topic 5)

Your company is designing its data lake on Google Cloud and wants to develop different ingestion pipelines to collect unstructured data from different sources. After the data is stored in Google Cloud, it will be processed in several data pipelines to build a recommendation engine for end users on the website. The structure of the data retrieved from the source systems can change at any time. The data must be stored exactly as it was retrieved for reprocessing purposes in case the data structure is incompatible with the current processing pipelines. You need to design an architecture to support the use case after you retrieve the data. What should you do?

- A. Send the data through the processing pipeline, and then store the processed data in a BigQuery table for reprocessing.
- B. Store the data in a BigQuery table
- C. Design the processing pipelines to retrieve the data from the table.
- D. Send the data through the processing pipeline, and then store the processed data in a Cloud Storage bucket for reprocessing.
- E. Store the data in a Cloud Storage bucket
- F. Design the processing pipelines to retrieve the data from the bucket

Answer: D

NEW QUESTION 46

- (Exam Topic 5)

You have created several preemptible Linux virtual machine instances using Google Compute Engine. You want to properly shut down your application before the virtual machines are preempted. What should you do?

- A. Create a shutdown script named k99.shutdown in the /etc/rc.6.d/ directory.
- B. Create a shutdown script registered as a xinetd service in Linux and configure a Stackdriver endpoint check to call the service.
- C. Create a shutdown script and use it as the value for a new metadata entry with the key shutdown-script in the Cloud Platform Console when you create the new virtual machine instance.
- D. Create a shutdown script, registered as a xinetd service in Linux, and use the gcloud compute instances add-metadata command to specify the service URL as the value for a new metadata entry with the key shutdown-script-url

Answer: C

NEW QUESTION 48

- (Exam Topic 5)

You are designing a mobile chat application. You want to ensure people cannot spoof chat messages, by providing a message were sent by a specific user. What should you do

- A. Tag messages client side with the originating user identifier and the destination user.
- B. Encrypt the message client side using block-based encryption with a shared key.
- C. Use public key infrastructure (PKI) to encrypt the message client side using the originating user's private key.
- D. Use a trusted certificate authority to enable SSL connectivity between the client application and the server.

Answer: C

NEW QUESTION 53

- (Exam Topic 5)

You are developing a globally scaled frontend for a legacy streaming backend data API. This API expects events in strict chronological order with no repeat data for proper processing.

Which products should you deploy to ensure guaranteed-once FIFO (first-in, first-out) delivery of data?

- A. Cloud Pub/Sub alone
- B. Cloud Pub/Sub to Cloud DataFlow
- C. Cloud Pub/Sub to Stackdriver
- D. Cloud Pub/Sub to Cloud SQL

Answer: B

Explanation:

Reference <https://cloud.google.com/pubsub/docs/ordering>

NEW QUESTION 57

- (Exam Topic 5)

You have been asked to select the storage system for the click-data of your company's large portfolio of websites. This data is streamed in from a custom website analytics package at a typical rate of 6,000 clicks per minute, with bursts of up to 8,500 clicks per second. It must be stored for future analysis by your data science and user experience teams. Which storage infrastructure should you choose?

- A. Google Cloud SQL
- B. Google Cloud Bigtable
- C. Google Cloud Storage
- D. Google cloud Datastore

Answer: C

Explanation:

<https://cloud.google.com/bigquery/docs/loading-data-cloud-storage>

NEW QUESTION 62

- (Exam Topic 5)

You have been engaged by your client to lead the migration of their application infrastructure to GCP. One of their current problems is that the on-premises high performance SAN is requiring frequent and expensive upgrades to keep up with the variety of workloads that are identified as follows: 20TB of log archives retained for legal reasons; 500 GB of VM boot/data volumes and templates; 500 GB of image thumbnails; 200 GB of customer session state data that allows customers to restart sessions even if off-line for several days.

Which of the following best reflects your recommendations for a cost-effective storage allocation?

- A. Local SSD for customer session state dat
- B. Lifecycle-managed Cloud Storage for log archives, thumbnails, and VM boot/data volumes.
- C. Memcache backed by Cloud Datastore for the customer session state dat
- D. Lifecycle- managed Cloud Storage for log archives, thumbnails, and VM boot/data volumes.
- E. Memcache backed by Cloud SQL for customer session state dat
- F. Assorted local SSD-backed instances for VM boot/data volume
- G. Cloud Storage for log archives and thumbnails.
- H. Memcache backed by Persistent Disk SSD storage for customer session state dat
- I. Assorted local SSDbacked instances for VM boot/data volume
- J. Cloud Storage for log archives and thumbnails.

Answer: D

Explanation:

<https://cloud.google.com/compute/docs/disks>

NEW QUESTION 63

- (Exam Topic 5)

Your company runs several databases on a single MySQL instance. They need to take backups of a specific database at regular intervals. The backup activity needs to complete as quickly as possible and cannot be allowed to impact disk performance. How should you configure the storage?

- A. Configure a cron job to use the gcloud tool to take regular backups using persistent disk snapshots.
- B. Mount a Local SSD volume as the backup locatio
- C. After the backup is complete, use gsutil to move the backup to Google Cloud Storage.
- D. Use gcsfuse to mount a Google Cloud Storage bucket as a volume directly on the instance and write backups to the mounted location using mysqldump
- E. Mount additional persistent disk volumes onto each virtual machine (VM) instance in a RAID10 array and use LVM to create snapshots to send to Cloud Storage.

Answer: B

Explanation:

<https://cloud.google.com/compute/docs/instances/sql-server/best-practices>

NEW QUESTION 68

- (Exam Topic 5)

Your application needs to process credit card transactions. You want the smallest scope of Payment Card Industry (PCI) compliance without compromising the ability to analyze transactional data and trends relating to which payment methods are used. How should you design your architecture?

- A. Create a tokenizer service and store only tokenized data.
- B. Create separate projects that only process credit card data.
- C. Create separate subnetworks and isolate the components that process credit card data.
- D. Streamline the audit discovery phase by labeling all of the virtual machines (VMs) that process PCI data.
- E. Enable Logging export to Google BigQuery and use ACLs and views to scope the data shared with the auditor.

Answer: A

Explanation:

<https://cloud.google.com/solutions/pci-dss-compliance-in-gcp>

NEW QUESTION 70

- (Exam Topic 5)

Your company is moving 75 TB of data into Google Cloud. You want to use Cloud Storage and follow Google recommended practices. What should you do?

- A. Move your data onto a Transfer Appliance
- B. Use a Transfer Appliance Rehydrator to decrypt the data into Cloud Storage.
- C. Move your data onto a Transfer Appliance
- D. Use Cloud Dataprep to decrypt the data into Cloud Storage.
- E. Install gsutil on each server that contains data
- F. Use resumable transfers to upload the data into Cloud Storage.
- G. Install gsutil on each server containing data
- H. Use streaming transfers to upload the data into Cloud Storage.

Answer: A

Explanation:

<https://cloud.google.com/transfer-appliance/docs/2.0/faq>

NEW QUESTION 75

- (Exam Topic 5)

Auditors visit your teams every 12 months and ask to review all the Google Cloud Identity and Access Management (Cloud IAM) policy changes in the previous 12 months. You want to streamline and expedite the analysis and audit process. What should you do?

- A. Create custom Google Stackdriver alerts and send them to the auditor.
- B. Enable Logging export to Google BigQuery and use ACLs and views to scope the data shared with the auditor.
- C. Use cloud functions to transfer log entries to Google Cloud SQL and use ACLs and views to limit an auditor's view.
- D. Enable Google Cloud Storage (GCS) log export to audit logs into a GCS bucket and delegate access to the bucket.

Answer: D

Explanation:

Export the logs to Google Cloud Storage bucket - Archive Storage, as it will not be used for 1 year, price for which is \$0.004 per GB per Month. The price for long term storage in BigQuery is \$0.01 per GB per Month (250% more). Also for analysis purpose, whenever Auditors are there (once per year), you can use BigQuery and use GCS bucket as external data source. BigQuery supports querying Cloud Storage data from these storage classes: Standard Nearline Coldline Archive

NEW QUESTION 77

- (Exam Topic 5)

Your company is building a new architecture to support its data-centric business focus. You are responsible for setting up the network. Your company's mobile and web-facing applications will be deployed on-premises, and all data analysis will be conducted in GCP. The plan is to process and load 7 years of archived .csv files totaling 900 TB of data and then continue loading 10 TB of data daily. You currently have an existing 100-MB internet connection. What actions will meet your company's needs?

- A. Compress and upload both archived files and files uploaded daily using the gsutil -m option.
- B. Lease a Transfer Appliance, upload archived files to it, and send it, and send it to Google to transfer archived data to Cloud Storage
- C. Establish a connection with Google using a Dedicated Interconnect or Direct Peering connection and use it to upload files daily.
- D. Lease a Transfer Appliance, upload archived files to it, and send it, and send it to Google to transfer archived data to Cloud Storage
- E. Establish one Cloud VPN Tunnel to VPC networks over the public internet, and compress and upload files daily using the gsutil -m option.
- F. Lease a Transfer Appliance, upload archived files to it, and send it to Google to transfer archived data to Cloud Storage
- G. Establish a Cloud VPN Tunnel to VPC networks over the public internet, and compress and upload files daily.

Answer: B

Explanation:

<https://cloud.google.com/interconnect/docs/how-to/direct-peering>

NEW QUESTION 81

- (Exam Topic 5)

The development team has provided you with a Kubernetes Deployment file. You have no infrastructure yet and need to deploy the application. What should you do?

- A. Use gcloud to create a Kubernetes cluster
- B. Use Deployment Manager to create the deployment.
- C. Use gcloud to create a Kubernetes cluster
- D. Use kubectl to create the deployment.
- E. Use kubectl to create a Kubernetes cluster
- F. Use Deployment Manager to create the deployment.
- G. Use kubectl to create a Kubernetes cluster
- H. Use kubectl to create the deployment.

Answer: B

Explanation:

<https://cloud.google.com/kubernetes-engine/docs/how-to/creating-a-cluster>

NEW QUESTION 85

- (Exam Topic 5)

You are designing an application for use only during business hours. For the minimum viable product release, you'd like to use a managed product that automatically "scales to zero" so you don't incur costs when there is no activity. Which primary compute resource should you choose?

- A. Cloud Functions
- B. Compute Engine
- C. Kubernetes Engine
- D. AppEngine flexible environment

Answer: A

Explanation:

<https://cloud.google.com/serverless-options>

NEW QUESTION 90

- (Exam Topic 5)

Your company just finished a rapid lift and shift to Google Compute Engine for your compute needs. You have another 9 months to design and deploy a more cloud-native solution. Specifically, you want a system that is no-ops and auto-scaling. Which two compute products should you choose? Choose 2 answers

- A. Compute Engine with containers
- B. Google Kubernetes Engine with containers
- C. Google App Engine Standard Environment
- D. Compute Engine with custom instance types
- E. Compute Engine with managed instance groups

Answer: BC

Explanation:

B: With Container Engine, Google will automatically deploy your cluster for you, update, patch, secure the nodes.

Kubernetes Engine's cluster autoscaler automatically resizes clusters based on the demands of the workloads you want to run.

C: Solutions like Datastore, BigQuery, AppEngine, etc are truly NoOps.

App Engine by default scales the number of instances running up and down to match the load, thus providing consistent performance for your app at all times while minimizing idle instances and thus reducing cost.

Note: At a high level, NoOps means that there is no infrastructure to build out and manage during usage of the platform. Typically, the compromise you make with NoOps is that you lose control of the underlying infrastructure.

References:

<https://www.quora.com/How-well-does-Google-Container-Engine-support-Google-Cloud-Platform%E2%80%99s>

NEW QUESTION 92

- (Exam Topic 5)

You need to develop procedures to test a disaster plan for a mission-critical application. You want to use Google-recommended practices and native capabilities within GCP.

What should you do?

- A. Use Deployment Manager to automate service provisionin
- B. Use Activity Logs to monitor and debug your tests.
- C. Use Deployment Manager to automate provisionin
- D. Use Stackdriver to monitor and debug your tests.
- E. Use gcloud scripts to automate service provisionin
- F. Use Activity Logs monitor and debug your tests.
- G. Use automated scripts to automate service provisionin
- H. Use Activity Logs monitor and debug your tests.

Answer: B

Explanation:

<https://cloud.google.com/solutions/dr-scenarios-planning-guide>

NEW QUESTION 94

- (Exam Topic 5)

Your customer is moving their corporate applications to Google Cloud Platform. The security team wants detailed visibility of all projects in the organization. You provision the Google Cloud Resource Manager and set up yourself as the org admin. What Google Cloud Identity and Access Management (Cloud IAM) roles should you give to the security team'?

- A. Org viewer, project owner
- B. Org viewer, project viewer
- C. Org admin, project browser
- D. Project owner, network admin

Answer: B

Explanation:

<https://cloud.google.com/iam/docs/using-iam-securely>

NEW QUESTION 99

- (Exam Topic 5)

Your architecture calls for the centralized collection of all admin activity and VM system logs within your project. How should you collect these logs from both VMs and services?

- A. All admin and VM system logs are automatically collected by Stackdriver.
- B. Stackdriver automatically collects admin activity logs for most service
- C. The Stackdriver Logging agent must be installed on each instance to collect system logs.
- D. Launch a custom syslogd compute instance and configure your GCP project and VMs to forward all logs to it.

E. Install the Stackdriver Logging agent on a single compute instance and let it collect all audit and access logs for your environment.

Answer: B

Explanation:

<https://cloud.google.com/logging/docs/agent/default-logs>

NEW QUESTION 100

- (Exam Topic 5)

You need to upload files from your on-premises environment to Cloud Storage. You want the files to be encrypted on Cloud Storage using customer-supplied encryption keys. What should you do?

- A. Supply the encryption key in a .boto configuration file
- B. Use gsutil to upload the files.
- C. Supply the encryption key using gcloud config
- D. Use gsutil to upload the files to that bucket.
- E. Use gsutil to upload the files, and use the flag --encryption-key to supply the encryption key.
- F. Use gsutil to create a bucket, and use the flag --encryption-key to supply the encryption key
- G. Use gsutil to upload the files to that bucket.

Answer: A

Explanation:

<https://cloud.google.com/storage/docs/encryption/customer-supplied-keys#gsutil>

NEW QUESTION 105

- (Exam Topic 5)

Your company has a Google Cloud project that uses BigQuery for data warehousing. They have a VPN tunnel between the on-premises environment and Google Cloud that is configured with Cloud VPN. The security team wants to avoid data exfiltration by malicious insiders, compromised code, and accidental oversharing. What should they do?

- A. Configure Private Google Access for on-premises only.
- B. Perform the following tasks: 1) Create a service account. 2) Give the BigQuery JobUser role and Storage Reader role to the service account. 3) Remove all other IAM access from the project.
- C. Configure VPC Service Controls and configure Private Google Access.
- D. Configure Private Google Access.

Answer: C

Explanation:

<https://cloud.google.com/vpc-service-controls/docs/overview>

VPC Service Controls improves your ability to mitigate the risk of data exfiltration from Google Cloud services such as Cloud Storage and BigQuery.

NEW QUESTION 110

- (Exam Topic 5)

You need to evaluate your team readiness for a new GCP project. You must perform the evaluation and create a skills gap plan that incorporates the business goal of cost optimization. Your team has deployed two GCP projects successfully to date. What should you do?

- A. Allocate budget for team training
- B. Set a deadline for the new GCP project.
- C. Allocate budget for team training
- D. Create a roadmap for your team to achieve Google Cloud certification based on job role.
- E. Allocate budget to hire skilled external consultant
- F. Set a deadline for the new GCP project.
- G. Allocate budget to hire skilled external consultant
- H. Create a roadmap for your team to achieve Google Cloud certification based on job role.

Answer: B

Explanation:

https://services.google.com/fh/files/misc/cloud_center_of_excellence.pdf

NEW QUESTION 115

- (Exam Topic 5)

Your company is using Google Cloud. You have two folders under the Organization: Finance and Shopping. The members of the development team are in a Google Group. The development team group has been assigned the Project Owner role on the Organization. You want to prevent the development team from creating resources in projects in the Finance folder. What should you do?

- A. Assign the development team group the Project Viewer role on the Finance folder, and assign the development team group the Project Owner role on the Shopping folder.
- B. Assign the development team group only the Project Viewer role on the Finance folder.
- C. Assign the development team group the Project Owner role on the Shopping folder, and remove the development team group Project Owner role from the Organization.
- D. Assign the development team group only the Project Owner role on the Shopping folder.

Answer: C

Explanation:

<https://cloud.google.com/resource-manager/docs/cloud-platform-resource-hierarchy>

"Roles are always inherited, and there is no way to explicitly remove a permission for a lower-level resource that is granted at a higher level in the resource hierarchy. Given the above example, even if you were to remove the Project Editor role from Bob on the "Test GCP Project", he would still inherit that role from the "Dept Y" folder, so he would still have the permissions for that role on "Test GCP Project"."

Reference: <https://cloud.google.com/resource-manager/docs/creating-managing-folders>

NEW QUESTION 120

- (Exam Topic 5)

A small number of API requests to your microservices-based application take a very long time. You know that each request to the API can traverse many services. You want to know which service takes the longest in those cases. What should you do?

- A. Set timeouts on your application so that you can fail requests faster.
- B. Send custom metrics for each of your requests to Stackdriver Monitoring.
- C. Use Stackdriver Monitoring to look for insights that show when your API latencies are high.
- D. Instrument your application with Stackdriver Trace in order to break down the request latencies at each microservice.

Answer: D

Explanation:

<https://cloud.google.com/trace/docs/overview>

NEW QUESTION 124

- (Exam Topic 5)

You are working in a highly secured environment where public Internet access from the Compute Engine VMs is not allowed. You do not yet have a VPN connection to access an on-premises file server. You need to install specific software on a Compute Engine instance. How should you install the software?

- A. Upload the required installation files to Cloud Storage
- B. Configure the VM on a subnet with a Private Google Access subne
- C. Assign only an internal IP address to the V
- D. Download the installation files to the VM using gsutil.
- E. Upload the required installation files to Cloud Storage and use firewall rules to block all traffic except the IP address range for Cloud Storag
- F. Download the files to the VM using gsutil.
- G. Upload the required installation files to Cloud Source Repositorie
- H. Configure the VM on a subnet with a Private Google Access subne
- I. Assign only an internal IP address to the V
- J. Download the installation files to the VM using gcloud.
- K. Upload the required installation files to Cloud Source Repositories and use firewall rules to block all traffic except the IP address range for Cloud Source Repositorie
- L. Download the files to the VM using gsutil.

Answer: A

Explanation:

<https://cloud.google.com/vpc/docs/private-access-options#pga-supported>

NEW QUESTION 128

- (Exam Topic 5)

Your company wants to start using Google Cloud resources but wants to retain their on-premises Active Directory domain controller for identity management. What should you do?

- A. Use the Admin Directory API to authenticate against the Active Directory domain controller.
- B. Use Google Cloud Directory Sync to synchronize Active Directory usernames with cloud identities and configure SAML SSO.
- C. Use Cloud Identity-Aware Proxy configured to use the on-premises Active Directory domain controller as an identity provider.
- D. Use Compute Engine to create an Active Directory (AD) domain controller that is a replica of the onpremises AD domain controller using Google Cloud Directory Sync.

Answer: B

Explanation:

https://cloud.google.com/solutions/federating-gcp-with-active-directory-introduction#implementing_federation

NEW QUESTION 132

- (Exam Topic 5)

You are using Cloud CDN to deliver static HTTP(S) website content hosted on a Compute Engine instance group. You want to improve the cache hit ratio. What should you do?

- A. Customize the cache keys to omit the protocol from the key.
- B. Shorten the expiration time of the cached objects.
- C. Make sure the HTTP(S) header "Cache-Region" points to the closest region of your users.
- D. Replicate the static content in a Cloud Storage bucke
- E. Point CloudCDN toward a load balancer on thatbucke

Answer: A

Explanation:

Reference https://cloud.google.com/cdn/docs/bestpractices#using_custom_cache_keys_to_improve_cache_hit_ratio

NEW QUESTION 136

- (Exam Topic 5)

Your company places a high value on being responsive and meeting customer needs quickly. Their primary business objectives are release speed and agility. You want to reduce the chance of security errors being accidentally introduced. Which two actions can you take? Choose 2 answers

- A. Ensure every code check-in is peer reviewed by a security SME.
- B. Use source code security analyzers as part of the CI/CD pipeline.
- C. Ensure you have stubs to unit test all interfaces between components.
- D. Enable code signing and a trusted binary repository integrated with your CI/CD pipeline.
- E. Run a vulnerability security scanner as part of your continuous-integration /continuous-delivery (CI/CD) pipeline.

Answer: BE

Explanation:

<https://docs.microsoft.com/en-us/vsts/articles/security-validation-cicd-pipeline?view=vsts>

NEW QUESTION 139

- (Exam Topic 5)

You want to allow your operations learn to store togs from all the production protects in your Organization, without during logs from other projects All of the production projects are contained in a folder. You want to ensure that all logs for existing and new production projects are captured automatically. What should you do?

- A. Create an aggregated export on the Production folde
- B. Set the log sink to be a Cloud Storage bucket in an operations project
- C. Create an aggregated export on the Organization resourc
- D. Set the tog sink to be a Cloud Storage bucket in an operations project.
- E. Create log exports in the production project
- F. Set the log sinks to be a Cloud Storage bucket in an operations project.
- G. Create tog exports in the production project
- H. Set the tog sinks to be BigQuery datasets in the production projects and grant IAM access to the operations team to run queries on the datasets

Answer: B

NEW QUESTION 140

- (Exam Topic 5)

You are designing a large distributed application with 30 microservices. Each of your distributed microservices needs to connect to a database back-end. You want to store the credentials securely. Where should you store the credentials?

- A. In the source code
- B. In an environment variable
- C. In a secret management system
- D. In a config file that has restricted access through ACLs

Answer: C

Explanation:

https://cloud.google.com/docs/authentication/production#providing_credentials_to_your_application

NEW QUESTION 141

- (Exam Topic 5)

During a high traffic portion of the day, one of your relational databases crashes, but the replica is never promoted to a master. You want to avoid this in the future. What should you do?

- A. Use a different database.
- B. Choose larger instances for your database.
- C. Create snapshots of your database more regularly.
- D. Implement routinely scheduled failovers of your databases.

Answer: D

Explanation:

<https://cloud.google.com/solutions/dr-scenarios-planning-guide>

NEW QUESTION 143

- (Exam Topic 5)

Your company pushes batches of sensitive transaction data from its application server VMs to Cloud Pub/Sub for processing and storage. What is the Google-recommended way for your application to authenticate to the required Google Cloud services?

- A. Ensure that VM service accounts are granted the appropriate Cloud Pub/Sub IAM roles.
- B. Ensure that VM service accounts do not have access to Cloud Pub/Sub, and use VM access scopes to grant the appropriate Cloud Pub/Sub IAM roles.
- C. Generate an OAuth2 access token for accessing Cloud Pub/Sub, encrypt it, and store it in Cloud Storage for access from each VM.
- D. Create a gateway to Cloud Pub/Sub using a Cloud Function, and grant the Cloud Function service account the appropriate Cloud Pub/Sub IAM roles.

Answer: A

NEW QUESTION 148

- (Exam Topic 5)

You have deployed an application on Anthos clusters (formerly Anthos GKE). According to the SRE practices at your company you need to be alerted if the request latency is above a certain threshold for a specified amount of time. What should you do?

- A. Enable the Cloud Trace API on your project and use Cloud Monitoring Alerts to send an alert based on the Cloud Trace metrics
- B. Configure Anthos Config Management on your cluster and create a yaml file that defines the SLO and alerting policy you want to deploy in your cluster
- C. Use Cloud Profiler to follow up the request latency
- D. Create a custom metric in Cloud Monitoring based on the results of Cloud Profiler, and create an Alerting Policy in case this metric exceeds the threshold
- E. Install Anthos Service Mesh on your cluster
- F. Use the Google Cloud Console to define a Service Level Objective (SLO)

Answer: D

Explanation:

<https://cloud.google.com/service-mesh/docs/overview> <https://cloud.google.com/service-mesh/docs/observability/slo-overview>

NEW QUESTION 149

- (Exam Topic 5)

You have an application that makes HTTP requests to Cloud Storage. Occasionally the requests fail with HTTP status codes of 5xx and 429. How should you handle these types of errors?

- A. Use gRPC instead of HTTP for better performance.
- B. Implement retry logic using a truncated exponential backoff strategy.
- C. Make sure the Cloud Storage bucket is multi-regional for geo-redundancy.
- D. Monitor <https://status.cloud.google.com/feed.atom> and only make requests if Cloud Storage is not reporting an incident.

Answer: A

Explanation:

Reference https://cloud.google.com/storage/docs/json_api/v1/status-codes

NEW QUESTION 151

- (Exam Topic 5)

Your company is developing a web-based application. You need to make sure that production deployments are linked to source code commits and are fully auditable. What should you do?

- A. Make sure a developer is tagging the code commit with the date and time of commit
- B. Make sure a developer is adding a comment to the commit that links to the deployment.
- C. Make the container tag match the source code commit hash.
- D. Make sure the developer is tagging the commits with :latest

Answer: C

Explanation:

From: <https://cloud.google.com/architecture/best-practices-for-building-containers> Under: Tagging using the Git commit hash (bottom of page almost)

"In this case, a common way of handling version numbers is to use the Git commit SHA-1 hash (or a short version of it) as the version number. By design, the Git commit hash is immutable and references a specific version of your software.

You can use this commit hash as a version number for your software, but also as a tag for the Docker image built from this specific version of your software. Doing so makes Docker images traceable: because in this case the image tag is immutable, you instantly know which specific version of your software is running inside a given container."

NEW QUESTION 152

- (Exam Topic 5)

Your company plans to migrate a multi-petabyte data set to the cloud. The data set must be available 24hrs a day. Your business analysts have experience only with using a SQL interface. How should you store the data to optimize it for ease of analysis?

- A. Load data into Google BigQuery.
- B. Insert data into Google Cloud SQL.
- C. Put flat files into Google Cloud Storage.
- D. Stream data into Google Cloud Datastore.

Answer: A

Explanation:

Google Big Query is for multi peta byte storage , HA(High availability) which means 24 hours, SQL interface.

<https://medium.com/google-cloud/the-12-components-of-google-bigquery-c2b49829a7c7> <https://cloud.google.com/solutions/bigquery-data-warehouse>

<https://cloud.google.com/bigquery/>

BigQuery is Google's serverless, highly scalable, low cost enterprise data warehouse designed to make all your data analysts productive. Because there is no infrastructure to manage, you can focus on analyzing data to find meaningful insights using familiar SQL and you don't need a database administrator.

BigQuery enables you to analyze all your data by creating a logical data warehouse over managed, columnar storage as well as data from object storage, and spreadsheets.

References: <https://cloud.google.com/bigquery/>

NEW QUESTION 155

- (Exam Topic 5)

Your organization has decided to restrict the use of external IP addresses on instances to only approved instances. You want to enforce this requirement across all of your Virtual Private Clouds (VPCs). What should you do?

- A. Remove the default route on all VPC
- B. Move all approved instances into a new subnet that has a default route to an internet gateway.
- C. Create a new VPC in custom mode
- D. Create a new subnet for the approved instances, and set a default route to the internet gateway on this new subnet.
- E. Implement a Cloud NAT solution to remove the need for external IP addresses entirely.

- F. Set an Organization Policy with a constraint on constraints/compute.vmExternallpAcces
- G. List the approved instances in the allowedValues list.

Answer: D

Explanation:

Reference: <https://cloud.google.com/compute/docs/ip-addresses/reserve-static-external-ip-address> <https://cloud.google.com/compute/docs/ip-addresses/reserve-static-external-ip-address#disableexternalip>

you might want to restrict external IP address so that only specific VM instances can use them. This option can help to prevent data exfiltration or maintain network isolation. Using an Organization Policy, you can restrict external IP addresses to specific VM instances with constraints to control use of external IP addresses for your VM instances within an organization or a project.

NEW QUESTION 160

- (Exam Topic 5)

You want to make a copy of a production Linux virtual machine in the US-Central region. You want to manage and replace the copy easily if there are changes on the production virtual machine. You will deploy the copy as a new instances in a different project in the US-East region. What steps must you take?

- A. Use the Linux dd and netcat command to copy and stream the root disk contents to a new virtual machine instance in the US-East region.
- B. Create a snapshot of the root disk and select the snapshot as the root disk when you create a new virtual machine instance in the US-East region.
- C. Create an image file from the root disk with Linux dd command, create a new disk from the image file, and use it to create a new virtual machine instance in the US-East region
- D. Create a snapshot of the root disk, create an image file in Google Cloud Storage from the snapshot, and create a new virtual machine instance in the US-East region using the image file for the root disk.

Answer: D

Explanation:

<https://stackoverflow.com/questions/36441423/migrate-google-compute-engine-instance-to-a-different-region>

NEW QUESTION 162

- (Exam Topic 5)

Your company has an application running on Compute Engine that allows users to play their favorite music. There are a fixed number of instances. Files are stored in Cloud Storage and data is streamed directly to users. Users are reporting that they sometimes need to attempt to play popular songs multiple times before they are successful. You need to improve the performance of the application. What should you do?

- A. * 1. Copy popular songs into CloudSQL as a blob* 2. Update application code to retrieve data from CloudSQL when Cloud Storage is overloaded
- B. * 1. Create a managed instance group with Compute Engine instances* 2. Create a global load balancer and configure it with two backends* Managed instance group* Cloud Storage bucket* 3. Enable Cloud CDN on the bucket backend
- C. * 1. Mount the Cloud Storage bucket using gcsfuse on all backend Compute Engine instances* 2. Serve music files directly from the backend Compute Engine instance
- D. * 1. Create a Cloud Filestore NFS volume and attach it to the backend Compute Engine instances* 2. Download popular songs in Cloud Filestore* 3. Serve music directly from the backend Compute Engine instance

Answer: B

NEW QUESTION 163

- (Exam Topic 5)

Your operations team currently stores 10 TB of data in an object storage service from a third-party provider. They want to move this data to a Cloud Storage bucket as quickly as possible, following Google-recommended practices. They want to minimize the cost of this data migration. Which approach should they use?

- A. Use the gsutil mv command to move the data
- B. Use the Storage Transfer Service to move the data
- C. Download the data to a Transfer Appliance and ship it to Google
- D. Download the data to the on-premises data center and upload it to the Cloud Storage bucket

Answer: B

Explanation:

<https://cloud.google.com/architecture/migration-to-google-cloud-transferring-your-large-datasets#transfer-options> <https://cloud.google.com/storage-transfer-service>

NEW QUESTION 165

- (Exam Topic 5)

You need to set up Microsoft SQL Server on GCP. Management requires that there's no downtime in case of a data center outage in any of the zones within a GCP region. What should you do?

- A. Configure a Cloud SQL instance with high availability enabled.
- B. Configure a Cloud Spanner instance with a regional instance configuration.
- C. Set up SQL Server on Compute Engine, using Always On Availability Groups using Windows Failover Cluster in
- D. Place nodes in different subnets.
- E. Set up SQL Server Always On Availability Groups using Windows Failover Cluster in
- F. Place nodes in different zones.

Answer: D

Explanation:

<https://cloud.google.com/sql/docs/sqlserver/configure-ha>

NEW QUESTION 168

- (Exam Topic 5)

You are deploying a PHP App Engine Standard service with SQL as the backend. You want to minimize the number of queries to the database. What should you do?

- A. Set the memcache service level to dedicate
- B. Create a key from the hash of the query, and return database values from memcache before issuing a query to Cloud SQL.
- C. Set the memcache service level to dedicate
- D. Create a cron task that runs every minute to populate the cache with keys containing query results.
- E. Set the memcache service level to share
- F. Create a cron task that runs every minute to save all expected queries to a key called "cached-queries".
- G. Set the memcache service level to share
- H. Create a key called "cached-queries", and return database values from the key before using a query to Cloud SQL.

Answer: A

Explanation:

<https://cloud.google.com/appengine/docs/standard/php/memcache/using>

NEW QUESTION 173

- (Exam Topic 5)

Your company is using BigQuery as its enterprise data warehouse. Data is distributed over several Google Cloud projects. All queries on BigQuery need to be billed on a single project. You want to make sure that no query costs are incurred on the projects that contain the data. Users should be able to query the datasets, but not edit them.

How should you configure users' access roles?

- A. Add all users to a group
- B. Grant the group the role of BigQuery user on the billing project and BigQuery dataViewer on the projects that contain the data.
- C. Add all users to a group
- D. Grant the group the roles of BigQuery dataViewer on the billing project and BigQuery user on the projects that contain the data.
- E. Add all users to a group
- F. Grant the group the roles of BigQuery jobUser on the billing project and BigQuery dataViewer on the projects that contain the data.
- G. Add all users to a group
- H. Grant the group the roles of BigQuery dataViewer on the billing project and BigQuery jobUser on the projects that contain the data.

Answer: A

Explanation:

Reference: <https://cloud.google.com/bigquery/docs/running-queries>

NEW QUESTION 176

- (Exam Topic 5)

Your solution is producing performance bugs in production that you did not see in staging and test environments. You want to adjust your test and deployment procedures to avoid this problem in the future. What should you do?

- A. Deploy fewer changes to production.
- B. Deploy smaller changes to production.
- C. Increase the load on your test and staging environments.
- D. Deploy changes to a small subset of users before rolling out to production.

Answer: C

NEW QUESTION 179

- (Exam Topic 5)

All compute Engine instances in your VPC should be able to connect to an Active Directory server on specific ports. Any other traffic emerging from your instances is not allowed. You want to enforce this using VPC firewall rules.

How should you configure the firewall rules?

- A. Create an egress rule with priority 1000 to deny all traffic for all instance
- B. Create another egress rule with priority 100 to allow the Active Directory traffic for all instances.
- C. Create an egress rule with priority 100 to deny all traffic for all instance
- D. Create another egress rule with priority 1000 to allow the Active Directory traffic for all instances.
- E. Create an egress rule with priority 1000 to allow the Active Directory traffi
- F. Rely on the implied deny egress rule with priority 100 to block all traffic for all instances.
- G. Create an egress rule with priority 100 to allow the Active Directory traffi
- H. Rely on the implied deny egress rule with priority 1000 to block all traffic for all instances.

Answer: B

Explanation:

<https://cloud.google.com/vpc/docs/firewalls>

NEW QUESTION 180

- (Exam Topic 5)

Your web application uses Google Kubernetes Engine to manage several workloads. One workload requires a consistent set of hostnames even after pod scaling and relaunches.

Which feature of Kubernetes should you use to accomplish this?

- A. StatefulSets

- B. Role-based access control
- C. Container environment variables
- D. Persistent Volumes

Answer: A

Explanation:

<https://kubernetes.io/docs/tutorials/stateful-application/basic-stateful-set/>

NEW QUESTION 182

- (Exam Topic 5)

You are working at a financial institution that stores mortgage loan approval documents on Cloud Storage.

Any change to these approval documents must be uploaded as a separate approval file, so you want to ensure that these documents cannot be deleted or overwritten for the next 5 years. What should you do?

- A. Create a retention policy on the bucket for the duration of 5 year
- B. Create a lock on the retention policy.
- C. Create the bucket with uniform bucket-level access, and grant a service account the role of Object Write
- D. Use the service account to upload new files.
- E. Use a customer-managed key for the encryption of the bucke
- F. Rotate the key after 5 years.
- G. Create the bucket with fine-grained access control, and grant a service account the role of Object Writer. Use the service account to upload new files.

Answer: A

Explanation:

Reference: <https://cloud.google.com/storage/docs/using-bucket-lock>

NEW QUESTION 186

- (Exam Topic 5)

You have an application that runs in Google Kubernetes Engine (GKE). Over the last 2 weeks, customers have reported that a specific part of the application returns errors very frequently. You currently have no logging or monitoring solution enabled on your GKE cluster. You want to diagnose the problem, but you have not been able to replicate the issue. You want to cause minimal disruption to the application. What should you do?

- A. * 1. Update your GKE cluster to use Cloud Operations for GKE.* 2. Use the GKE Monitoring dashboard to investigate logs from affected Pods.
- B. * 1. Create a new GKE cluster with Cloud Operations for GKE enabled.* 2. Migrate the affected Pods to the new cluster, and redirect traffic for those Pods to the new cluster.* 3. Use the GKE Monitoring dashboard to investigate logs from affected Pods.
- C. * 1. Update your GKE cluster to use Cloud Operations for GKE, and deploy Prometheus.* 2. Set an alert to trigger whenever the application returns an error.
- D. * 1. Create a new GKE cluster with Cloud Operations for GKE enabled, and deploy Prometheus.* 2. Migrate the affected Pods to the new cluster, and redirect traffic for those Pods to the new cluste
- E. * 3. Set an alert to trigger whenever the application returns an error.

Answer: A

Explanation:

Reference: <https://cloud.google.com/blog/products/management-tools/using-logging-your-apps-running-kubernetes-engine>

NEW QUESTION 187

- (Exam Topic 5)

Your company is developing a new application that will allow globally distributed users to upload pictures and share them with other selected users. The application will support millions of concurrent users. You want to allow developers to focus on just building code without having to create and maintain the underlying infrastructure. Which service should you use to deploy the application?

- A. App Engine
- B. Cloud Endpoints
- C. Compute Engine
- D. Google Kubernetes Engine

Answer: A

Explanation:

Reference: <https://cloud.google.com/terms/services> <https://cloud.google.com/appengine/docs/standard/go/how-requests-are-handled>

NEW QUESTION 191

- (Exam Topic 5)

The application reliability team at your company has added a debug feature to their backend service to send all server events to Google Cloud Storage for eventual analysis. The event records are at least 50 KB and at most 15 MB and are expected to peak at 3,000 events per second. You want to minimize data loss. Which process should you implement?

- A. • Append metadata to file body. • Compress individual files. • Name files with serverName-Timestamp. • Create a new bucket if bucket is older than 1 hour and save individual files to the new bucke
- B. Otherwise, save files to existing bucket
- C. • Batch every 10,000 events with a single manifest file for metadata. • Compress event files and manifest file into a single archive file. • Name files using serverName-EventSequence. • Create a new bucket if bucket is older than 1 day and save the single archive file to the new bucke
- D. Otherwise, save the single archive file to existing bucket.
- E. • Compress individual files. • Name files with serverName-EventSequence. • Save files to one bucket • Set custom metadata headers for each object after saving.
- F. • Append metadata to file body. • Compress individual files. • Name files with a random prefix pattern. • Save files to one bucket

Answer: D

Explanation:

In order to maintain a high request rate, avoid using sequential names. Using completely random object names will give you the best load distribution. Randomness after a common prefix is effective under the prefix <https://cloud.google.com/storage/docs/request-rate>

NEW QUESTION 192

- (Exam Topic 5)

You are working at a sports association whose members range in age from 8 to 30. The association collects a large amount of health data, such as sustained injuries. You are storing this data in BigQuery. Current legislation requires you to delete such information upon request of the subject. You want to design a solution that can accommodate such a request. What should you do?

- A. Use a unique identifier for each individual
- B. Upon a deletion request, delete all rows from BigQuery with this identifier.
- C. When ingesting new data in BigQuery, run the data through the Data Loss Prevention (DLP) API to identify any personal information
- D. As part of the DLP scan, save the result to Data Catalog
- E. Upon a deletion request, query Data Catalog to find the column with personal information.
- F. Create a BigQuery view over the table that contains all data
- G. Upon a deletion request, exclude the rows that affect the subject's data from this view
- H. Use this view instead of the source table for all analysis tasks.
- I. Use a unique identifier for each individual
- J. Upon a deletion request, overwrite the column with the unique identifier with a salted SHA256 of its value.

Answer: B

Explanation:

Current legislation requires you to delete "PII" information upon request of the subject. " " So from that point of view the question is not to delete the entire user records but specific data related to personal health data. With DLP you can use InfoTypes and InfoType detectors to specifically scan for those entries and how to act upon them (link <https://cloud.google.com/dlp/docs/concepts-infotypes>)
<https://cloud.google.com/dlp#section-6>

NEW QUESTION 197

- (Exam Topic 5)

You have a Python web application with many dependencies that requires 0.1 CPU cores and 128 MB of memory to operate in production. You want to monitor and maximize machine utilization. You also to reliably deploy new versions of the application. Which set of steps should you take?

- A. Perform the following:1) Create a managed instance group with f1-micro type machines.2) Use a startup script to clone the repository, check out the production branch, install the dependencies, and start the Python app.3) Restart the instances to automatically deploy new production releases.
- B. Perform the following:1) Create a managed instance group with n1-standard-1 type machines.2) Build a Compute Engine image from the production branch that contains all of the dependencies and automatically starts the Python app.3) Rebuild the Compute Engine image, and update the instance template to deploy new production releases.
- C. Perform the following:1) Create a Kubernetes Engine cluster with n1-standard-1 type machines.2) Build a Docker image from the production branch with all of the dependencies, and tag it with the version number.3) Create a Kubernetes Deployment with the imagePullPolicy set to "IfNotPresent" in the staging namespace, and then promote it to the production namespace after testing.
- D. Perform the following:1) Create a Kubernetes Engine (GKE) cluster with n1-standard-4 type machines.2) Build a Docker image from the master branch with all of the dependencies, and tag it with "latest".3) Create a Kubernetes Deployment in the default namespace with the imagePullPolicy set to "Always". Restart the pods to automatically deploy new production releases.

Answer: D

Explanation:

<https://cloud.google.com/compute/docs/instance-templates>

NEW QUESTION 202

- (Exam Topic 5)

Your company has an application running on a deployment in a GKE cluster. You have a separate cluster for development, staging and production. You have discovered that the team is able to deploy a Docker image to the production cluster without first testing the deployment in development and then staging. You want to allow the team to have autonomy but want to prevent this from happening. You want a Google Cloud solution that can be implemented quickly with minimal effort. What should you do?

- A. Create a Kubernetes admission controller to prevent the container from starting if it is not approved for usage in the given environment
- B. Configure a Kubernetes lifecycle hook to prevent the container from starting if it is not approved for usage in the given environment
- C. Implement a corporate policy to prevent teams from deploying Docker image to an environment unless the Docker image was tested in an earlier environment
- D. Configure the binary authorization policies for the development, staging and production cluster
- E. Create attestations as part of the continuous integration pipeline

Answer: D

Explanation:

<https://cloud.google.com/architecture/prep-kubernetes-engine-for-prod#binary-authorization>

The most common Binary Authorization use cases involve attestations. An attestation certifies that a specific image has completed a previous stage, as described previously. You configure the Binary Authorization policy to verify the attestation before allowing the image to be deployed. At deploy time, instead of redoing activities that were completed in earlier stages, Binary Authorization only needs to verify the attestation. <https://cloud.google.com/binary-authorization/docs/overview>

NEW QUESTION 203

- (Exam Topic 5)

You want your Google Kubernetes Engine cluster to automatically add or remove nodes based on CPU load. What should you do?

- A. Configure a HorizontalPodAutoscaler with a target CPU usage
- B. Enable the Cluster Autoscaler from the GCP Console.
- C. Configure a HorizontalPodAutoscaler with a target CPU usage
- D. Enable autoscaling on the managed instance group for the cluster using the gcloud command.
- E. Create a deployment and set the maxUnavailable and maxSurge properties
- F. Enable the Cluster Autoscaler using the gcloud command.
- G. Create a deployment and set the maxUnavailable and maxSurge properties
- H. Enable autoscaling on the cluster managed instance group from the GCP Console.

Answer: B

NEW QUESTION 206

- (Exam Topic 5)

Your company captures all web traffic data in Google Analytics 260 and stores it in BigQuery. Each country has its own dataset. Each dataset has multiple tables. You want analysts from each country to be able to see and query only the data for their respective countries. How should you configure the access rights?

- A. Create a group per country
- B. Add analysts to their respective country-group
- C. Create a single group 'all_analysts', and add all country-groups as member
- D. Grant the 'all-analysis' group the IAM role of BigQuery jobUser
- E. Share the appropriate dataset with view access with each respective analyst country-group.
- F. Create a group per country
- G. Add analysts to their respective country-group
- H. Create a single group 'all_analysts', and add all country-groups as member
- I. Grant the 'all-analysis' group the IAM role of BigQuery jobUser
- J. Share the appropriate tables with view access with each respective analyst countrygroup.
- K. Create a group per country
- L. Add analysts to their respective country-group
- M. Create a single group 'all_analysts', and add all country-groups as member
- N. Grant the 'all-analysis' group the IAM role of BigQuery dataViewer
- O. Share the appropriate dataset with view access with each respective analyst country-group.
- P. Create a group per country
- Q. Add analysts to their respective country-group
- R. Create a single group 'all_analysts', and add all country-groups as member
- S. Grant the 'all-analysis' group the IAM role of BigQuery dataViewer
- T. Share the appropriate table with view access with each respective analyst countrygroup.

Answer: A

NEW QUESTION 208

- (Exam Topic 5)

You are configuring the cloud network architecture for a newly created project in Google Cloud that will host applications in Compute Engine. Compute Engine virtual machine instances will be created in two different subnets (sub-a and sub-b) within a single region.

- Instances in sub-a will have public IP addresses
- Instances in sub-b will have only private IP addresses

To download updated packages, instances must connect to a public repository outside the boundaries of Google Cloud. You need to allow sub-b to access the external repository. What should you do?

- A. Enable Private Google Access on sub-b
- B. Configure Cloud NAT and select sub-b in the NAT mapping section
- C. Configure a bastion host instance in sub-a to connect to instances in sub-b
- D. Enable Identity Aware Proxy for TCP forwarding for instances in sub-b

Answer: B

NEW QUESTION 212

- (Exam Topic 5)

You have deployed an application to Kubernetes Engine, and are using the Cloud SQL proxy container to make the Cloud SQL database available to the services running on Kubernetes. You are notified that the application is reporting database connection issues. Your company policies require a post-mortem. What should you do?

- A. Use gcloud sql instances restart.
- B. Validate that the Service Account used by the Cloud SQL proxy container still has the Cloud Build Editor role.
- C. In the GCP Console, navigate to Stackdriver Logging
- D. Consult logs for Kubernetes Engine and Cloud SQL.
- E. In the GCP Console, navigate to Cloud SQL
- F. Restore the latest backup
- G. Use kubectl to restart all pods.

Answer: C

NEW QUESTION 213

- (Exam Topic 5)

An application development team believes their current logging tool will not meet their needs for their new cloud-based product. They want a better tool to capture errors and help them analyze their historical log data. You want to help them find a solution that meets their needs, what should you do?

- A. Direct them to download and install the Google StackDriver logging agent.
- B. Send them a list of online resources about logging best practices.

- C. Help them define their requirements and assess viable logging tools.
- D. Help them upgrade their current tool to take advantage of any new features.

Answer: C

Explanation:

Help them define their requirements and assess viable logging tools. They know the requirements and the existing tools' problems. While it's true StackDriver Logging and Error Reporting possibly meet all their requirements, there might be other tools also meet their need. They need you to provide expertise to make assessment for new tools, specifically, logging tools that can "capture errors and help them analyze their historical log data".

References: <https://cloud.google.com/logging/docs/agent/installation>

NEW QUESTION 214

- (Exam Topic 5)

You are creating an App Engine application that uses Cloud Datastore as its persistence layer. You need to retrieve several root entities for which you have the identifiers. You want to minimize the overhead in operations performed by Cloud Datastore. What should you do?

- A. Create the Key object for each Entity and run a batch get operation
- B. Create the Key object for each Entity and run multiple get operations, one operation for each entity
- C. Use the identifiers to create a query filter and run a batch query operation
- D. Use the identifiers to create a query filter and run multiple query operations, one operation for each entity

Answer: C

Explanation:

<https://cloud.google.com/datastore/docs/concepts/entities#datastore-datastore-batch-upsert-nodejs>

NEW QUESTION 216

- (Exam Topic 5)

Your company is forecasting a sharp increase in the number and size of Apache Spark and Hadoop jobs being run on your local datacenter. You want to utilize the cloud to help you scale this upcoming demand with the least amount of operations work and code change. Which product should you use?

- A. Google Cloud Dataflow
- B. Google Cloud Dataproc
- C. Google Compute Engine
- D. Google Container Engine

Answer: B

Explanation:

Google Cloud Dataproc is a fast, easy-to-use, low-cost and fully managed service that lets you run the Apache Spark and Apache Hadoop ecosystem on Google Cloud Platform. Cloud Dataproc provisions big or small clusters rapidly, supports many popular job types, and is integrated with other Google Cloud Platform services, such as Google Cloud Storage and Stackdriver Logging, thus helping you reduce TCO.

References: <https://cloud.google.com/dataproc/docs/resources/faq>

NEW QUESTION 219

- (Exam Topic 5)

You are helping the QA team to roll out a new load-testing tool to test the scalability of your primary cloud services that run on Google Compute Engine with Cloud Bigtable. Which three requirements should they include? Choose 3 answers

- A. Ensure that the load tests validate the performance of Cloud Bigtable.
- B. Create a separate Google Cloud project to use for the load-testing environment.
- C. Schedule the load-testing tool to regularly run against the production environment.
- D. Ensure all third-party systems your services use are capable of handling high load.
- E. Instrument the production services to record every transaction for replay by the load-testing tool.
- F. Instrument the load-testing tool and the target services with detailed logging and metrics collection.

Answer: ABF

NEW QUESTION 224

- (Exam Topic 5)

Your company recently acquired a company that has infrastructure in Google Cloud. Each company has its own Google Cloud organization. Each company is using a Shared Virtual Private Cloud (VPC) to provide network connectivity for its applications. Some of the subnets used by both companies overlap. In order for both businesses to integrate, the applications need to have private network connectivity. These applications are not on overlapping subnets. You want to provide connectivity with minimal re-engineering. What should you do?

- A. Set up VPC peering and peer each Shared VPC together
- B. Configure SSH port forwarding on each application to provide connectivity between applications in the different Shared VPCs
- C. Migrate the projects from the acquired company into your company's Google Cloud organization. Relaunch the instances in your company's Shared VPC
- D. Set up a Cloud VPN gateway in each Shared VPC and peer Cloud VPNs

Answer: B

NEW QUESTION 227

- (Exam Topic 5)

Your company provides a recommendation engine for retail customers. You are providing retail customers with an API where they can submit a user ID and the API returns a list of recommendations for that user. You are responsible for the API lifecycle and want to ensure stability for your customers in case the API makes backward-incompatible changes. You want to follow Google-recommended practices. What should you do?

- A. Create a distribution list of all customers to inform them of an upcoming backward-incompatible change at least one month before replacing the old API with the new API.
- B. Create an automated process to generate API documentation, and update the public API documentation as part of the CI/CD process when deploying an update to the API.
- C. Use a versioning strategy for the APIs that increases the version number on every backward-incompatible change.
- D. Use a versioning strategy for the APIs that adds the suffix “DEPRECATED” to the current API version number on every backward-incompatible change.
- E. Use the current version number for the new API.

Answer: C

Explanation:

<https://cloud.google.com/apis/design/versioning>

All Google API interfaces must provide a major version number, which is encoded at the end of the protobuf package, and included as the first part of the URI path for REST APIs. If an API introduces a breaking change, such as removing or renaming a field, it must increment its API version number to ensure that existing user code does not suddenly break.

NEW QUESTION 228

- (Exam Topic 5)

Your company operates nationally and plans to use GCP for multiple batch workloads, including some that are not time-critical. You also need to use GCP services that are HIPAA-certified and manage service costs. How should you design to meet Google best practices?

- A. Provisioning preemptible VMs to reduce cost
- B. Discontinue use of all GCP services and APIs that are not HIPAA-compliant.
- C. Provisioning preemptible VMs to reduce cost
- D. Disable and then discontinue use of all GCP and APIs that are not HIPAA-compliant.
- E. Provision standard VMs in the same region to reduce cost
- F. Discontinue use of all GCP services and APIs that are not HIPAA-compliant.
- G. Provision standard VMs to the same region to reduce cost
- H. Disable and then discontinue use of all GCP services and APIs that are not HIPAA-compliant.

Answer: B

Explanation:

<https://cloud.google.com/security/compliance/hipaa/>

NEW QUESTION 230

- (Exam Topic 5)

Your company is designing its application landscape on Compute Engine. Whenever a zonal outage occurs, the application should be restored in another zone as quickly as possible with the latest application data. You need to design the solution to meet this requirement. What should you do?

- A. Create a snapshot schedule for the disk containing the application data
- B. Whenever a zonal outage occurs, use the latest snapshot to restore the disk in the same zone.
- C. Configure the Compute Engine instances with an instance template for the application, and use a regional persistent disk for the application data
- D. Whenever a zonal outage occurs, use the instance template to spin up the application in another zone in the same region
- E. Use the regional persistent disk for the application data.
- F. Create a snapshot schedule for the disk containing the application data
- G. Whenever a zonal outage occurs, use the latest snapshot to restore the disk in another zone within the same region.
- H. Configure the Compute Engine instances with an instance template for the application, and use a regional persistent disk for the application data
- I. Whenever a zonal outage occurs, use the instance template to spin up the application in another region
- J. Use the regional persistent disk for the application data,

Answer: B

Explanation:

Regional persistent disk is a storage option that provides synchronous replication of data between two zones in a region. Regional persistent disks can be a good building block to use when you implement HA services in Compute Engine. <https://cloud.google.com/compute/docs/disks/high-availability-regional-persistent-disk>

NEW QUESTION 234

- (Exam Topic 5)

You are migrating your on-premises solution to Google Cloud in several phases. You will use Cloud VPN to maintain a connection between your on-premises systems and Google Cloud until the migration is completed.

You want to make sure all your on-premises systems remain reachable during this period. How should you organize your networking in Google Cloud?

- A. Use the same IP range on Google Cloud as you use on-premises
- B. Use the same IP range on Google Cloud as you use on-premises for your primary IP range and use a secondary range that does not overlap with the range you use on-premises
- C. Use an IP range on Google Cloud that does not overlap with the range you use on-premises
- D. Use an IP range on Google Cloud that does not overlap with the range you use on-premises for your primary IP range and use a secondary range with the same IP range as you use on-premises

Answer: C

NEW QUESTION 237

- (Exam Topic 6)

For this question, refer to the Dress4Win case study. You are responsible for the security of data stored in Cloud Storage for your company, Dress4Win. You have already created a set of Google Groups and assigned the appropriate users to those groups. You should use Google best practices and implement the simplest design to meet the requirements.

Considering Dress4Win's business and technical requirements, what should you do?

- A. Assign custom IAM roles to the Google Groups you created in order to enforce security requirements. Encrypt data with a customer-supplied encryption key when storing files in Cloud Storage.
- B. Assign custom IAM roles to the Google Groups you created in order to enforce security requirements. Enable default storage encryption before storing files in Cloud Storage.
- C. Assign predefined IAM roles to the Google Groups you created in order to enforce security requirements. Utilize Google's default encryption at rest when storing files in Cloud Storage.
- D. Assign predefined IAM roles to the Google Groups you created in order to enforce security requirement
- E. Ensure that the default Cloud KMS key is set before storing files in Cloud Storage.

Answer: D

Explanation:

<https://cloud.google.com/iam/docs/understanding-service-accounts>

NEW QUESTION 241

- (Exam Topic 6)

For this question, refer to the Dress4Win case study. You want to ensure that your on-premises architecture meets business requirements before you migrate your solution.

What change in the on-premises architecture should you make?

- A. Replace RabbitMQ with Google Pub/Sub.
- B. Downgrade MySQL to v5.7, which is supported by Cloud SQL for MySQL.
- C. Resize compute resources to match predefined Compute Engine machine types.
- D. Containerize the micro services and host them in Google Kubernetes Engine.

Answer: C

NEW QUESTION 242

- (Exam Topic 6)

For this question, refer to the Dress4Win case study. Which of the compute services should be migrated as –is and would still be an optimized architecture for performance in the cloud?

- A. Web applications deployed using App Engine standard environment
- B. RabbitMQ deployed using an unmanaged instance group
- C. Hadoop/Spark deployed using Cloud Dataproc Regional in High Availability mode
- D. Jenkins, monitoring, bastion hosts, security scanners services deployed on custom machine types

Answer: C

NEW QUESTION 243

- (Exam Topic 7)

For this question, refer to the TerramEarth case study. You need to implement a reliable, scalable GCP solution for the data warehouse for your company, TerramEarth. Considering the TerramEarth business and technical requirements, what should you do?

- A. Replace the existing data warehouse with BigQuer
- B. Use table partitioning.
- C. Replace the existing data warehouse with a Compute Engine instance with 96 CPUs.
- D. Replace the existing data warehouse with BigQuer
- E. Use federated data sources.
- F. Replace the existing data warehouse with a Compute Engine instance with 96 CPU
- G. Add an additional Compute Engine pre-emptible instance with 32 CPUs.

Answer: C

Explanation:

https://cloud.google.com/solutions/bigquery-data-warehouse#external_sources <https://cloud.google.com/solutions/bigquery-data-warehouse>

NEW QUESTION 244

- (Exam Topic 7)

For this question, refer to the TerramEarth case study. You are asked to design a new architecture for the ingestion of the data of the 200,000 vehicles that are connected to a cellular network. You want to follow Google-recommended practices.

Considering the technical requirements, which components should you use for the ingestion of the data?

- A. Google Kubernetes Engine with an SSL Ingress
- B. Cloud IoT Core with public/private key pairs
- C. Compute Engine with project-wide SSH keys
- D. Compute Engine with specific SSH keys

Answer: A

Explanation:

<https://cloud.google.com/solutions/iot-overview> <https://cloud.google.com/iot/quotas>

NEW QUESTION 248

- (Exam Topic 7)

TerramEarth has about 1 petabyte (PB) of vehicle testing data in a private data center. You want to move the data to Cloud Storage for your machine learning team. Currently, a 1-Gbps interconnect link is available for you. The machine learning team wants to start using the data in a month. What should you do?

- A. Request Transfer Appliances from Google Cloud, export the data to appliances, and return the appliances to Google Cloud.
- B. Configure the Storage Transfer service from Google Cloud to send the data from your data center to Cloud Storage
- C. Make sure there are no other users consuming the 1 Gbps link, and use multi-thread transfer to upload the data to Cloud Storage.
- D. Export files to an encrypted USB device, send the device to Google Cloud, and request an import of the data to Cloud Storage

Answer: A

NEW QUESTION 250

- (Exam Topic 7)

For this question, refer to the TerramEarth case study.

You start to build a new application that uses a few Cloud Functions for the backend. One use case requires a Cloud Function func_display to invoke another Cloud Function func_query. You want func_query only to accept invocations from func_display. You also want to follow Google's recommended best practices. What should you do?

- A. Create a token and pass it in as an environment variable to func_displa
- B. When invoking func_query, include the token in the request Pass the same token to func_query and reject the invocation if the tokens are different.
- C. Make func_query 'Require authentication.' Create a unique service account and associate it to func_displa
- D. Grant the service account invoker role for func_quer
- E. Create an id token in func_display and include the token to the request when invoking func_query.
- F. Make func_query 'Require authentication' and only accept internal traffi
- G. Create those two functions in the same VP
- H. Create an ingress firewall rule for func_query to only allow traffic from func_display.
- I. Create those two functions in the same project and VP
- J. Make func_query only accept internal traffic.Create an ingress firewall for func_query to only allow traffic from func_displa
- K. Also, make sure both functions use the same service account.

Answer: B

Explanation:

https://cloud.google.com/functions/docs/securing/authenticating#authenticating_function_to_function_calls

NEW QUESTION 254

- (Exam Topic 7)

TerramEarth has a legacy web application that you cannot migrate to cloud. However, you still want to build a cloud-native way to monitor the application. If the application goes down, you want the URL to point to a "Site is unavailable" page as soon as possible. You also want your Ops team to receive a notification for the issue. You need to build a reliable solution for minimum cost What should you do?

- A. Create a scheduled job in Cloud Run to invoke a container every minut
- B. The container will check the application URL If the application is down, switch the URL to the "Site is unavailable" page, and notify the Ops team.
- C. Create a cron job on a Compute Engine VM that runs every minut
- D. The cron job invokes a Python program to check the application URL If the application is down, switch the URL to the "Site is unavailable" page, and notify the Ops team.
- E. Create a Cloud Monitoring uptime check to validate the application URL If it fails, put a message in a Pub/Sub queue that triggers a Cloud Function to switch the URL to the "Site is unavailable" page, and notify the Ops team.
- F. Use Cloud Error Reporting to check the application URL If the application is down, switch the URL to the "Site is unavailable" page, and notify the Ops team.

Answer: C

Explanation:

<https://cloud.google.com/blog/products/management-tools/how-to-use-pubsub-as-a-cloud-monitoring-notificatio>

NEW QUESTION 257

- (Exam Topic 7)

You have broken down a legacy monolithic application into a few containerized RESTful microservices. You want to run those microservices on Cloud Run. You also want to make sure the services are highly available with low latency to your customers. What should you do?

- A. Deploy Cloud Run services to multiple availability zone
- B. Create Cloud Endpoints that point to the service
- C. Create a global HTIP(S) Load Balancing instance and attach the Cloud Endpoints to its backend.
- D. Deploy Cloud Run services to multiple regions Create serverless network endpoint groups pointing to the service
- E. Add the serverless NE Gs to a backend service that is used by a global HTIP(S) Load Balancing instance.
- F. Cloud Run services to multiple region
- G. In Cloud DNS, create a latency-based DNS name that points to the services.
- H. Deploy Cloud Run services to multiple availability zone
- I. Create a TCP/IP global load balance
- J. Add the Cloud Run Endpoints to its backend service.

Answer: B

Explanation:

<https://cloud.google.com/run/docs/multiple-regions>

NEW QUESTION 259

- (Exam Topic 8)

For this question, refer to the Mountkirk Games case study. Mountkirk Games wants to migrate from their current analytics and statistics reporting model to one that meets their technical requirements on Google Cloud Platform.

Which two steps should be part of their migration plan? (Choose two.)

- A. Evaluate the impact of migrating their current batch ETL code to Cloud Dataflow.
- B. Write a schema migration plan to denormalize data for better performance in BigQuery.
- C. Draw an architecture diagram that shows how to move from a single MySQL database to a MySQL cluster.
- D. Load 10 TB of analytics data from a previous game into a Cloud SQL instance, and run test queries against the full dataset to confirm that they complete successfully.
- E. Integrate Cloud Armor to defend against possible SQL injection attacks in analytics files uploaded to Cloud Storage.

Answer: AB

Explanation:

https://cloud.google.com/bigquery/docs/loading-data#loading_denormalized_nested_and_repeated_data

NEW QUESTION 262

- (Exam Topic 8)

For this question, refer to the Mountkirk Games case study. You need to analyze and define the technical architecture for the compute workloads for your company, Mountkirk Games. Considering the Mountkirk Games business and technical requirements, what should you do?

- A. Create network load balancer
- B. Use preemptible Compute Engine instances.
- C. Create network load balancer
- D. Use non-preemptible Compute Engine instances.
- E. Create a global load balancer with managed instance groups and autoscaling policie
- F. Use preemptible Compute Engine instances.
- G. Create a global load balancer with managed instance groups and autoscaling policie
- H. Use non-preemptible Compute Engine instances.

Answer: D

NEW QUESTION 267

- (Exam Topic 8)

Your development team has created a mobile game app. You want to test the new mobile app on Android and iOS devices with a variety of configurations. You need to ensure that testing is efficient and cost-effective. What should you do?

- A. Upload your mobile app to the Firebase Test Lab, and test the mobile app on Android and iOS devices.
- B. Create Android and iOS VMs on Google Cloud, install the mobile app on the VMs, and test the mobile app.
- C. Create Android and iOS containers on Google Kubernetes Engine (GKE), install the mobile app on the containers, and test the mobile app.
- D. Upload your mobile app with different configurations to Firebase Hosting and test each configuration.

Answer: C

NEW QUESTION 268

- (Exam Topic 8)

Mountkirk Games wants to limit the physical location of resources to their operating Google Cloud regions. What should you do?

- A. Configure an organizational policy which constrains where resources can be deployed.
- B. Configure IAM conditions to limit what resources can be configured.
- C. Configure the quotas for resources in the regions not being used to 0.
- D. Configure a custom alert in Cloud Monitoring so you can disable resources as they are created in other regions.

Answer: A

NEW QUESTION 271

- (Exam Topic 9)

For this question, refer to the Helicopter Racing League (HRL) case study. The HRL development team releases a new version of their predictive capability application every Tuesday evening at 3 a.m. UTC to a repository. The security team at HRL has developed an in-house penetration test Cloud Function called Airwolf.

The security team wants to run Airwolf against the predictive capability application as soon as it is released every Tuesday. You need to set up Airwolf to run at the recurring weekly cadence. What should you do?

- A. Set up Cloud Tasks and a Cloud Storage bucket that triggers a Cloud Function.
- B. Set up a Cloud Logging sink and a Cloud Storage bucket that triggers a Cloud Function.
- C. Configure the deployment job to notify a Pub/Sub queue that triggers a Cloud Function.
- D. Set up Identity and Access Management (IAM) and Confidential Computing to trigger a Cloud Function.

Answer: A

NEW QUESTION 272

- (Exam Topic 9)

For this question, refer to the Helicopter Racing League (HRL) case study. Recently HRL started a new regional racing league in Cape Town, South Africa. In an effort to give customers in Cape Town a better user experience, HRL has partnered with the Content Delivery Network provider, Fastly. HRL needs to allow traffic coming from all of the Fastly IP address ranges into their Virtual Private Cloud network (VPC network). You are a member of the HRL security team and you need to configure the update that will allow only the Fastly IP address ranges through the External HTTP(S) load balancer. Which command should you use?

- A. `gcloud compute firewall rules update hlr-policy --priority 1000 \target tags-sourceiplist fastly --allow tcp:443`
- B. `gcloud compute security policies rules update 1000 --security-policy hlr-policy --expression "evaluatePreconfiguredExpr('sourceiplist-fastly')" --action " allow"`
- C. `gcloud compute firewall rules update sourceiplist-fastly \priority 1000 \allow tcp: 443`
- D. `gcloud compute priority-policies rules update 1000 \security policy from fastly--src- ip-ranges"-- action " allow"`

Answer: B

Explanation:

Reference: <https://cloud.google.com/load-balancing/docs/https> D18912E1457D5D1DDCBD40AB3BF70D5D

NEW QUESTION 276

- (Exam Topic 9)

For this question, refer to the Helicopter Racing League (HRL) case study. A recent finance audit of cloud infrastructure noted an exceptionally high number of Compute Engine instances are allocated to do video encoding and transcoding. You suspect that these Virtual Machines are zombie machines that were not deleted after their workloads completed. You need to quickly get a list of which VM instances are idle. What should you do?

- A. Log into each Compute Engine instance and collect disk, CPU, memory, and network usage statistics for analysis.
- B. Use the gcloud compute instances list to list the virtual machine instances that have the idle: true label set.
- C. Use the gcloud recommender command to list the idle virtual machine instances.
- D. From the Google Console, identify which Compute Engine instances in the managed instance groups are no longer responding to health check probes.

Answer: C

Explanation:

Reference: <https://cloud.google.com/compute/docs/instances/viewing-and-applying-idle-vm-recommendations>

NEW QUESTION 279

- (Exam Topic 10)

You need to upgrade the EHR connection to comply with their requirements. The new connection design must support business-critical needs and meet the same network and security policy requirements. What should you do?

- A. Add a new Dedicated Interconnect connection.
- B. Upgrade the bandwidth on the Dedicated Interconnect connection to 100 G.
- C. Add three new Cloud VPN connections.
- D. Add a new Carrier Peering connection.

Answer: D

NEW QUESTION 282

- (Exam Topic 10)

For this question, refer to the EHR Healthcare case study. You are responsible for designing the Google Cloud network architecture for Google Kubernetes Engine. You want to follow Google best practices. Considering the EHR Healthcare business and technical requirements, what should you do to reduce the attack surface?

- A. Use a private cluster with a private endpoint with master authorized networks configured.
- B. Use a public cluster with firewall rules and Virtual Private Cloud (VPC) routes.
- C. Use a private cluster with a public endpoint with master authorized networks configured.
- D. Use a public cluster with master authorized networks enabled and firewall rules.

Answer: A

Explanation:

<https://cloud.google.com/kubernetes-engine/docs/concepts/private-cluster-concept#overview>

NEW QUESTION 287

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

Professional-Cloud-Architect Practice Exam Features:

- * Professional-Cloud-Architect Questions and Answers Updated Frequently
- * Professional-Cloud-Architect Practice Questions Verified by Expert Senior Certified Staff
- * Professional-Cloud-Architect Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * Professional-Cloud-Architect Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The Professional-Cloud-Architect Practice Test Here](#)