

Exam Questions AZ-204

Developing Solutions for Microsoft Azure (beta)

<https://www.2passeasy.com/dumps/AZ-204/>



NEW QUESTION 1

- (Exam Topic 1)

You need to secure the Shipping Logic App. What should you use?

- A. Azure App Service Environment (ASE)
- B. Azure AD B2B integration
- C. Integration Service Environment (ISE)
- D. VNet service endpoint

Answer: C

Explanation:

Scenario: The Shipping Logic App requires secure resources to the corporate VNet and use dedicated storage resources with a fixed costing model.

You can access to Azure Virtual Network resources from Azure Logic Apps by using integration service environments (ISEs).

Sometimes, your logic apps and integration accounts need access to secured resources, such as virtual machines (VMs) and other systems or services, that are inside an Azure virtual network. To set up this access, you can create an integration service environment (ISE) where you can run your logic apps and create your integration accounts.

References:

<https://docs.microsoft.com/en-us/azure/logic-apps/connect-virtual-network-vnet-isolated-environment-overview>

NEW QUESTION 2

- (Exam Topic 1)

You need to configure Azure App Service to support the REST API requirements.

Which values should you use? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Setting	Value
Plan	<div><div>▼</div><div>Basic</div><div>Standard</div><div>Premium</div><div>Isolated</div></div>
Instance Count	<div><div>▼</div><div>1</div><div>10</div><div>20</div><div>100</div></div>

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Plan: Standard

Standard support auto-scaling Instance Count: 10

Max instances for standard is 10. Scenario:

The REST API's that support the solution must meet the following requirements:

- Allow deployment to a testing location within Azure while not incurring additional costs.
- Automatically scale to double capacity during peak shipping times while not causing application downtime.
- Minimize costs when selecting an Azure payment model. References:

<https://azure.microsoft.com/en-us/pricing/details/app-service/plans/>

NEW QUESTION 3

- (Exam Topic 1)

You need to update the APIs to resolve the testing error.

How should you complete the Azure CLI command? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

az webapp

cors

config

deployment

add

up

remove

--

slot

allowed-origins

name

http://*.wideworldimporters.com

http://test-shippingapi.wideworldimporters.com

http://test.wideworldimporters.com

http://www.wideworldimporters.com

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Enable Cross-Origin Resource Sharing (CORS) on your Azure App Service Web App.
Enter the full URL of the site you want to allow to access your WEB API or * to allow all domains. Box 1: cors
Box 2: add
Box 3: allowed-origins
Box 4: http://testwideworldimporters.com/ References:
http://donovanbrown.com/post/How-to-clear-No-Access-Control-Allow-Origin-header-error-wit
h-Azure-App-Service

NEW QUESTION 4

- (Exam Topic 1)
You need to secure the Shipping Function app.
How should you configure the app? To answer, select the appropriate options in the answer area.
NOTE: Each correct selection is worth one point.

Answer Area

Setting	Value
Authorization level	<div><div></div><div>Function</div><div>Anonymous</div><div>Admin</div></div>
User claims	<div><div></div><div>JSON Web Token (JWT)</div><div>Shared Access Signature (SAS) token</div><div>API Key</div></div>
Trigger type	<div><div></div><div>blob</div><div>HTTP</div><div>queue</div><div>timer</div></div>

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Scenario: Shipping Function app: Implement secure function endpoints by using app-level security and include Azure Active Directory (Azure AD).

Box 1: Function

Box 2: JSON based Token (JWT)

Azure AD uses JSON based tokens (JWTs) that contain claims Box 3: HTTP

How a web app delegates sign-in to Azure AD and obtains a token

User authentication happens via the browser. The OpenID protocol uses standard HTTP protocol messages. References:

<https://docs.microsoft.com/en-us/azure/active-directory/develop/authentication-scenarios>

NEW QUESTION 5

- (Exam Topic 3)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this question, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You are developing a website that will run as an Azure Web App. Users will authenticate by using their Azure Active Directory (Azure AD) credentials.

You plan to assign users one of the following permission levels for the website: admin, normal, and reader. A user's Azure AD group membership must be used to determine the permission level. You need to configure authorization.

Solution: Configure the Azure Web App for the website to allow only authenticated requests and require Azure AD log on.

Does the solution meet the goal?

A. Yes

B. No

Answer: B

Explanation:

Instead in the Azure AD application's manifest, set value of the groupMembershipClaims option to All. References:

<https://blogs.msdn.microsoft.com/waws/2017/03/13/azure-app-service-authentication-aad-groups/>

NEW QUESTION 6

- (Exam Topic 3)

You develop an app that allows users to upload photos and videos to Azure storage. The app uses a storage REST API call to upload the media to a blob storage account named Account1. You have blob storage

containers named Container1 and Container2. Uploading of videos occurs on an irregular basis.

You need to copy specific blobs from Container1 to Container2 in real time when specific requirements are met, excluding backup blob copies.

What should you do?

A. Download the blob to a virtual machine and then upload the blob to Container2.

B. Run the Azure PowerShell command Start-AzureStorageBlobCopy.

C. Copy blobs to Container2 by using the Put Blob operation of the Blob Service REST API.

D. Use AzCopy with the Snapshot switch blobs to Container2.

Answer: B

Explanation:

The Start-AzureStorageBlobCopy cmdlet starts to copy a blob. Example 1: Copy a named blob

C:\PS>Start-AzureStorageBlobCopy -SrcBlob "ContosoPlanning2015" -DestContainer "ContosoArchives"

-SrcContainer "ContosoUploads"

This command starts the copy operation of the blob named ContosoPlanning2015 from the container named ContosoUploads to the container named ContosoArchives.

References:

<https://docs.microsoft.com/en-us/powershell/module/azure.storage/start-azurestorageblobcopy?view=azurermps>

NEW QUESTION 7

- (Exam Topic 3)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

Margie's Travel is an international travel and bookings management service. The company is expanding into restaurant bookings. You are tasked with implementing Azure Search for the restaurants listed in their solution.

You create the index in Azure Search.

You need to import the restaurant data into the Azure Search service by using the Azure Search NET SDK. Solution:

* 1. Create a SearchServiceClient object to connect to the search index.

* 2. Create a DataContainer that contains the documents which must be added.

* 3. Create a DataSource instance and set its Container property to the DataContainer.

* 4. Set the DataSource property of the SearchServiceClient Does the solution meet the goal?

A. Yes

B. No

Answer: B

Explanation:

Use the following method:

* 1.Create a SearchIndexClient object to connect to the search index

* 2.Create an IndexBatch that contains the documents which must be added.

* 3. Call the Documents.Index method of the SearchIndexClient and pass the IndexBatch. References:

<https://docs.microsoft.com/en-us/azure/search/search-howto-dotnet-sdk>

NEW QUESTION 8

- (Exam Topic 3)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You are developing an Azure solution to collect point-of-sale (POS) device data from 2,000 stores located throughout the world. A single device can produce 2 megabytes (MB) of data every 24 hours. Each store location has one to five devices that send data.

You must store the device data in Azure Blob storage. Device data must be correlated based on a device identifier. Additional stores are expected to open in the future.

You need to implement a solution to receive the device data.

Solution: Provision an Azure Service Bus. Configure a topic to receive the device data by using a correlation filter.

Does the solution meet the goal?

- A. Yes
- B. No

Answer: A

Explanation:

A message is raw data produced by a service to be consumed or stored elsewhere. The Service Bus is for high-value enterprise messaging, and is used for order processing and financial transactions.

Reference:

<https://docs.microsoft.com/en-us/azure/event-grid/compare-messaging-services>

NEW QUESTION 9

- (Exam Topic 3)

You are preparing to deploy a medical records application to an Azure virtual machine (VM). The application will be deployed by using a VHD produced by an on-premises build server.

You need to ensure that both the application and related data are encrypted during and after deployment to Azure.

Which three actions should you perform in sequence? To answer, move the appropriate actions from the list of actions to the answer area and arrange them in the correct order.

Actions

- Encrypt the on-premises VHD by using BitLocker without a TPM. Upload the VM to Azure Storage.
- Run the Azure PowerShell command Set-AzureRmVMDiskEncryptionExtension.
- Run the Azure PowerShell command Set-AzureRmVMOsdisk.
- Encrypt the on-premises VHD by using BitLocker with a TPM. Upload the VM to Azure Storage.
- Run the Azure PowerShell command New-AzureRmVm.

Answer area

Encrypt the on-premises VHD by using BitLocker without a TPM. Upload the VM to Azure Storage.

Run the Azure PowerShell command Set-AzureRmVMOsdisk.

Run the Azure PowerShell command Set-AzureRmVMDiskEncryptionExtension.

➡
⬅

⬆
⬆

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Step 1: Encrypt the on-premises VHD by using BitLocker without a TPM. Upload the VM to Azure Storage Step 2: Run the Azure PowerShell command Set-AzureRMVMOSDisk

To use an existing disk instead of creating a new disk you can use the Set-AzureRMVMOSDisk command. Example:

```
$osDiskName = $vmname+'_osDisk'
```

```
$osDiskCaching = 'ReadWrite'
```

```
$osDiskVhdUri = "https://$storageName.blob.core.windows.net/vhds/" + $vmname + "_os.vhd"
```

```
$vm = Set-AzureRmVMOsdisk -VM $vm -VhdUri $osDiskVhdUri -name $osDiskName -Create Step 3: Run the Azure PowerShell command Set-AzureRmVMDiskEncryptionExtension
```

Use the Set-AzVMDiskEncryptionExtension cmdlet to enable encryption on a running IaaS virtual machine in Azure.

Incorrect:

Not TPM: BitLocker can work with or without a TPM. A TPM is a tamper resistant security chip on the system board that will hold the keys for encryption and check the integrity of the boot sequence and allows the most secure BitLocker implementation. A VM does not have a TPM.

References:

<https://www.itprotoday.com/iaaspaas/use-existing-vhd-azurerem-vm>

NEW QUESTION 10

- (Exam Topic 3)

You are implementing a software as a service (SaaS) ASP.NET Core web service that will run as an Azure Web App. The web service will use an on-premises SQL Server database for storage. The web service also includes a WebJob that processes data updates. Four customers will use the web service.

- Each instance of the WebJob processes data for a single customer and must run as a singleton instance.
- Each deployment must be tested by using deployment slots prior to serving production data.
- Azure costs must be minimized.
- Azure resources must be located in an isolated network. You need to configure the App Service plan for the Web App.

How should you configure the App Service plan? To answer, select the appropriate settings in the answer area.
NOTE: Each correct selection is worth one point.

Answer Area

App service plan setting	Value
Number of VM instances	<div><div></div><div>2</div><div>4</div><div>8</div><div>16</div></div>
Pricing tier	<div><div></div><div>Isolated</div><div>Standard</div><div>Premium</div><div>Consumption</div></div>

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Number of VM instances: 4
You are not charged extra for deployment slots. Pricing tier: Isolated
The App Service Environment (ASE) is a powerful feature offering of the Azure App Service that gives network isolation and improved scale capabilities. It is essentially a deployment of the Azure App Service into a subnet of a customer's Azure Virtual Network (VNet).
References:
<https://azure.microsoft.com/sv-se/blog/announcing-app-service-isolated-more-power-scale-and-ease-of-use/>

NEW QUESTION 10

- (Exam Topic 3)
You develop a news and blog content delivery app for Windows devices.
A notification must arrive on a user's device when there is a new article available for them to view. You need to implement push notifications.
How should you complete the code segment? To answer, select the appropriate options in the answer area.
NOTE: Each correct selection is worth one point.

Answer Area

```
string notificationHubName = "contoso_hub";
string notificationHubConnection = "connection_string";

NotificationHubClient hub =
    NotificationHubClientSettings
        NotificationHubJob
        NotificationDetails

NotificationHubClient
NotificationHubClientSettings
NotificationHubJob
NotificationDetails

GetInstallation
CreateClientFromConnectionString
CreateOrUpdateInstallation
PatchInstallation

(notificationHubConnection, notificationHubName);
string windowsToastPayload =
@"<toast><visual><binding template=""ToastText01""><text id=""1"">" +
@"New item to view" + @"</text></binding></visual></toast>";
try
{
    var result =
        await hub.
            SendWindowsNativeNotificationAsync
            SubmitNotificationHubJobAsync
            ScheduleNotificationAsync
            SendAppleNativeNotificationAsync
            (windowsToastPayload);

    . . .
}
catch (System.Exception ex)
{
    . . .
}
. . .
```

- A. Mastered
 B. Not Mastered

Answer: A

Explanation:

Box 1: NotificationHubClient

Box 2: NotificationHubClient

Box 3: CreateClientFromConnectionString

// Initialize the Notification Hub

NotificationHubClient hub = NotificationHubClient.CreateClientFromConnectionString(listenConnString, hubName);

Box 4: SendWindowsNativeNotificationAsync Send the push notification.

var result = await hub.SendWindowsNativeNotificationAsync(windowsToastPayload);

References:
<https://docs.microsoft.com/en-us/azure/notification-hubs/notification-hubs-push-notification-registration-manag>

<https://github.com/MicrosoftDocs/azure-docs/blob/master/articles/app-service-mobile/app-service-mobile-windo>

NEW QUESTION 15

- (Exam Topic 3)

You are developing an ASP.NET Core Web API web service. The web service uses Azure Application Insights for all telemetry and dependency tracking. The web service reads and writes data to a database other than Microsoft SQL Server.

You need to ensure that dependency tracking works for calls to the third-party database.

Which two Dependency Telemetry properties should you store in the database? Each correct answer presents part of the solution.

NOTE: Each correct selection is worth one point.

- A. Telemetry.Context.Operation.Id
 B. Telemetry.Context.Cloud.RoleInstance
 C. Telemetry.Id
 D. Telemetry.Context.Session.Id
 E. Telemetry.Name

Answer: AC

Explanation:

References:

<https://docs.microsoft.com/en-us/azure/azure-monitor/app/custom-operations-tracking>

NEW QUESTION 19

- (Exam Topic 3)

You are building a website to access project data related to terms within your organization. The website does not allow anonymous access. Authentication performed using an Azure Active Directory (Azure AD) app named internal.

The website has the following authentication requirements:

•Azure AD users must be able to login to the website.
•Personalization of the website must be based on membership in Active Directory groups. You need to configure the application’s manifest to meet the authentication requirements.
How should you configure the manifest? To answer, select the appropriate options in the answer area.
NOTE: Each correct selection is worth one point.

...

"appId": "d61126e3-089b-4adb-b721-d5023213df7d",

: "All",

"optionalClaims"

"groupMembershipClaims"

...

"allowPublicClient"

"oauth2Permissions"

"requiredResourceAccess"

"oauth2AllowImplicitFlow"

: true

...

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Box 1: groupMembershipClaims
Scenario: Personalization of the website must be based on membership in Active Directory groups. Group claims can also be configured in the Optional Claims section of the Application Manifest. Enable group membership claims by changing the groupMembershipClaim
The valid values are: "All" "SecurityGroup" "DistributionList" "DirectoryRole"
Box 2: oauth2Permissions
Scenario: Azure AD users must be able to login to the website.
oauth2Permissions specifies the collection of OAuth 2.0 permission scopes that the web API (resource) app exposes to client apps. These permission scopes may be granted to client apps during consent.

NEW QUESTION 23

- (Exam Topic 3)
You are a developer for a software as a service (SaaS) company that uses an Azure Function to process orders. The Azure Function currently runs on an Azure Function app that is triggered by an Azure Storage queue.
You are preparing to migrate the Azure Function to Kubernetes using Kubernetes-based Event Driven Autoscaling (KEDA).
You need to configure Kubernetes Custom Resource Definitions (CRD) for the Azure Function.
Which CRDs should you configure? To answer, drag the appropriate CRD types to the correct locations. Each CRD type may be used once, more than once, or not at all. You may need to drag the split bar between panes or scroll to view content.
NOTE: Each correct selection is worth one point.

Answer Area

CRD types	Setting	CRD type
Secret	Azure Function code	
Deployment		
ScaledObject	Polling interval	
TriggerAuthentication	Azure Storage connection string	

- A. Mastered

B. Not Mastered

Answer: A

Explanation:

Box 1: Deployment

To deploy Azure Functions to Kubernetes use the func kubernetes deploy command has several attributes that directly control how our app scales, once it is deployed to Kubernetes.

Box 2: ScaledObject

With --polling-interval, we can control the interval used by KEDA to check Azure Service Bus Queue for messages.

Example of ScaledObject with polling interval apiVersion: keda.k8s.io/v1alpha1

kind: ScaledObject metadata:

name: transformer-fn namespace: tt

labels:

deploymentName: transformer-fn spec:

scaleTargetRef: deploymentName: transformer-fn pollingInterval: 5

minReplicaCount: 0

maxReplicaCount: 100

Box 3: Secret

Store connection strings in Kubernetes Secrets. Example: to create the Secret in our demo Namespace:

```
# create the k8s demo namespace kubectl create namespace tt
```

```
# grab connection string from Azure Service Bus KEDA_SCALER_CONNECTION_STRING=$(az servicebus queue authorization-rule keys list \
```

```
-g $RG_NAME \
```

```
--namespace-name $SBN_NAME \
```

```
--queue-name inbound \
```

```
-n keda-scaler \
```

```
--query "primaryConnectionString" \
```

```
-o tsv)
```

```
# create the kubernetes secret
```

```
kubectl create secret generic tt-keda-auth \
```

```
--from-literal KedaScaler=$KEDA_SCALER_CONNECTION_STRING \
```

```
--namespace tt Reference:
```

<https://www.thinktecture.com/en/kubernetes/serverless-workloads-with-keda/>

NEW QUESTION 25

- (Exam Topic 3)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution. Determine whether the solution meets the stated goals.

You are developing and deploying several ASP.Net web applications to Azure App Service. You plan to save session state information and HTML output. You must use a storage mechanism with the following requirements:

- Share session state across all ASP.NET web applications
- Support controlled, concurrent access to the same session state data for multiple readers and a single writer
- Save full HTTP responses for concurrent requests You need to store the information.

Proposed Solution: Deploy and configure an Azure Database for PostgreSQL. Update the web applications. Does the solution meet the goal?

A. Yes

B. No

Answer: B

NEW QUESTION 27

- (Exam Topic 3)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You develop a software as a service (SaaS) offering to manage photographs. Users upload photos to a web service which then stores the photos in Azure Storage Blob storage. The storage account type is

General-purpose V2.

When photos are uploaded, they must be processed to produce and save a mobile-friendly version of the image. The process to produce a mobile-friendly version of the image must start in less than one minute.

You need to design the process that starts the photo processing.

Solution: Move photo processing to an Azure Function triggered from the blob upload. Does the solution meet the goal?

A. Yes

B. No

Answer: A

Explanation:

Azure Storage events allow applications to react to events. Common Blob storage event scenarios include image or video processing, search indexing, or any file-oriented workflow.

Events are pushed using Azure Event Grid to subscribers such as Azure Functions, Azure Logic Apps, or even to your own http listener.

Note: Only storage accounts of kind StorageV2 (general purpose v2) and BlobStorage support event integration. Storage (general purpose v1) does not support integration with Event Grid.

Reference:

<https://docs.microsoft.com/en-us/azure/storage/blobs/storage-blob-event-overview>

NEW QUESTION 29

- (Exam Topic 3)

You have a web service that is used to pay for food deliveries. The web service uses Azure Cosmos DB as the data store.

You plan to add a new feature that allows users to set a tip amount. The new feature requires that a property named tip on the document in Cosmos DB must be present and contain a numeric value.

There are many existing websites and mobile apps that use the web service that will not be updated to set the tip property for some time.

How should you complete the trigger?

NOTE: Each correct selection is worth one point.

```
function ensureTip() {
  var r = 
  var i = r.getBody();
  i["tip"] = 0;
}
```

Box 1: `getContext().getRequest();`

Box 2: `if (!("tip" in i)) {
 if (request.getValue("tip") === null){
 if (isNaN(i["tip"]) || i["tip"] === null) {
 if (typeof _pluck("tip") == 'number') {`

Box 3: `r.setBody(i);
 r.setValue(i);
 _upsertDocument(i);
 _replaceDocument(i)`

- A. Mastered
 B. Not Mastered

Answer: A

Explanation:

Box 1: `getContext().getRequest();` Box 2: `if (isNaN(i) ["tip"]) ..`

In JavaScript, there are two ways to check if a variable is a number :

`isNaN()` – Stands for “is Not a Number”, if variable is not a number, it return true, else return false. `typeof` – If variable is a number, it will returns a string named “number”.

Box 3: `r.setBody(i);`

// update the item that will be created References:

<https://docs.microsoft.com/bs-latn-ba/azure/cosmos-db/how-to-write-stored-procedures-triggers-udfs>

<https://mkyong.com/javascript/check-if-variable-is-a-number-in-javascript/>

NEW QUESTION 30

- (Exam Topic 3)

You provide an Azure API Management managed web service to clients. The back end web service implements HTTP Strict Transport Security (HSTS).

Every request to the backend service must include a valid HTTP authorization header. You need to configure the Azure API Management instance with an authentication policy. Which two policies can you use? Each correct answer presents a complete solution NOTE: Each correct selection is worth one point.

- A. Certificate Authentication
 B. Basic Authentication
 C. OAuth Client Credential Grant
 D. Digest Authentication

Answer: AC

NEW QUESTION 34

- (Exam Topic 3)

You are developing a mobile instant messaging app for a company. The mobile app must meet the following requirements:

- Support offline data sync.
- Update the latest messages during normal sync cycles. You need to implement Offline Data Sync.

Which two actions should you perform? Each correct answer presents part of the solution. NOTE: Each correct selection is worth one point.

- A. Retrieve records from Offline Data Sync on every call to the PullAsync method.
 B. Retrieve records from Offline Data Sync using an Incremental Sync.
 C. Push records to Offline Data Sync using an Incremental Sync.

- D. Return the updatedAt column from the Mobile Service Backend and implement sorting by using the column.
 E. Return the updatedAt column from the Mobile Service Backend and implement sorting by the message id.

Answer: BE

Explanation:

B: Incremental Sync: the first parameter to the pull operation is a query name that is used only on the client. If you use a non-null query name, the Azure Mobile SDK performs an incremental sync. Each time a pull operation returns a set of results, the latest updatedAt timestamp from that result set is stored in the SDK local system tables. Subsequent pull operations retrieve only records after that timestamp.

E (not D): To use incremental sync, your server must return meaningful updatedAt values and must also support sorting by this field. However, since the SDK adds its own sort on the updatedAt field, you cannot use a pull query that has its own orderBy clause.

References:

<https://docs.microsoft.com/en-us/azure/app-service-mobile/app-service-mobile-offline-data-sync>

NEW QUESTION 35

- (Exam Topic 3)

You develop an ASP.NET Core MVC application. You configure the application to track webpages and custom events.

You need to identify trends in application usage.

Which Azure Application Insights Usage Analysis features should you use? To answer, drag the appropriate features to the correct requirements. Each feature may be used once, more than once, or not at all. You may need to drag the split bar between panes or scroll to view content.

NOTE: Each correct selection is worth one point.

Requirement	Feature
Which pages visited by users most often correlate to a product purchase?	<input type="text"/>
How does load time of the product display page affect a user's decision to purchase a product?	<input type="text"/>
Which events most influence a user's decision to continue to use the application?	<input type="text"/>
Are there places in the application that users often perform repetitive actions?	<input type="text"/>

- A. Mastered
 B. Not Mastered

Answer: A

Explanation:

Box1: Users Box 2: Impact

One way to think of Impact is as the ultimate tool for settling arguments with someone on your team about how slowness in some aspect of your site is affecting whether users stick around. While users may tolerate a certain amount of slowness, Impact gives you insight into how best to balance optimization and performance to maximize user conversion.

Box 3: Retention

The retention feature in Azure Application Insights helps you analyze how many users return to your app, and how often they perform particular tasks or achieve goals. For example, if you run a game site, you could compare the numbers of users who return to the site after losing a game with the number who return after winning. This knowledge can help you improve both your user experience and your business strategy.

Box 4: User flows

The User Flows tool visualizes how users navigate between the pages and features of your site. It's great for answering questions like:

How do users navigate away from a page on your site? What do users click on a page on your site?

Where are the places that users churn most from your site?

Are there places where users repeat the same action over and over?

NEW QUESTION 40

- (Exam Topic 3)

You are configuring a development environment for your team. You deploy the latest Visual Studio image from the Azure Marketplace to your Azure subscription.

The development environment requires several software development kits (SDKs) and third-party components to support application development across the organization. You install and customize the deployed virtual machine (VM) for your development team. The customized VM must be saved to allow provisioning of a new team member development environment.

You need to save the customized VM for future provisioning.

Which tools or services should you use? To answer, select the appropriate options in the answer area. NOTE: Each correct selection is worth one point.

Answer Area

Action	Tool or service
Generalize the VM.	Azure PowerShell Visual Studio command prompt Azure Migrate Azure Backup
Store images.	Azure Blob Storage Azure Data Lake Storage Azure File Storage Azure Table Storage

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Box 1: Azure Powershell
Creating an image directly from the VM ensures that the image includes all of the disks associated with the VM, including the OS disk and any data disks. Before you begin, make sure that you have the latest version of the Azure PowerShell module. You use Sysprep to generalize the virtual machine, then use Azure PowerShell to create the image. Box 2: Azure Blob Storage
References:
<https://docs.microsoft.com/en-us/azure/virtual-machines/windows/capture-image-resource#create-an-image-of-a>

NEW QUESTION 43

- (Exam Topic 3)
A company is developing a mobile app for field service employees using Azure App Service Mobile Apps as the backend. The company's network connectivity varies throughout the day. The solution must support offline use and synchronize changes in the background when the app is online app.
You need to implement the solution.
How should you complete the code segment? To answer, select the appropriate options in the answer area.
NOTE: Each correct selection is worth one point.

```
var client = new MobileServiceClient("MOBILE_APP_URL");  
var store = new MobileServiceSQLiteStore  
(Constants.OfflineDbPath);  
store.DefineTable<ToDoItem>();  
await client.SyncContext.IntitalizeAsync(store);
```

var todoTable = client.GetSyncTable<ToDoItem>();
var todoTable = client.GetTable<ToDoItem>();
var todoTable = client.SyncTable;
var todoTable = client.Table;

```
await client.SyncContext.PushAsync();
```

await todoTable.PullAsync("allToDoItems",todoTable.CreateQuery());
await todoTable.UpdateAsync();
todoTable.PullAsync("allToDoItems", todoTable.CreateQuery());
todoTable.UpdateAsync();

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Box 1: var todoTable = client GetSyncTable<ToDoItem>()
To setup offline access, when connecting to your mobile service, use the method GetSyncTable instead of GetTable (example):
IMobileServiceSyncTable todoTable = App.MobileService.GetSyncTable(); / Box 2: await todoTable.PullAsync("allToDoItems",todo.Table.CreateQuery());
Your app should now use IMobileServiceSyncTable (instead of IMobileServiceTable) for CRUD operations. This will save changes to the local database and also keep a log of the changes. When the app is ready to synchronize its changes with the Mobile Service, use the methods PushAsync and PullAsync (example):
await App.MobileService.SyncContext.PushAsync(); await todoTable.PullAsync();

References:

<https://azure.microsoft.com/es-es/blog/offline-sync-for-mobile-services/>

NEW QUESTION 44

- (Exam Topic 3)

You develop a serverless application using several Azure Functions. These functions connect to data from within the code.

You want to configure tracing for an Azure Function App project. You need to change configuration settings in the hostjson file. Which tool should you use?

- A. Azure portal
- B. Azure PowerShell
- C. Azure Functions Core Tools (Azure CLI)
- D. Visual Studio

Answer: A

Explanation:

The function editor built into the Azure portal lets you update the function.json file and the code file for a function. The host.json file, which contains some runtime-specific configurations, is in the root folder of the function app.

References:

<https://docs.microsoft.com/en-us/azure/azure-functions/functions-reference#fileupdate>

NEW QUESTION 46

- (Exam Topic 3)

You are writing code to create and run an Azure Batch job. You have created a pool of compute nodes.

You need to choose the right class and its method to submit a batch job to the Batch service. Which method should you use?

- A. JobOperations.CreateJobO
- B. CloudJob.Enable(IEnumerable<BatchClientBehavior>)
- C. CloudJob.CommitAsync(IEnumerable<BatchClientBehavior>, CancellationToken)
- D. JobOperations.EnableJob(String, IEnumerable<BatchClientBehavior>)
- E. JobOperations.EnableJobAsync(Strin
- F. IEnumerable<BatchClientBehavior>. CancellationToken)

Answer: C

Explanation:

A Batch job is a logical grouping of one or more tasks. A job includes settings common to the tasks, such as priority and the pool to run tasks on. The app uses the BatchClient.JobOperations.CreateJob method to create a job on your pool.

The Commit method submits the job to the Batch service. Initially the job has no tasks.

```
{
CloudJob job = batchClient.JobOperations.CreateJob(); job.Id = JobId;
job.PoolInformation = new PoolInformation { PoolId = PoolId }; job.Commit();
}
```

References:

<https://docs.microsoft.com/en-us/azure/batch/quick-run-dotnet>

NEW QUESTION 47

- (Exam Topic 3)

A company uses Azure SQL Database to store data for an app. The data includes sensitive information.

You need to implement measures that allow only members of the managers group to see sensitive information. Which two actions should you perform? Each correct answer presents part of the solution.

NOTE: Each correct selection is worth one point.

- A. Include the managers group.
- B. Exclude the managers group.
- C. Exclude the administrators group.
- D. Navigate to the following URL:
`PUT https://management.azure.com/subscriptions/00000000-1111-2222-3333-444444444444
/resourceGroups/rg01/providers/Microsoft.Sql/servers/server01/databases/customers
/transparentDataEncryption/current?api-version=2014-04-01`
- E. Run the following Azure PowerShell command:
`New-AzureRmSqlDatabaseDataMaskingRule -SchemaName "dbo" -TableName "customers" '
-ColumnName "ssn" -MaskingFunction "Default"`

- A. Option A
- B. Option B
- C. Option C
- D. Option D
- E. Option E

Answer: BE

Explanation:

Dynamic data masking helps prevent unauthorized access to sensitive data by enabling customers to designate how much of the sensitive data to reveal with minimal impact on the application layer.

SQL users excluded from masking - A set of SQL users or AAD identities that get unmasked data in the SQL query results.

Note: The New-AzureRmSqlDatabaseDataMaskingRule cmdlet creates a data masking rule for an Azure SQL database.

References:

<https://docs.microsoft.com/en-us/powershell/module/azurermsql/new-azurermsqldatabasedatamaskingrule?view>

NEW QUESTION 48

- (Exam Topic 3)

You are developing a software solution for an autonomous transportation system. The solution uses large data sets and Azure Batch processing to simulate navigation sets for entire fleets of vehicles.

You need to create compute nodes for the solution on Azure Batch. What should you do?

- A. In the Azure portal, create a Batch account.
- B. In a .NET method, call the method: BatchClient.PoolOperations.CreatePool
- C. In Python, implement the class: JobAddParameter
- D. In Python, implement the class: TaskAddParameter

Answer: B

Explanation:

A Batch job is a logical grouping of one or more tasks. A job includes settings common to the tasks, such as priority and the pool to run tasks on. The app uses the BatchClient.JobOperations.CreateJob method to create a job on your pool.

NEW QUESTION 51

- (Exam Topic 3)

A company runs an international travel and bookings management service. The company plans to begin offering restaurant bookings. You must develop a solution that uses Azure Search and meets the following requirements:

- Users must be able to search for restaurants by name, description, location, and cuisine.
- Users must be able to narrow the results further by location, cuisine, rating, and family-friendliness.
- All words in descriptions must be included in searches. You need to add annotations to the restaurant class.

How should you complete the code segment? To answer, select the appropriate options in the answer area. NOTE: Each correct selection is worth one point.

```
[SerializePropertyNameAsCamelCase]
public class Restaurant
{
    [Key, IsFilterable]
    public int RestaurantId { get; set; }
    [IsSearchable, IsFilterable, IsSortable]
    public string Name { get; set; }

    [IsSearchable.IsFilterable.IsSortable, IsFacetable]
    [IsFilterable.IsFacetable, Required]
    [IsSearchable]
    [IsSearchable, Required]

    public string location { get; set; }
    public string Phone { get; set; }

    [Required]
    [IsSearchable]
    [IsFilterable, IsFacetable, Required]
    [IsFilterable, IsFacetable, IsSortable]

    public string Description { get; set; }

    [IsFilterable, IsSortable, IsSearchable]
    [IsFilterable, IsSortable, IsFacetable]
    [IsFilterable, IsSortable, Key]
    [IsFilterable, IsSortable, IsSearchable, Required]

    public double Rating { get; set; }

    [IsSearchable, IsFilterable, IsFacetable]
    [IsFilterable, IsSortable, Key]
    [IsFilterable, IsSortable, IsSearchable]
    [IsFilterable, IsSortable, Key, Required]

    public List<string> Cuisines { get; set; }

    [IsFilterable, IsSortable, Key, Required]
    [IsSearchable, IsSortable, IsFacetable]
    [IsFilterable, IsSortable, Key, IsSearchable]
    [IsFilterable, IsFacetable]

    public bool FamilyFriendly { get; set; }
}
```

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Box 1: [IsSearchable.IsFilterable.IsSortable,IsFacetable] Location

Users must be able to search for restaurants by name, description, location, and cuisine.

Users must be able to narrow the results further by location, cuisine, rating, and family-friendliness. Box 2: [IsSearchable.IsFilterable.IsSortable,Required]

Description

Users must be able to search for restaurants by name, description, location, and cuisine. All words in descriptions must be included in searches.

Box 3: [IsFilterable,IsSortable,IsFaceTable] Rating

Users must be able to narrow the results further by location, cuisine, rating, and family-friendliness. Box 4: [IsSearchable.IsFilterable,IsFacetable]

Cuisines

Users must be able to search for restaurants by name, description, location, and cuisine.

Users must be able to narrow the results further by location, cuisine, rating, and family-friendliness. Box 5: [IsFilterable,IsFacetable]

FamilyFriendly

Users must be able to narrow the results further by location, cuisine, rating, and family-friendliness. References:

<https://www.henkboelman.com/azure-search-the-basics/>

NEW QUESTION 56

- (Exam Topic 3)

You develop an Azure web app. You monitor performance of the web app by using Application Insights. You need to ensure the cost for Application Insights does not exceed a preset budget. What should you do?

- A. Implement ingestion sampling using the Azure portal.
- B. Set a daily cap for the Application Insights instance.
- C. Implement adaptive sampling using the Azure portal.
- D. Implement adaptive sampling using the Application Insights SDK.
- E. Implement ingestion sampling using the Application Insights SDK.

Answer: D

Explanation:

Sampling is an effective way to reduce charges and stay within your monthly quota.

You can set sampling manually, either in the portal on the Usage and estimated costs page; or in the ASP.NET SDK in the .config file; or in the Java SDK in the ApplicationInsights.xml file, to also reduce the network traffic.

Adaptive sampling is the default for the ASP.NET SDK. Adaptive sampling automatically adjusts to the volume of telemetry that your app sends. It operates automatically in the SDK in your web app so that telemetry traffic on the network is reduced.

References:

<https://docs.microsoft.com/en-us/azure/azure-monitor/app/sampling>

NEW QUESTION 61

- (Exam Topic 3)

You plan to create a Docker image that runs as ASP.NET Core application named ContosoApp. You have a setup script named setupScript.ps1 and a series of application files including ContosoApp.dll.

You need to create a Dockerfile document that meets the following requirements:

- Call setupScript.ps1 when the container is built.
- Run ContosoApp.dll when the container starts.

The Docker document must be created in the same folder where ContosoApp.dll and setupScript.ps1 are stored.

Which four commands should you use to develop the solution? To answer, move the appropriate commands from the list of commands to the answer area and arrange them in the correct order.

Commands

Answer Area

RUN powershell .\setupScript.ps1
CMD ["dotnet", "ContosoApp.dll"]

EXPOSE ./ContosoApp/ /apps/ContosoApp

COPY /.

FROM microsoft/aspnetcore:2.0

WORKDIR /apps/ContosoApp

CMD powershell .\setupScript.ps1
ENTRYPOINT ["dotnet", "ContosoApp.dll"]



- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Step 1: WORKDIR /apps/ContosoApp Step 2: COPY ./The Docker document must be created in the same folder where ContosoApp.dll and setupScript.ps1 are stored.
Step 3: EXPOSE ./ContosApp/ /app/ContosoApp Step 4: CMD powershell ./setupScript.ps1 ENTRYPOINT ["dotnet", "ContosoApp.dll"]
You need to create a Dockerfile document that meets the following requirements:
> Call setupScript.ps1 when the container is built.
> Run ContosoApp.dll when the container starts. References:
<https://docs.microsoft.com/en-us/azure/app-service/containers/tutorial-custom-docker-image>

NEW QUESTION 64

- (Exam Topic 3)
You are working for Contoso, Ltd.
You define an API Policy object by using the following XML markup:

```
<set-variable name= "bodySize" value="@ (context.Request.Headers["Content-Length"] [0])"/>  
<choose>  
  <when condition= "@ (int.Parse(context.Variables.GetValueOrDefault<string> ("bodySize"))<512000)">  
</when>  
<otherwise>  
  <rewrite-uri template= "/put"/>  
  <set-backend-service base-url= "http://contoso.com/api/9.1"/>  
</otherwise>  
</choose>
```

For each of the following statements, select Yes if the statement is true. Otherwise, select No.
NOTE: Each correct selection is worth one point.

Answer Area

Statement	Yes	No
The XML segment belongs in the <inbound> section of the policy.	<input type="radio"/>	<input type="radio"/>
If the body size is >256k, an error will occur.	<input type="radio"/>	<input type="radio"/>
If the request is http://contoso.com/api/9.2/, the policy will retain the higher version.	<input type="radio"/>	<input type="radio"/>

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Box 1: Yes
Use the set-backend-service policy to redirect an incoming request to a different backend than the one specified in the API settings for that operation. Syntax: <set-backend-service base-url="base URL of the backend service" />
Box 2: No
The condition is on 512k, not on 256k. Box 3: No
The set-backend-service policy changes the backend service base URL of the incoming request to the one specified in the policy.
Reference:
<https://docs.microsoft.com/en-us/azure/api-management/api-management-transformation-policies>

NEW QUESTION 67

- (Exam Topic 3)
You are developing an application. You have an Azure user account that has access to two subscriptions. You need to retrieve a storage account key secret from Azure Key Vault.
In which order should you arrange the PowerShell commands to develop the solution? To answer, move all commands from the list of commands to the answer area and arrange them in the correct order.

Powershell commands

Answer Area

```
$secretvalue = ConvertTo-SecureString
$storAcctkey -AsPlainText
-Force
Set-AzKeyVaultSecret -VaultName
$vaultName -Name $secretName
-SecretValue $secretvalue
```

```
Get-AzStorageAccountKey -
ResourceGroupName $resGroup -Name
$storAcct
```

```
Set-AzContext -SubscriptionId
$subscriptionID
```

```
Get-AzKeyVaultSecret -VaultName
$vaultName
```

```
Get-AzSubscription
```



- A. Mastered
 B. Not Mastered

Answer: A

Explanation:

Step 1: Get-AzSubscription

If you have multiple subscriptions, you might have to specify the one that was used to create your key vault. Enter the following to see the subscriptions for your account:

Get-AzSubscription

Step 2: Set-AzContext -SubscriptionId

To specify the subscription that's associated with the key vault you'll be logging, enter: Set-AzContext -SubscriptionId <subscriptionID>

Step 3: Get-AzStorageAccountKey You must get that storage account key.

Step 4: \$secretvalue = ConvertTo-SecureString <storageAccountKey> -AsPlainText -Force

Set-AzKeyVaultSecret -VaultName <vaultName> -Name <secretName> -SecretValue \$secretvalue After retrieving your secret (in this case, your storage account key), you must convert that key to a secure string, and then create a secret with that value in your key vault.

Step 5: Get-AzKeyVaultSecret

Next, get the URI for the secret you created. You'll need this URI in a later step to call the key vault and retrieve your secret. Run the following PowerShell command and make note of the ID value, which is the secret's URI:

Get-AzKeyVaultSecret -VaultName <vaultName> Reference:

<https://docs.microsoft.com/bs-latn-ba/Azure/key-vault/key-vault-key-rotation-log-monitoring>

NEW QUESTION 68

- (Exam Topic 3)

You plan to deploy a web app to App Service on Linux. You create an App Service plan. You create and push a custom Docker image that image that contains the web app to Azure Container Registry.

You need to access the console logs generated from inside the container in real-time.

How should you complete the Azure CLI command? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

az webapp log

config

download

show

tail

filesystem

--web-server-logging

--docker-container-logging

--application-logging

az

webapp

acr

aks

config

download

show

tail

- A. Mastered
 B. Not Mastered

Answer: A

Explanation:

Box 1: config

To Configure logging for a web app use the command: az webapp log config

Box 2: --docker-container-logging Syntax include:

az webapp log config [--docker-container-logging {filesystem, off}]

Box 3: webapp

To download a web app's log history as a zip file use the command: az webapp log download

Box 4: download References:

<https://docs.microsoft.com/en-us/cli/azure/webapp/log>

NEW QUESTION 72

- (Exam Topic 3)

You plan to deploy a new application to a Linux virtual machine (VM) that is hosted in Azure.

The entire VM must be secured at rest by using industry-standard encryption technology to address organizational security and compliance requirements.

You need to configure Azure Disk Encryption for the VM.

How should you complete the Azure Cli commands? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer Area

```
az provider register -n Microsoft.KeyVault
resourcegroup="myResourceGroup"
az group create --name $resourcegroup --location westus
keyvault_name=myvaultname$RANDOM
az 
vm 
keyvault 
keyvault key 
vm encryption 
az 
vm 
keyvault 
keyvault key 
vm encryption 
az 
vm 
keyvault 
keyvault key 
vm encryption 
az 
vm 
keyvault 
keyvault key 
vm encryption 
--volume-type 
all
data
os
```

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Box 1: keyvault

Create an Azure Key Vault with az keyvault create and enable the Key Vault for use with disk encryption. Specify a unique Key Vault name for keyvault_name as follows:

```
keyvault_name=myvaultname$RANDOM az keyvault create \  
--name $keyvault_name \  
--resource-group $resourcegroup \  
--location eastus \  
--enabled-for-disk-encryption True
```

Box 2: keyvault key

The Azure platform needs to be granted access to request the cryptographic keys when the VM boots to decrypt the virtual disks. Create a cryptographic key in your Key Vault with az keyvault key create. The following example creates a key named myKey:

```
az keyvault key create \  
--vault-name $keyvault_name \  
--name myKey \  
--protection software
```

Box 3: vm

Create a VM with az vm create. Only certain marketplace images support disk encryption. The following example creates a VM named myVM using an Ubuntu 16.04 LTS image:

```
az vm create \  
--resource-group $resourcegroup \  
--name myVM \  
--image Canonical:UbuntuServer:16.04-LTS:latest \  
--admin-username azureuser \  
--generate-ssh-keys
```

Box 4: vm encryption

Encrypt your VM with az vm encryption enable: az vm encryption enable \

```
--resource-group $resourcegroup \  
--name myVM \  
--disk-encryption-keyvault $keyvault_name \  
--key-encryption-key myKey \  
--volume-type all
```

Note: seems to an error in the question. Should have enable instead of create. Box 5: all

Encrypt both data and operating system.

References:

<https://docs.microsoft.com/bs-latn-ba/azure/virtual-machines/linux/encrypt-disks>

NEW QUESTION 74

- (Exam Topic 3)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution. Determine whether the solution meets the stated goals.

You are developing and deploying several ASP.Net web applications to Azure App Service. You plan to save session state information and HTML output. You must use a storage mechanism with the following requirements:

- Share session state across all ASP.NET web applications
- Support controlled, concurrent access to the same session state data for multiple readers and a single writer
- Save full HTTP responses for concurrent requests You need to store the information.

Proposed Solution: Deploy and configure Azure Cache for Redis. Update the web applications.

Does the solution meet the goal?

- A. Yes
- B. No

Answer: B

NEW QUESTION 76

- (Exam Topic 3)

You develop a solution that uses an Azure SQL Database to store user information for a mobile app. The app stores sensitive information about users.

You need to hide sensitive information from developers that query the data for the mobile app.

Which three items must you identify when configuring dynamic data masking? Each correct answer presents a part of the solution.

NOTE: Each correct selection is worth one point.

- A. Column
- B. Table
- C. Trigger
- D. Index
- E. Schema

Answer: ABE

Explanation:

In the Dynamic Data Masking configuration page, you may see some database columns that the recommendations engine has flagged for masking. In order to accept the recommendations, just click Add Mask for one or more columns and a mask is created based on the default type for this column. You can change the masking function by clicking on the masking rule and editing the masking field format to a different format of your choice.

Dynamic Data Masking

demo_database

Save
 Discard
 Add Mask

Downlevel clients require the use of Security Enabled Connection Strings.

Masking Rules

MASK NAME	MASK FUNCTION
You haven't created any masking rules.	

SQL users excluded from masking (administrators are always excluded)

Recommended fields to mask

SCHEMA	TABLE	COLUMN	
SalesLT	Customer	FirstName	
SalesLT	Customer	LastName	
SalesLT	Customer	EmailAddress	
SalesLT	Customer	Phone	
SalesLT	CustomerAddress	AddressID	

References:

<https://docs.microsoft.com/en-us/azure/sql-database/sql-database-dynamic-data-masking-get-started-portal>

NEW QUESTION 78

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual AZ-204 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the AZ-204 Product From:

<https://www.2passeasy.com/dumps/AZ-204/>

Money Back Guarantee

AZ-204 Practice Exam Features:

- * AZ-204 Questions and Answers Updated Frequently
- * AZ-204 Practice Questions Verified by Expert Senior Certified Staff
- * AZ-204 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * AZ-204 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year