

Exam Questions DVA-C02

DVA-C02

<https://www.2passeasy.com/dumps/DVA-C02/>



NEW QUESTION 1

A data visualization company wants to strengthen the security of its core applications. The applications are deployed on AWS across its development, staging, pre-production, and production environments. The company needs to encrypt all of its stored sensitive credentials. The sensitive credentials need to be automatically rotated. A version of the sensitive credentials needs to be stored for each environment. Which solution will meet these requirements in the MOST operationally efficient way?

- A. Configure AWS Secrets Manager versions to store different copies of the same credentials across multiple environments.
- B. Create a new parameter version in AWS Systems Manager Parameter Store for each environment. Store the environment-specific credentials in the parameter version.
- C. Configure the environment variables in the application code. Use different names for each environment type. Store the environment-specific credentials in the secret.
- D. Configure AWS Secrets Manager to create a new secret for each environment type.

Answer: D

Explanation:

AWS Secrets Manager is the best option for managing sensitive credentials across multiple environments, as it provides automatic secret rotation, auditing, and monitoring features. It also allows storing environment-specific credentials in separate secrets, which can be accessed by the applications using the SDK or CLI. AWS Systems Manager Parameter Store does not have built-in secret rotation capability, and it requires creating individual parameters or storing the entire credential set as a JSON object. Configuring the environment variables in the application code is not a secure or scalable solution, as it exposes the credentials to anyone who can access the code. References

? AWS Secrets Manager vs. Systems Manager Parameter Store

? AWS Systems Manager Parameter Store vs. Secrets Manager vs. Environment Variables in Lambda, when to use which

? AWS Secrets Manager vs. Parameter Store: Features, Cost & More

NEW QUESTION 2

A developer wants to add request validation to a production environment Amazon API Gateway API. The developer needs to test the changes before the API is deployed to the production environment. For the test, the developer will send test requests to the API through a testing tool. Which solution will meet these requirements with the LEAST operational overhead?

- A. Export the existing API to an OpenAPI file.
- B. Create a new API. Modify the new API to add request validation.
- C. Import the OpenAPI file.
- D. Perform the test.
- E. Modify the existing API to add request validation.
- F. Deploy the existing API to production.
- G. Modify the existing API to add request validation.
- H. Deploy the updated API to a new API Gateway stage.
- I. Perform the test.
- J. Deploy the updated API to the API Gateway production stage.
- K. Create a new API.
- L. Add the necessary resources and methods, including new request validation.
- M. Perform the test.
- N. Modify the existing API to add request validation.
- O. Deploy the existing API to production.
- P. Clone the existing API.
- Q. Modify the new API to add request validation.
- R. Perform the test.
- S. Modify the existing API to add request validation.
- T. Deploy the existing API to production.

Answer: B

Explanation:

Amazon API Gateway allows you to create, deploy, and manage a RESTful API to expose backend HTTP endpoints, AWS Lambda functions, or other AWS services¹. You can use API Gateway to perform basic validation of an API request before proceeding with the integration request¹. When the validation fails, API Gateway immediately fails the request, returns a 400 error response to the caller, and publishes the validation results in CloudWatch Logs¹.

To test changes before deploying to a production environment, you can modify the existing API to add request validation and deploy the updated API to a new API Gateway stage¹. This allows you to perform tests without affecting the production environment. Once testing is complete and successful, you can then deploy the updated API to the API Gateway production stage¹.

This approach has the least operational overhead as it avoids unnecessary creation of new APIs or exporting and importing of APIs. It leverages the existing infrastructure and only requires changes in the configuration of the existing API¹.

NEW QUESTION 3

A developer is creating a mobile app that calls a backend service by using an Amazon API Gateway REST API. For integration testing during the development phase, the developer wants to simulate different backend responses without invoking the backend service. Which solution will meet these requirements with the LEAST operational overhead?

- A. Create an AWS Lambda function.
- B. Use API Gateway proxy integration to return constant HTTP responses.
- C. Create an Amazon EC2 instance that serves the backend REST API by using an AWS CloudFormation template.
- D. Customize the API Gateway stage to select a response type based on the request.
- E. Use a request mapping template to select the mock integration response.

Answer: D

Explanation:

Amazon API Gateway supports mock integration responses, which are predefined responses that can be returned without sending requests to a backend service. Mock integration responses can be used for testing or prototyping purposes, or for simulating different backend responses based on certain conditions. A request

mapping template can be used to select a mock integration response based on an expression that evaluates some aspects of the request, such as headers, query strings, or body content. This solution does not require any additional resources or code changes and has the least operational overhead. Reference: Set up mock integrations for an API Gateway REST API

<https://docs.aws.amazon.com/apigateway/latest/developerguide/how-to-mock-integration.html>

NEW QUESTION 4

A developer is deploying a company's application to Amazon EC2 instances. The application generates gigabytes of data files each day. The files are rarely accessed but the files must be available to the application's users within minutes of a request during the first year of storage. The company must retain the files for 7 years.

How can the developer implement the application to meet these requirements MOST cost-effectively?

- A. Store the files in an Amazon S3 bucket. Use the S3 Glacier Instant Retrieval storage class. Create an S3 Lifecycle policy to transition the files to the S3 Glacier Deep Archive storage class after 1 year.
- B. Store the files in an Amazon S3 bucket.
- C. Use the S3 Standard storage class.
- D. Create an S3 Lifecycle policy to transition the files to the S3 Glacier Flexible Retrieval storage class after 1 year.
- E. Store the files on an Amazon Elastic Block Store (Amazon EBS) volume. Use Amazon Data Lifecycle Manager (Amazon DLM) to create snapshots of the EBS volumes and to store those snapshots in Amazon S3.
- F. Store the files on an Amazon Elastic File System (Amazon EFS) mount.
- G. Configure EFS lifecycle management to transition the files to the EFS Standard-Infrequent Access (Standard-IA) storage class after 1 year.

Answer: A

Explanation:

Amazon S3 Glacier Instant Retrieval is an archive storage class that delivers the lowest-cost storage for long-lived data that is rarely accessed and requires retrieval in

milliseconds. With S3 Glacier Instant Retrieval, you can save up to 68% on storage costs compared to using the S3 Standard-Infrequent Access (S3 Standard-IA) storage class, when your data is accessed once per quarter. <https://aws.amazon.com/s3/storage-classes/glacier/instant-retrieval/>

NEW QUESTION 5

A company is using AWS CloudFormation to deploy a two-tier application. The application will use Amazon RDS as its backend database. The company wants a solution that will randomly generate the database password during deployment. The solution also must automatically rotate the database password without requiring changes to the application.

What is the MOST operationally efficient solution that meets these requirements?

- A. Use an AWS Lambda function as a CloudFormation custom resource to generate and rotate the password.
- B. Use an AWS Systems Manager Parameter Store resource with the SecureString data type to generate and rotate the password.
- C. Use a cron daemon on the application's host to generate and rotate the password.
- D. Use an AWS Secrets Manager resource to generate and rotate the password.

Answer: D

Explanation:

This solution will meet the requirements by using AWS Secrets Manager, which is a service that helps protect secrets such as database credentials by encrypting them with AWS Key Management Service (AWS KMS) and enabling automatic rotation of secrets. The developer can use an AWS Secrets Manager resource in an AWS CloudFormation template, which enables creating and managing secrets as part of a CloudFormation stack. The developer can use an `AWS::SecretsManager::Secret` resource type to generate and rotate the password for accessing RDS database during deployment. The developer can also specify a `RotationSchedule` property for the secret resource, which defines how often to rotate the secret and which Lambda function to use for rotation logic. Option A is not optimal because it will use an AWS Lambda function as a CloudFormation custom resource, which may introduce additional complexity and overhead for creating and managing a custom resource and implementing rotation logic. Option B is not optimal because it will use an AWS Systems Manager Parameter Store resource with the SecureString data type, which does not support automatic rotation of secrets. Option C is not optimal because it will use a cron daemon on the application's host to generate and rotate the password, which may incur more costs and require more maintenance for running and securing a host.

References: [AWS Secrets Manager], [AWS::SecretsManager::Secret]

NEW QUESTION 6

An Amazon Kinesis Data Firehose delivery stream is receiving customer data that contains personally identifiable information. A developer needs to remove pattern-based customer identifiers from the data and store the modified data in an Amazon S3 bucket.

What should the developer do to meet these requirements?

- A. Implement Kinesis Data Firehose data transformation as an AWS Lambda function.
- B. Configure the function to remove the customer identifier.
- C. Set an Amazon S3 bucket as the destination of the delivery stream.
- D. Launch an Amazon EC2 instance.
- E. Set the EC2 instance as the destination of the delivery stream.
- F. Run an application on the EC2 instance to remove the customer identifier.
- G. Store the transformed data in an Amazon S3 bucket.
- H. Create an Amazon OpenSearch Service instance.
- I. Set the OpenSearch Service instance as the destination of the delivery stream.
- J. Use search and replace to remove the customer identifier.
- K. Export the data to an Amazon S3 bucket.
- L. Create an AWS Step Functions workflow to remove the customer identifier.
- M. As the last step in the workflow, store the transformed data in an Amazon S3 bucket.
- N. Set the workflow as the destination of the delivery stream.

Answer: A

Explanation:

Amazon Kinesis Data Firehose is a service that delivers real-time streaming data to destinations such as Amazon S3, Amazon Redshift, Amazon OpenSearch

Service, and Amazon Kinesis Data Analytics. The developer can implement Kinesis Data Firehose data transformation as an AWS Lambda function. The function can remove pattern-based customer identifiers from the data and return the modified data to Kinesis Data Firehose. The developer can set an Amazon S3 bucket as the destination of the delivery stream. References:

? [What Is Amazon Kinesis Data Firehose? - Amazon Kinesis Data Firehose]

? [Data Transformation - Amazon Kinesis Data Firehose]

NEW QUESTION 7

A developer has been asked to create an AWS Lambda function that is invoked any time updates are made to items in an Amazon DynamoDB table. The function has been created and appropriate permissions have been added to the Lambda execution role Amazon DynamoDB streams have been enabled for the table, but the function is still not being

invoked.
Which option would enable DynamoDB table updates to invoke the Lambda function?

- A. Change the StreamViewType parameter value to NEW_AND_OLD_IMAGES for the DynamoDB table.
- B. Configure event source mapping for the Lambda function.
- C. Map an Amazon Simple Notification Service (Amazon SNS) topic to the DynamoDB streams.
- D. Increase the maximum runtime (timeout) setting of the Lambda function.

Answer: B

Explanation:

This solution allows the Lambda function to be invoked by the DynamoDB stream whenever updates are made to items in the DynamoDB table. Event source mapping is a feature of Lambda that enables a function to be triggered by an event source, such as a DynamoDB stream, an Amazon Kinesis stream, or an Amazon Simple Queue Service (SQS) queue. The developer can configure event source mapping for the Lambda function using the AWS Management Console, the AWS CLI, or the AWS SDKs. Changing the StreamViewType parameter value to NEW_AND_OLD_IMAGES for the DynamoDB table will not affect the invocation of the Lambda function, but only change the information that is written to the stream record. Mapping an Amazon Simple Notification Service (Amazon SNS) topic to the DynamoDB stream will not invoke the Lambda function directly, but require an additional subscription from the Lambda function to the SNS topic. Increasing the maximum runtime (timeout) setting of the Lambda function will not affect the invocation of the Lambda function, but only change how long the function can run before it is terminated.

Reference: [Using AWS Lambda with Amazon DynamoDB], [Using AWS Lambda with Amazon SNS]

NEW QUESTION 8

An online sales company is developing a serverless application that runs on AWS. The application uses an AWS Lambda function that calculates order success rates and stores the data in an Amazon DynamoDB table. A developer wants an efficient way to invoke the Lambda function every 15 minutes.

Which solution will meet this requirement with the LEAST development effort?

- A. Create an Amazon EventBridge rule that has a rate expression that will run the rule every 15 minute
- B. Add the Lambda function as the target of the EventBridge rule.
- C. Create an AWS Systems Manager document that has a script that will invoke the Lambda function on Amazon EC2. Use a Systems Manager Run Command task to run the shell script every 15 minutes.
- D. Create an AWS Step Functions state machine
- E. Configure the state machine to invoke the Lambda function execution role at a specified interval by using a Wait state
- F. Set the interval to 15 minutes.
- G. Provision a small Amazon EC2 instance
- H. Set up a cron job that invokes the Lambda function every 15 minutes.

Answer: A

Explanation:

The best solution for this requirement is option A. Creating an Amazon EventBridge rule that has a rate expression that will run the rule every 15 minutes and adding the Lambda function as the target of the EventBridge rule is the most efficient way to invoke the Lambda function periodically. This solution does not require any additional resources or development effort, and it leverages the built-in scheduling capabilities of EventBridge.

NEW QUESTION 9

A developer is creating a mobile application that will not require users to log in. What is the MOST efficient method to grant users access to AWS resources?

- A. Use an identity provider to securely authenticate with the application.
- B. Create an AWS Lambda function to create an IAM user when a user accesses the application.
- C. Create credentials using AWS KMS and apply these credentials to users when using the application.
- D. Use Amazon Cognito to associate unauthenticated users with an IAM role that has limited access to resources.

Answer: D

Explanation:

This solution is the most efficient method to grant users access to AWS resources without requiring them to log in. Amazon Cognito is a service that provides user sign-up, sign-in, and access control for web and mobile applications. Amazon Cognito identity pools support both authenticated and unauthenticated users. Unauthenticated users receive access to your AWS resources even if they aren't logged in with any of your identity providers (IdPs). You can use Amazon Cognito to associate unauthenticated users with an IAM role that has limited access to resources, such as Amazon S3 buckets or DynamoDB tables. This degree of access is useful to display content to users before they log in or to allow them to perform certain actions without signing up. Using an identity provider to securely authenticate with the application will require users to log in, which does not meet the requirement. Creating an AWS Lambda function to create an IAM user when a user accesses the application will incur unnecessary costs and complexity, and may pose security risks if not implemented properly. Creating credentials using AWS KMS and applying them to users when using the application will also incur unnecessary costs and complexity, and may not provide fine-grained access control for resources.

Reference: Switching unauthenticated users to authenticated users (identity pools), Allow user access to your API without authentication (Anonymous user access)

NEW QUESTION 10

A company is using an AWS Lambda function to process records from an Amazon Kinesis data stream. The company recently observed slow processing of the records. A developer notices that the iterator age metric for the function is increasing and that the Lambda run duration is constantly above normal.

Which actions should the developer take to increase the processing speed? (Choose two.)

- ☐ Increase the number of shards of the Kinesis data stream.
- ☐ A: Decrease the timeout of the Lambda function.
- ☐ C: Increase the memory that is allocated to the Lambda function.
- ☐ D: Decrease the number of shards of the Kinesis data stream.
- ☐ E: Increase the timeout of the Lambda function.

Answer: AC

Explanation:

Increasing the number of shards of the Kinesis data stream will increase the throughput and parallelism of the data processing. Increasing the memory that is allocated to the Lambda function will also increase the CPU and network performance of the function, which will reduce the run duration and improve the processing speed. Option B is not correct because decreasing the timeout of the Lambda function will not affect the processing speed, but may cause some records to fail if they exceed the timeout limit. Option D is not correct because decreasing the number of shards of the Kinesis data stream will decrease the throughput and parallelism of the data processing, which will slow down the processing speed. Option E is not correct because increasing the timeout of the Lambda function will not affect the processing speed, but may increase the cost of running the function.

References: [Amazon Kinesis Data Streams Scaling], [AWS Lambda Performance Tuning]

NEW QUESTION 10

A developer is creating an AWS Lambda function that consumes messages from an Amazon Simple Queue Service (Amazon SQS) standard queue. The developer notices that the Lambda function processes some messages multiple times.

How should developer resolve this issue MOST cost-effectively?

- ☐ A. Change the Amazon SQS standard queue to an Amazon SQS FIFO queue by using the Amazon SQS message deduplication ID.
- ☐ B. Set up a dead-letter queue.
- ☐ C. Set the maximum concurrency limit of the AWS Lambda function to 1
- ☐ D. Change the message processing to use Amazon Kinesis Data Streams instead of Amazon SQS.

Answer: A

Explanation:

Amazon Simple Queue Service (Amazon SQS) is a fully managed queue service that allows you to de-couple and scale for applications¹. Amazon SQS offers two types of queues: Standard and FIFO (First In First Out) queues¹. The FIFO queue uses

the messageDeduplicationId property to treat messages with the same value as duplicate².

Therefore, changing the Amazon SQS standard queue to an Amazon SQS FIFO queue using the Amazon SQS message deduplication ID can help resolve the issue of the Lambda function processing some messages multiple times. Therefore, option A is correct.

NEW QUESTION 15

A developer has an application that makes batch requests directly to Amazon DynamoDB by using the BatchGetItem low-level API operation. The responses frequently return values in the UnprocessedKeys element.

Which actions should the developer take to increase the resiliency of the application when the batch response includes values in UnprocessedKeys? (Choose two.)

- ☐ A. Retry the batch operation immediately.
- ☐ B. Retry the batch operation with exponential backoff and randomized delay.
- ☐ C. Update the application to use an AWS software development kit (AWS SDK) to make the requests.
- ☐ D. Increase the provisioned read capacity of the DynamoDB tables that the operation accesses.
- ☐ E. Increase the provisioned write capacity of the DynamoDB tables that the operation accesses.

Answer: BC

Explanation:

The UnprocessedKeys element indicates that the BatchGetItem operation did not process all of the requested items in the current response. This can happen if the

response size limit is exceeded or if the table's provisioned throughput is exceeded. To handle this situation, the developer should retry the batch operation with exponential backoff and randomized delay to avoid throttling errors and reduce the load on the table. The developer should also use an AWS SDK to make the requests, as the SDKs automatically retry requests that return UnprocessedKeys.

References:

? [BatchGetItem - Amazon DynamoDB]

? [Working with Queries and Scans - Amazon DynamoDB]

? [Best Practices for Handling DynamoDB Throttling Errors]

NEW QUESTION 18

A developer is using AWS Step Functions to automate a workflow The workflow defines each step as an AWS Lambda function task The developer notices that runs of the Step Functions state machine fail in the GetResource task with either an UlegalArgumentException error or a TooManyRequestsException error The developer wants the state machine to stop running when the state machine encounters an UlegalArgumentException error. The state machine needs to retry the GetResource task one additional time after 10 seconds if the state machine encounters a TooManyRequestsException error. If the second attempt fails, the developer wants the state machine to stop running.

How can the developer implement the Lambda retry functionality without adding unnecessary complexity to the state machine'?

- ☐ A. Add a Delay task after the GetResource tas
- ☐ B. Add a catcher to the GetResource tas
- ☐ C. Configure the catcher with an error type of TooManyRequestsExceptio
- ☐ D. Configure the next step to be the Delay task Configure the Delay task to wait for an interval of 10 seconds Configure the next step to be the GetResource task.
- ☐ E. Add a catcher to the GetResource task Configure the catcher with an error type of TooManyRequestsExceptio
- ☐ F. an interval of 10 seconds, and a maximum attempts value of 1. Configure the next step to be the GetResource task.
- ☐ G. Add a retrier to the GetResource task Configure the retrier with an error type of TooManyRequestsException, an interval of 10 seconds, and a maximum attempts value of 1.
- ☐ H. Duplicate the GetResource task Rename the new GetResource task to TryAgain Add a catcher to the original GetResource task

Configure the catcher with an error type of TooManyRequestsExceptio
I. Configure the next step to be TryAgain.

Answer: C

Explanation:

The best way to implement the Lambda retry functionality is to use the Retry field in the state definition of the GetResource task. The Retry field allows the developer to specify an array of retriers, each with an error type, an interval, and a maximum number of attempts. By setting the error type to TooManyRequestsException, the interval to 10 seconds, and the maximum attempts to 1, the developer can achieve the desired behavior of retrying the GetResource task once after 10 seconds if it encounters a TooManyRequestsException error. If the retry fails, the state machine will stop running. If the GetResource task encounters an UlegalArgumentException error, the state machine will also stop running without retrying, as this error type is not specified in the Retry field. References
? Error handling in Step Functions
? Handling Errors, Retries, and adding Alerting to Step Function State Machine Executions
? The Jitter Strategy for Step Functions Error Retries on the New Workflow Studio

NEW QUESTION 19

A company receives food orders from multiple partners. The company has a microservices application that uses Amazon API Gateway APIs with AWS Lambda integration. Each partner sends orders by calling a customized API that is exposed through API Gateway. The API call invokes a shared Lambda function to process the orders.

Partners need to be notified after the Lambda function processes the orders. Each partner must receive updates for only the partner's own orders. The company wants to add new partners in the future with the fewest code changes possible.

Which solution will meet these requirements in the MOST scalable way?

- A. Create a different Amazon Simple Notification Service (Amazon SNS) topic for each partne
- B. Configure the Lambda function to publish messages for each partner to the partner's SNS topic.
- C. Create a different Lambda function for each partne
- D. Configure the Lambda function to notify each partner's service endpoint directly.
- E. Create an Amazon Simple Notification Service (Amazon SNS) topi
- F. Configure the Lambda function to publish messages with specific attributes to the SNS topi
- G. Subscribe each partner to the SNS topi
- H. Apply the appropriate filter policy to the topic subscriptions.
Create one Amazon Simple Notification Service (Amazon SNS) topi
- I. Subscribe all partners to the SNS topic.

Answer: C

Explanation:

Amazon Simple Notification Service (Amazon SNS) is a fully managed messaging service that enables pub/sub communication between distributed systems. The developer can create an SNS topic and configure the Lambda function to publish messages with specific attributes to the topic. The developer can subscribe each partner to the SNS topic and apply the appropriate filter policy to the topic subscriptions. This way, each partner will receive updates for only their own orders based on the message attributes. This solution will meet the requirements in the most scalable way and allow adding new partners in the future with minimal code changes.

References:

- ? [Amazon Simple Notification Service (SNS)]
- ? [Filtering Messages with Attributes - Amazon Simple Notification Service]

NEW QUESTION 21

A company has an application that runs as a series of AWS Lambda functions. Each Lambda function receives data from an Amazon Simple Notification Service (Amazon SNS) topic and writes the data to an Amazon Aurora DB instance.

To comply with an information security policy, the company must ensure that the Lambda functions all use a single securely encrypted database connection string to access Aurora.

Which solution will meet these requirements'?

- A. Use IAM database authentication for Aurora to enable secure database connections for ail the Lambda functions.
- B. Store the credentials and read the credentials from an encrypted Amazon RDS DB instance.
- C. Store the credentials in AWS Systems Manager Parameter Store as a secure string parameter.
- D. Use Lambda environment variables with a shared AWS Key Management Service (AWS KMS) key for encryption.

Answer: A

Explanation:

This solution will meet the requirements by using IAM database authentication for Aurora, which enables using IAM roles or users to authenticate with Aurora databases instead of using passwords or other secrets. The developer can use IAM database authentication for Aurora to enable secure database connections for all the Lambda functions that access Aurora DB instance. The developer can create an IAM role with permission to connect to Aurora DB instance and attach it to each Lambda function. The developer can also configure Aurora DB instance to use IAM database authentication and enable encryption in transit using SSL certificates. This way, the Lambda functions can use a single securely encrypted database connection string to access Aurora without needing any secrets or passwords. Option B is not optimal because it will store the credentials and read them from an encrypted Amazon RDS DB instance, which may introduce additional costs and complexity for managing and accessing another RDS DB instance. Option C is not optimal because it will store the credentials in AWS Systems Manager Parameter Store as a secure string parameter, which may require additional steps or permissions to retrieve and decrypt the credentials from Parameter Store. Option D is not optimal because it will use Lambda environment variables with a shared AWS Key Management Service (AWS KMS) key for encryption, which may not be secure or scalable as environment variables are stored as plain text unless encrypted with AWS KMS. References: [IAM Database Authentication for MySQL and PostgreSQL], [Using SSL/TLS to Encrypt a Connection to a DB Instance]

NEW QUESTION 24

A company is building a web application on AWS. When a customer sends a request, the application will generate reports and then make the reports available to the customer within one hour. Reports should be accessible to the customer for 8 hours. Some reports are larger than 1 MB. Each report is unique to the customer. The application should delete all reports that are older than 2 days.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Generate the reports and then store the reports as Amazon DynamoDB items that have a specified TTL
- B. Generate a URL that retrieves the reports from DynamoDB
- C. Provide the URL to customers through the web application.
- D. Generate the reports and then store the reports in an Amazon S3 bucket that uses server-side encryption
- E. Attach the reports to an Amazon Simple Notification Service (Amazon SNS) message
- F. Subscribe the customer to email notifications from Amazon SNS.
- G. Generate the reports and then store the reports in an Amazon S3 bucket that uses server-side encryption
- H. Generate a presigned URL that contains an expiration date Provide the URL to customers through the web application
- I. Add S3 Lifecycle configuration rules to the S3 bucket to delete old reports.
- J. Generate the reports and then store the reports in an Amazon RDS database with a date stamp
- K. Generate a URL that retrieves the reports from the RDS database
- L. Provide the URL to customers through the web application
- M. Schedule an hourly AWS Lambda function to delete database records that have expired date stamps.

Answer: C

Explanation:

This solution will meet the requirements with the least operational overhead because it uses Amazon S3 as a scalable, secure, and durable storage service for the reports. The presigned URL will allow customers to access their reports for a limited time (8 hours) without requiring additional authentication. The S3 Lifecycle configuration rules will automatically delete the reports that are older than 2 days, reducing storage costs and complying with the data retention policy. Option A is not optimal because it will incur additional costs and complexity to store the reports as DynamoDB items, which have a size limit of 400 KB. Option B is not optimal because it will not provide customers with access to their reports within one hour, as Amazon SNS email delivery is not guaranteed. Option D is not optimal because it will require more operational overhead to manage an RDS database and a Lambda function for storing and deleting the reports.

References: Amazon S3 Presigned URLs, Amazon S3 Lifecycle

NEW QUESTION 25

A company is migrating an on-premises database to Amazon RDS for MySQL. The company has read-heavy workloads. The company wants to refactor the code to achieve optimum read performance for queries.

Which solution will meet this requirement with LEAST current and future effort?

- A. Use a multi-AZ Amazon RDS deployment
- B. Increase the number of connections that the code makes to the database or increase the connection pool size if a connection pool is in use.
- C. Use a multi-AZ Amazon RDS deployment
- D. Modify the code so that queries access the secondary RDS instance.
- E. Deploy Amazon RDS with one or more read replicas
- F. Modify the application code so that queries use the URL for the read replicas.
- G. Use open source replication software to create a copy of the MySQL database on an Amazon EC2 instance
- H. Modify the application code so that queries use the IP address of the EC2 instance.

Answer: C

Explanation:

Amazon RDS for MySQL supports read replicas, which are copies of the primary database instance that can handle read-only queries. Read replicas can improve the read performance of the database by offloading the read workload from the primary instance and distributing it across multiple replicas. To use read replicas, the application code needs to be modified to direct read queries to the URL of the read replicas, while write queries still go to the URL of the primary instance. This solution requires less current and future effort than using a multi-AZ deployment, which does not provide read scaling benefits, or using open source replication software, which requires additional configuration and maintenance. Reference: Working with read replicas

NEW QUESTION 30

A company has a web application that runs on Amazon EC2 instances with a custom Amazon Machine Image (AMI) The company uses AWS CloudFormation to provision the application The application runs in the us-east-1 Region, and the company needs to deploy the application to the us-west-1 Region

An attempt to create the AWS CloudFormation stack in us-west-1 fails. An error message states that the AMI ID does not exist. A developer must resolve this error with a solution that uses the least amount of operational overhead

Which solution meets these requirements?

- A. Change the AWS CloudFormation templates for us-east-1 and us-west-1 to use an AWS AMI
- B. Relaunch the stack for both Regions.
- C. Copy the custom AMI from us-east-1 to us-west-1. Update the AWS CloudFormation template for us-west-1 to refer to AMI ID for the copied AMI Relaunch the stack
- D. Build the custom AMI in us-west-1 Create a new AWS CloudFormation template to launch the stack in us-west-1 with the new AMI ID
- E. Manually deploy the application outside AWS CloudFormation in us-west-1.

Answer: B

Explanation:

<https://aws.amazon.com/blogs/aws/ec2-ami-copy-between-regions/>

NEW QUESTION 34

A company has an application that stores data in Amazon RDS instances. The application periodically experiences surges of high traffic that cause performance problems.

During periods of peak traffic, a developer notices a reduction in query speed in all database queries.

The team's technical lead determines that a multi-threaded and scalable caching solution should be used to offload the heavy read traffic. The solution needs to improve performance.

Which solution will meet these requirements with the LEAST complexity?

- A. Use Amazon ElastiCache for Memcached to offload read requests from the main database.
- B. Replicate the data to Amazon DynamoDB
- C. Set up a DynamoDB Accelerator (DAX) cluster.

- D. Configure the Amazon RDS instances to use Multi-AZ deployment with one standby instance.
- E. Offload read requests from the main database to the standby instance.
- F. Use Amazon ElastiCache for Redis to offload read requests from the main database.

Answer: A

Explanation:

? Amazon ElastiCache for Memcached is a fully managed, multithreaded, and scalable in-memory key-value store that can be used to cache frequently accessed data and improve application performance¹. By using Amazon ElastiCache for Memcached, the developer can reduce the load on the main database and handle high traffic surges more efficiently.

? To use Amazon ElastiCache for Memcached, the developer needs to create a cache cluster with one or more nodes, and configure the application to store and retrieve data from the cache cluster². The developer can use any of the supported Memcached clients to interact with the cache cluster³. The developer can also use Auto Discovery to dynamically discover and connect to all cache nodes in a cluster⁴.

? Amazon ElastiCache for Memcached is compatible with the Memcached protocol, which means that the developer can use existing tools and libraries that work with

Memcached¹. Amazon ElastiCache for Memcached also supports data partitioning, which allows the developer to distribute data among multiple nodes and scale out the cache cluster as needed.

? Using Amazon ElastiCache for Memcached is a simple and effective solution that meets the requirements with the least complexity. The developer does not need to change the database schema, migrate data to a different service, or use a different caching model. The developer can leverage the existing Memcached ecosystem and easily integrate it with the application.

NEW QUESTION 38

A developer is trying get data from an Amazon DynamoDB table called demoman-table. The developer configured the AWS CLI to use a specific IAM user's credentials and ran the following command.

```
aws dynamodb get-item --table-name demoman-table --key '{"id": {"N": "1993"}}'
```

The command returned errors and no rows were returned. What is the MOST likely cause of these issues?

- A. The command is incorrect; it should be rewritten to use put-item with a string argument
- B. The developer needs to log a ticket with AWS Support to enable access to the demoman-table
- C. Amazon DynamoDB cannot be accessed from the AWS CLI and needs to be called via the REST API
- D. The IAM user needs an associated policy with read access to demoman-table

Answer: D

Explanation:

This solution will most likely solve the issues because it will grant the IAM user the necessary permission to access the DynamoDB table using the AWS CLI command. The error message indicates that the IAM user does not have sufficient access rights to perform the scan operation on the table. Option A is not optimal because it will change the command to use put-item instead of scan, which will not achieve the desired result of getting data from the table. Option B is not optimal because it will involve contacting AWS Support, which may not be necessary or efficient for this issue. Option C is not optimal because it will state that DynamoDB cannot be accessed from the AWS CLI, which is incorrect as DynamoDB supports AWS CLI commands.

References: AWS CLI for DynamoDB, [IAM Policies for DynamoDB]

NEW QUESTION 40

A developer is building a serverless application by using AWS Serverless Application Model (AWS SAM) on multiple AWS Lambda functions.

When the application is deployed, the developer wants to shift 10% of the traffic to the new deployment of the application for the first 10 minutes after deployment. If there are no issues, all traffic must switch over to the new version.

Which change to the AWS SAM template will meet these requirements?

- A. Set the Deployment Preference Type to Canary10Percent10Minute
AutoPublishAlias property to the Lambda alias.
- B. Set the Deployment Preference Type to Linear10PercentEvery10Minute
- C. Set the Deployment Preference Type to Canary10Percent10Minute
- D. Set AutoPublishAlias property to the Lambda alias.
- E. Set the Deployment Preference Type to Canary10Percent10Minute
- F. Set the PreTraffic and PostTraffic properties to the Lambda alias.
- G. Set the Deployment Preference Type to Linear10PercentEvery10Minute
- H. Set PreTraffic and Post Traffic properties to the Lambda alias.

Answer: A

Explanation:

The AWS Serverless Application Model (AWS SAM) comes built-in with CodeDeploy to provide gradual AWS Lambda deployments¹.

The DeploymentPreference property in AWS SAM allows you to specify the type of deployment that you want. The Canary10Percent10Minutes option means that 10 percent of your customer traffic is immediately shifted to your new version. After 10 minutes, all traffic is shifted to the new version¹. The AutoPublishAlias property in AWS SAM allows AWS SAM to automatically create an alias that points to the updated version of the Lambda function¹. Therefore, option A is correct.

NEW QUESTION 44

A developer has an application that is composed of many different AWS Lambda functions. The Lambda functions all use some of the same dependencies. To avoid security issues the developer is constantly updating the dependencies of all of the Lambda functions. The result is duplicated effort to reach function.

How can the developer keep the dependencies of the Lambda functions up to date with the LEAST additional complexity?

- A. Define a maintenance window for the Lambda functions to ensure that the functions get updated copies of the dependencies.
- B. Upgrade the Lambda functions to the most recent runtime version.
- C. Define a Lambda layer that contains all of the shared dependencies.
- D. Use an AWS CodeCommit repository to host the dependencies in a centralized location.

Answer: C

Explanation:

This solution allows the developer to keep the dependencies of the Lambda functions up to date with the least additional complexity because it eliminates the need to update each function individually. A Lambda layer is a ZIP archive that contains libraries, custom runtimes, or other dependencies. The developer can create a layer that contains all of the shared dependencies and attach it to multiple Lambda functions. When the developer updates the layer, all of the functions that use the layer will have access to the latest version of the dependencies.

Reference: [AWS Lambda layers]

NEW QUESTION 45

A company wants to deploy and maintain static websites on AWS. Each website's source code is hosted in one of several version control systems, including AWS CodeCommit, Bitbucket, and GitHub.

The company wants to implement phased releases by using development, staging, user acceptance testing, and production environments in the AWS Cloud. Deployments to each environment must be started by code merges on the relevant Git branch. The company wants to use HTTPS for all data exchange. The company needs a solution that does not require servers to run continuously.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Host each website by using AWS Amplify with a serverless backen
- B. Conned the repository branches that correspond to each of the desired environment
- C. Start deployments by merging code changes to a desired branch.
- D. Host each website in AWS Elastic Beanstalk with multiple environment
- E. Use the EB CLI to link each repository branc
- F. Integrate AWS CodePipeline to automate deployments from version control code merges.
- G. Host each website in different Amazon S3 buckets for each environmen
- H. Configure AWS CodePipeline to pull source code from version contro
- I. Add an AWS CodeBuild stage to copy source code to Amazon S3.
- J. Host each website on its own Amazon EC2 instanc
- K. Write a custom deployment script to bundle each website's static asset
- L. Copy the assets to Amazon EC2. Set up a workflow to run the script when code is merged.

Answer: A

Explanation:

AWS Amplify is a set of tools and services that enables developers to build and deploy full-stack web and mobile applications that are powered by AWS. AWS Amplify supports hosting static websites on Amazon S3 and Amazon CloudFront, with HTTPS enabled by default. AWS Amplify also integrates with various version control systems, such as AWS CodeCommit, Bitbucket, and GitHub, and allows developers to connect different branches to different environments. AWS Amplify automatically builds and deploys the website whenever code changes are merged to a connected branch, enabling phased releases with minimal operational overhead. Reference: AWS Amplify Console

NEW QUESTION 48

A company is migrating legacy internal applications to AWS. Leadership wants to rewrite the internal employee directory to use native AWS services. A developer needs to create a solution for storing employee contact details and high-resolution photos for use with the new application.

Which solution will enable the search and retrieval of each employee's individual details and high-resolution photos using AWS APIs?

- A. Encode each employee's contact information and photos using Base64. Store the information in an Amazon DynamoDB table using a sort key.
- B. Store each employee's contact information in an Amazon DynamoDB table along with the object keys for the photos stored in Amazon S3.
- C. Use Amazon Cognito user pools to implement the employee directory in a fully managed software-as-a-service (SaaS) method.
- D. Store employee contact information in an Amazon RDS DB instance with the photos stored in Amazon Elastic File System (Amazon EFS).

Answer: B

Explanation:

Amazon DynamoDB is a fully managed NoSQL database service that provides fast and consistent performance with seamless scalability. The developer can store each employee's contact information in a DynamoDB table along with the object keys for the photos stored in Amazon S3. Amazon S3 is an object storage service that offers industry-leading scalability, data availability, security, and performance. The developer can use AWS APIs to search and retrieve the employee details and photos from DynamoDB and S3.

References:

? [Amazon DynamoDB]

? [Amazon Simple Storage Service (S3)]

NEW QUESTION 52

A company runs a batch processing application by using AWS Lambda functions and Amazon API Gateway APIs with deployment stages for development, user acceptance testing and production A development team needs to configure the APIs in the deployment stages to connect to third-party service endpoints.

Which solution will meet this requirement?

- A. Store the third-party service endpoints in Lambda layers that correspond to the stage
- B. Store the third-party service endpoints in API Gateway stage variables that correspond to the stage
- C. Encode the third-party service endpoints as query parameters in the API Gateway request URL.
- D. Store the third-party service endpoint for each environment in AWS AppConfig

Answer: B

Explanation:

API Gateway stage variables are name-value pairs that can be defined as configuration attributes associated with a deployment stage of a REST API. They act like environment variables and can be used in the API setup and mapping templates. For example, the development team can define a stage variable named endpoint and assign it different values for each stage, such as dev.example.com for development, uat.example.com for user acceptance testing, and prod.example.com for production. Then, the team can use the stage variable value in the integration request URL, such as `http://{ stageVariables.endpoint}/api`. This way, the team can use the same API setup with different endpoints at each stage by resetting the stage variable value. The other solutions are either not feasible or not cost-effective. Lambda layers are used to package and load dependencies for Lambda functions, not for storing endpoints. Encoding the endpoints as query parameters would expose them to the public and make the request URL unnecessarily long. Storing the endpoints in AWS AppConfig would incur additional costs and complexity, and would require additional logic to retrieve the values from the configuration store. References

? Using Amazon API Gateway stage variables

? Setting up stage variables for a REST API deployment

? Setting stage variables using the Amazon API Gateway console

NEW QUESTION 55

A developer wants to add request validation to a production environment Amazon API Gateway API. The developer needs to test the changes before the API is deployed to the production environment. For the least the developer will send test requests to the API through a testing tool. Which solution will meet these requirements with the LEAST operational overhead?

- A. Export the existing API to an OpenAPI file
 - B. Create a new API Import the OpenAPI file Modify the new API to add request validation
 - C. Perform the tests Modify the existing API to add request validation
 - D. Deploy the existing API to production.
 - E. Modify the existing API to add request validation
 - F. Deploy the updated API to a new API Gateway stage Perform the tests Deploy the updated API to the API Gateway production stage.
 - G. Create a new API Add the necessary resources and methods including new request validation
 - H. Perform the tests Modify the existing API to add request validation
 - I. Deploy the existing API to production.
 - J. Clone the existing API Modify the new API to add request validation
 - K. Perform the tests
- Modify the existing API to add request validation Deploy the existing API to production.

Answer: D

Explanation:

This solution allows the developer to test the changes without affecting the production environment. Cloning an API creates a copy of the API definition that can be modified independently. The developer can then add request validation to the new API and test it using a testing tool. After verifying that the changes work as expected, the developer can apply the same changes to the existing API and deploy it to production.

Reference: Clone an API, [Enable Request Validation for an API in API Gateway]

NEW QUESTION 57

A company is expanding the compatibility of its photo-sharing mobile app to hundreds of additional devices with unique screen dimensions and resolutions. Photos are stored in Amazon S3 in their original format and resolution. The company uses an Amazon CloudFront distribution to serve the photos. The app includes the dimension and resolution of the display as GET parameters with every request.

A developer needs to implement a solution that optimizes the photos that are served to each device to reduce load time and increase photo quality.

Which solution will meet these requirements MOST cost-effectively?

- A. Use S3 Batch Operations to invoke an AWS Lambda function to create new variants of the photos with the required dimensions and resolution
- B. Create a dynamic CloudFront origin that automatically maps the request of each device to the corresponding photo variant.
- C. Use S3 Batch Operations to invoke an AWS Lambda function to create new variants of the photos with the required dimensions and resolution
- D. Create a Lambda@Edge function to route requests to the corresponding photo variant by using request headers.
- E. Create a Lambda@Edge function that optimizes the photos upon request and returns the photos as a response
- F. Change the CloudFront TTL cache policy to the maximum value possible.
- G. Create a Lambda@Edge function that optimizes the photos upon request and returns the photos as a response
- H. In the same function store a copy of the processed photos on Amazon S3 for subsequent requests.

Answer: D

Explanation:

This solution meets the requirements most cost-effectively because it optimizes the photos on demand and caches them for future requests. Lambda@Edge allows the developer to run Lambda functions at AWS locations closer to viewers, which can reduce latency and improve photo quality. The developer can create a Lambda@Edge function that uses the GET parameters from each request to optimize the photos with the required dimensions and resolutions and returns them as a response. The function can also store a copy of the processed photos on Amazon S3 for subsequent requests, which can reduce processing time and costs. Using S3 Batch Operations to create new variants of the photos will incur additional storage costs and may not cover all possible dimensions and resolutions. Creating a dynamic CloudFront origin or a Lambda@Edge function to route requests to corresponding photo variants will require maintaining a mapping of device types and photo variants, which can be complex and error-prone.

Reference: [Lambda@Edge Overview], [Resizing Images with Amazon CloudFront & Lambda@Edge]

NEW QUESTION 58

A company is developing an ecommerce application that uses Amazon API Gateway APIs. The application uses AWS Lambda as a backend. The company needs to test the code in a dedicated, monitored test environment before the company releases the code to the production environment.

When solution will meet these requirements?

- A. Use a single stage in API Gateway
- B. Create a Lambda function for each environment
- C. Configure API clients to send a query parameter that indicates the environment and the specific lambda function.
- D. Use multiple stages in API Gateway
- E. Create a single Lambda function for all environments
- F. Add different code blocks for different environments in the Lambda function based on Lambda environment variables.
- G. Use multiple stages in API Gateway
- H. Create a Lambda function for each environment
- I. Configure API Gateway stage variables to route traffic to the Lambda function in different environments.
- J. Use a single stage in API Gateway
- K. Configure a API client to send a query parameter that indicated the environment
- L. Add different code blocks for different environments in the Lambda function to match the value of the query parameter.

Answer: C

Explanation:

The solution that will meet the requirements is to use multiple stages in API Gateway. Create a Lambda function for each environment. Configure API Gateway stage variables to route traffic to the Lambda function in different environments. This way, the company can test the code in a dedicated, monitored test

environment before releasing it to the production environment. The company can also use stage variables to specify the Lambda function version or alias for each stage, and avoid hard-coding the Lambda function name in the API Gateway integration. The other options either involve using a single stage in API Gateway, which does not allow testing in different environments, or adding different code blocks for different environments in the Lambda function, which increases complexity and maintenance.

Reference: Set up stage variables for a REST API in API Gateway

NEW QUESTION 61

A developer is building a web application that uses Amazon API Gateway to expose an AWS Lambda function to process requests from clients. During testing, the developer notices that the API Gateway times out even though the Lambda function finishes under the set time limit.

Which of the following API Gateway metrics in Amazon CloudWatch can help the developer troubleshoot the issue? (Choose two.)

- A. CacheHitCount
- B. IntegrationLatency
- C. CacheMissCount
- D. Latency
- E. Count

Answer: BD

Explanation:

Amazon API Gateway is a service that enables developers to create, publish, maintain, monitor, and secure APIs at any scale. Amazon CloudWatch is a service that monitors AWS resources and applications. API Gateway provides several CloudWatch metrics to help developers troubleshoot issues with their APIs. Two of the metrics that can help the developer troubleshoot the issue of API Gateway timing out are:

? IntegrationLatency: This metric measures the time between when API Gateway relays a request to the backend and when it receives a response from the backend. A high value for this metric indicates that the backend is taking too long to respond and may cause API Gateway to time out.

? Latency: This metric measures the time between when API Gateway receives a request from a client and when it returns a response to the client. A high value for this metric indicates that either the integration latency is high or API Gateway is taking too long to process the request or response.

References:

? [What Is Amazon API Gateway? - Amazon API Gateway]

? [Amazon API Gateway Metrics and Dimensions - Amazon CloudWatch]

? [Troubleshooting API Errors - Amazon API Gateway]

NEW QUESTION 62

A company developed an API application on AWS by using Amazon CloudFront, Amazon API Gateway, and AWS Lambda. The API has a minimum of four requests every second. A developer notices that many API users run the same query by using the POST method. The developer wants to cache the POST request to optimize the API resources. Which solution will meet these requirements?

A.

Configure the CloudFront cach

- B. Update the application to return cached content based upon the default request headers.
- C. Override the cache method in the selected stage of API Gatewa
- D. Select the POST method.
- E. Save the latest request response in Lambda /tmp director
- F. Update the Lambda function to check the /tmp directory.
- G. Save the latest request in AWS Systems Manager Parameter Stor
- H. Modify the Lambda function to take the latest request response from Parameter Store.

Answer: B

Explanation:

Amazon API Gateway provides tools for creating and documenting web APIs that route HTTP requests to Lambda functions². You can secure access to your API with authentication and authorization controls. Your APIs can serve traffic over the internet or can be accessible only within your VPC². You can override the cache method in the selected stage of API Gateway². Therefore, option B is correct.

NEW QUESTION 65

A company is planning to use AWS CodeDeploy to deploy an application to Amazon Elastic Container Service (Amazon ECS) During the deployment of a new version of the application, the company initially must expose only 10% of live traffic to the new version of the deployed application. Then, after 15 minutes elapse, the company must route all the remaining live traffic to the new version of the deployed application.

Which CodeDeploy predefined configuration will meet these requirements?

- A. CodeDeployDefault ECSCanary10Percent15Minutes
- B. CodeDeployDefault LambdaCanary10Percent5Minutes
- C. CodeDeployDefault LambdaCanary10Percent15Minutes
- D. CodeDeployDefault ECSLinear10PercentEvery1 Minutes

Answer: A

Explanation:

The predefined configuration "CodeDeployDefault.ECSCanary10Percent15Minutes" is designed for Amazon Elastic Container Service (Amazon ECS) deployments and meets the specified requirements. It will perform a canary deployment, which means it will initially route 10% of live traffic to the new version of the application, and then after 15 minutes elapse, it will automatically route all the remaining live traffic to the new version. This gradual deployment approach allows

the company to verify the health and performance of the new version with a small portion of traffic before fully deploying it to all users.

NEW QUESTION 69

A developer wants to store information about movies. Each movie has a title, release year, and genre. The movie information also can include additional properties about the cast and production crew. This additional information is inconsistent across movies. For example, one movie might have an assistant director, and another movie might have an animal trainer.

The developer needs to implement a solution to support the following use cases:

For a given title and release year, get all details about the movie that has that title and release year.

For a given title, get all details about all movies that have that title. For a given genre, get all details about all movies in that genre. Which data store configuration will meet these requirements?

- A. Create an Amazon DynamoDB tabl
- B. Configure the table with a primary key that consists of the title as the partition key and the release year as the sort ke
- C. Create a global secondary index that uses the genre as the partition key and the title as the sort key.
- D. Create an Amazon DynamoDB tabl
- E. Configure the table with a primary key that consists of the genre as the partition key and the release year as the sort ke

- F. Create a global secondary index that uses the title as the partition key.
- G. On an Amazon RDS DB instance, create a table that contains columns for title, release year, and genre.
- H. Configure the title as the primary key.
- I. On an Amazon RDS DB instance, create a table where the primary key is the title and all other data is encoded into JSON format as one additional column.

Answer: A

Explanation:

Amazon DynamoDB is a fully managed NoSQL database service that provides fast and consistent performance with seamless scalability. The developer can create a DynamoDB table and configure the table with a primary key that consists of the title as the partition key and the release year as the sort key. This will enable querying for a given title and release year efficiently. The developer can also create a global secondary index that uses the genre as the partition key and the title as the sort key. This will enable querying for a given genre efficiently. The developer can store additional properties about the cast and production crew as attributes in the DynamoDB table. These attributes can have different data types and structures, and they do not need to be consistent across items.

References:

? [Amazon DynamoDB]

? [Working with Queries - Amazon DynamoDB]

? [Working with Global Secondary Indexes - Amazon DynamoDB]

NEW QUESTION 72

A developer is building a microservices-based application by using Python on AWS and several AWS services. The developer must use AWS X-Ray. The developer views the service map by using the console to view the service dependencies. During testing, the developer notices that some services are missing from the service map.

What can the developer do to ensure that all services appear in the X-Ray service map?

- A. Modify the X-Ray Python agent configuration in each service to increase the sampling rate.
- B. Instrument the application by using the X-Ray SDK for Python.
- C. Install the X-Ray SDK for all the services that the application uses.
- D. Enable X-Ray data aggregation in Amazon CloudWatch Logs for all the services that the application uses.
- E. Increase the X-Ray service map timeout value in the X-Ray console.

Answer: B

Explanation:

The X-Ray SDK for Python provides libraries and tools for instrumenting Python applications that use AWS services and other AWS X-Ray integrations. By installing the X-Ray SDK for all the services that the application uses, the developer can ensure that all the service dependencies are captured and displayed in the X-Ray service map. The other options are not relevant or effective for this scenario. References:

? AWS X-Ray SDK for Python

? Instrumenting a Python Application

NEW QUESTION 75

A company is preparing to migrate an application to the company's first AWS environment. Before this migration, a developer is creating a proof-of-concept application to validate a model for building and deploying container-based applications on AWS.

Which combination of steps should the developer take to deploy the containerized proof-of-concept application with the LEAST operational effort? (Select TWO.)

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

To deploy a containerized application on AWS with the least operational effort, the developer should package the application into a container image by using the Docker CLI and upload the image to Amazon ECR, which is a fully managed container registry service. Then, the developer should deploy the application to Amazon ECS on AWS Fargate, which is a serverless compute engine for containers that eliminates the need to provision and manage servers or clusters. Amazon ECS will automatically scale, load balance, and monitor the application. References:

? How to Deploy Docker Containers | AWS

? Deploy a Web App Using AWS App Runner
? How to Deploy Containerized Apps on AWS Using ECR and Docker

NEW QUESTION 76

A developer wants to insert a record into an Amazon DynamoDB table as soon as a new file is added to an Amazon S3 bucket. Which set of steps would be necessary to achieve this?

- A. Create an event with Amazon EventBridge that will monitor the S3 bucket and then insert the records into DynamoDB.
- B. Configure an S3 event to invoke an AWS Lambda function that inserts records into DynamoDB.
- C. Create an AWS Lambda function that will poll the S3 bucket and then insert the records into DynamoDB.
- D. Create a cron job that will run at a scheduled time and insert the records into DynamoDB.

Answer: B

Explanation:

Amazon S3 is a service that provides highly scalable, durable, and secure object storage. Amazon DynamoDB is a fully managed NoSQL database service that

provides fast and consistent performance with seamless scalability. AWS Lambda is a service that lets developers run code without provisioning or managing servers. The developer can configure an S3 event to invoke a Lambda function that inserts records into DynamoDB whenever a new file is added to the S3 bucket. This solution will meet the requirement of inserting a record into DynamoDB as soon as a new file is added to S3. References:

? [Amazon Simple Storage Service (S3)]

? [Amazon DynamoDB]

? [What Is AWS Lambda? - AWS Lambda]

? [Using AWS Lambda with Amazon S3 - AWS Lambda]

NEW QUESTION 77

A developer is modifying an existing AWS Lambda function. While checking the code, the developer notices hardcoded parameter values for an Amazon RDS for SQL Server user name, password, database host, and port. There are also hardcoded parameter values for an Amazon DynamoDB table, an Amazon S3 bucket, and an Amazon Simple Notification Service (Amazon SNS) topic.

The developer wants to securely store the parameter values outside the code in an encrypted format and wants to turn on rotation for the credentials. The developer also wants to be able to reuse the parameter values from other applications and to update the parameter values without modifying code.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create an RDS database secret in AWS Secrets Manager

- B. Set the user name password, database, host and port
- C. Turn on secret rotation
- D. Create encrypted Lambda environment variables for the DynamoDB table, S3 bucket and SNS topic.
- E. Create an RDS database secret in AWS Secrets Manager
- F. Set the user name password, database, host and port
- G. Turn on secret rotation
- H. Create Secure String parameters in AWS Systems Manager Parameter Store for the DynamoDB table, S3 bucket and SNS topic.
- I. Create RDS database parameters in AWS Systems Manager Parameter Store
- J. Store for the user name password, database, host and port
- K. Create encrypted Lambda environment variables for the DynamoDB table, S3 bucket, and SNS topic
- L. Create a Lambda function and set the logic for the credentials rotation task. Schedule the credentials rotation task in Amazon EventBridge.
- M. Create RDS database parameters in AWS Systems Manager Parameter Store
- N. Store for the user name password database, host, and port
- O. Store the DynamoDB table
- P. S3 bucket, and SNS topic in Amazon S3. Create a Lambda function and set the logic for the credentials rotation. Invoke the Lambda function on a schedule.

Answer: B

Explanation:

This solution will meet the requirements by using AWS Secrets Manager and AWS Systems Manager Parameter Store to securely store the parameter values outside the code in an encrypted format. AWS Secrets Manager is a service that helps protect secrets such as database credentials by encrypting them with AWS Key Management Service (AWS KMS) and enabling automatic rotation of secrets. The developer can create an RDS database secret in AWS Secrets Manager and set the user name, password, database, host, and port for accessing the RDS database. The developer can also turn on secret rotation, which will change the database credentials periodically according to a specified schedule or event. AWS Systems Manager Parameter Store is a service that provides secure and scalable storage for configuration data and secrets. The developer can create Secure String parameters in AWS Systems Manager Parameter Store for the DynamoDB table, S3 bucket, and SNS topic, which will encrypt them with AWS KMS. The developer can also reuse the parameter values from other applications and update them without modifying code. Option A is not optimal because it will create encrypted Lambda

environment variables for the DynamoDB table, S3 bucket, and SNS topic, which may not be reusable or updatable without modifying code. Option C is not optimal because it will create RDS database parameters in AWS Systems Manager Parameter Store, which does not support automatic rotation of secrets. Option D is not optimal because it will store the DynamoDB table, S3 bucket, and SNS topic in Amazon S3, which may introduce additional costs and complexity for accessing configuration data. References: AWS Secrets Manager, [AWS Systems Manager Parameter Store]

NEW QUESTION 80

A developer is designing an AWS Lambda function that creates temporary files that are less than 10 MB during invocation. The temporary files will be accessed and modified multiple times during invocation. The developer has no need to save or retrieve these files in the future. Where should the temporary files be stored?

- A. the /tmp directory
- B. Amazon Elastic File System (Amazon EFS)
- C. Amazon Elastic Block Store (Amazon EBS)
- D. Amazon S3

Answer: A

Explanation:

AWS Lambda is a service that lets developers run code without provisioning or managing servers. Lambda provides a local file system that can be used to store temporary files during invocation. The local file system is mounted under the /tmp directory and has a limit of 512 MB. The temporary files are accessible only by the Lambda function that created them and are deleted after the function execution ends. The developer can store temporary files that are less than 10 MB in the /tmp directory and access and modify them multiple times during invocation.

References:

? [What Is AWS Lambda? - AWS Lambda]

? [AWS Lambda Execution Environment - AWS Lambda]

NEW QUESTION 83

A company wants to automate part of its deployment process. A developer needs to automate the process of checking for and deleting unused resources that supported previously deployed stacks but that are no longer used.

The company has a central application that uses the AWS Cloud Development Kit (AWS CDK) to manage all deployment stacks. The stacks are spread out across

multiple accounts. The developer's solution must integrate as seamlessly as possible within the current deployment process. Which solution will meet these requirements with the LEAST amount of configuration?

- A. In the central AWS CDK application, write a handler function in the code that uses AWS SDK calls to check for and delete unused resource
- B. Create an AWS CloudFormation template from a JSON file
- C. Use the template to attach the function code to an AWS Lambda function and to invoke the Lambda function when the deployment stack runs.
- D. In the central AWS CDK application, write a handler function in the code that uses AWS SDK calls to check for and delete unused resource
- E. Create an AWS CDK custom resource Use the custom resource to attach the function code to an AWS Lambda function and to invoke the Lambda function when the deployment stack runs.
- G. In the central AWS CDK, write a handler function in the code that uses AWS SDK calls to check for and delete unused resource
- H. Create an API in AWS Amplify Use the API to attach the function code to an AWS Lambda function and to invoke the Lambda function when the deployment stack runs.
- I. In the AWS Lambda console write a handler function in the code that uses AWS SDK calls to check for and delete unused resource
- J. Create an AWS CDK custom resource
- K. Use the custom resource to import the Lambda function into the stack and to invoke the Lambda function when the deployment stack runs.

Answer: B

Explanation:

This solution meets the requirements with the least amount of configuration because it uses a feature of AWS CDK that allows custom logic to be executed during stack deployment or deletion. The AWS Cloud Development Kit (AWS CDK) is a software development framework that allows you to define cloud infrastructure as code and provision it through CloudFormation. An AWS CDK custom resource is a construct that enables you to create resources that are not natively supported by CloudFormation or perform tasks that are not supported by CloudFormation during stack deployment or deletion. The developer can write a handler function in the code that uses AWS SDK calls to check for and delete unused resources, and create an AWS CDK custom resource that attaches the function code to a Lambda function and invokes it when the deployment stack runs. This way, the developer can automate the cleanup process without requiring additional configuration or integration. Creating a CloudFormation template from a JSON file will require additional configuration and integration with the central AWS CDK application. Creating an API in AWS Amplify will require additional configuration and integration with the central AWS CDK application and may not provide optimal performance or availability. Writing a handler function in the AWS Lambda console will require additional configuration and integration with the central AWS CDK application.

Reference: [AWS Cloud Development Kit (CDK)], [Custom Resources]

NEW QUESTION 88

A developer at a company needs to create a small application that makes the same API call once each day at a designated time. The company does not have infrastructure in the AWS Cloud yet, but the company wants to implement this functionality on AWS. Which solution meets these requirements in the MOST operationally efficient manner?

- A. Use a Kubernetes cron job that runs on Amazon Elastic Kubernetes Service (Amazon EKS)
- B. Use an Amazon Linux crontab scheduled job that runs on Amazon EC2
- C. Use an AWS Lambda function that is invoked by an Amazon EventBridge scheduled event.
- D. Use an AWS Batch job that is submitted to an AWS Batch job queue.

Answer: C

Explanation:

This solution meets the requirements in the most operationally efficient manner because it does not require any infrastructure provisioning or management. The developer can create a Lambda function that makes the API call and configure an EventBridge rule that triggers the function once a day at a designated time. This is a serverless solution that scales automatically and only charges for the execution time of the function.

Reference: [Using AWS Lambda with Amazon EventBridge], [Schedule Expressions for Rules]

NEW QUESTION 93

An application runs on multiple EC2 instances behind an ELB.

Where is the session data best written so that it can be served reliably across multiple requests?

- A. Write data to Amazon ElastiCache
- B. Write data to Amazon Elastic Block Store
- C. Write data to Amazon EC2 instance Store
- D. Write data to the root filesystem

Answer: A

Explanation:

The solution that will meet the requirements is to write data to Amazon ElastiCache. This way, the application can write session data to a fast, scalable, and reliable in-memory data store that can be served reliably across multiple requests. The other options either involve writing data to persistent storage, which is slower and more expensive than in-memory storage, or writing data to the root filesystem, which is not shared among multiple EC2 instances.

Reference: Using ElastiCache for session management

NEW QUESTION 94

A developer is building a serverless application by using the AWS Serverless Application Model (AWS SAM). The developer is currently testing the application in a development environment. When the application is nearly finished, the developer will need to set up additional testing and staging environments for a quality assurance team.

The developer wants to use a feature of the AWS SAM to set up deployments to multiple environments.

Which solution will meet these requirements with the LEAST development effort?

- A. Add a configuration file in TOML format to group configuration entries to every environment
- B. Add a table for each testing and staging environment

- C. Deploy updates to the environments by using the sam deploy command and the --config-env flag that corresponds to the each environment.
- D. Create additional AWS SAM templates for each testing and staging environmen
- E. Write a custom shell script that uses the sam deploy command and the --template-file flag to deploy updates to the environments.
- F. Create one AWS SAM configuration file that has default parameter
- G. Perform updates to the testing and staging environments by using the —parameter-overrides flag in the AWS SAM CLI and the parameters that the updates will override.
- H. Use the existing AWS SAM templat
- I. Add additional parameters to configure specific attributes for the serverless function and database table resources that are in each environmen
- J. Deploy updates to the testing and staging environments by using the sam deploy command.

Answer: A

Explanation:

The correct answer is A. Add a configuration file in TOML format to group configuration entries to every environment. Add a table for each testing and staging environment. Deploy updates to the environments by using the sam deploy command and the --config-env flag that corresponds to the each environment.

* A. Add a configuration file in TOML format to group configuration entries to every environment. Add a table for each testing and staging environment. Deploy updates to the environments by using the sam deploy command and the --config-env flag that corresponds to the each environment. This is correct. This solution will meet the requirements with the least development effort, because it uses a feature of the AWS SAM CLI that supports a project-level configuration file that can be used to configure AWS SAM CLI command parameter values¹. The configuration file can have multiple environments, each with its own set of parameter values, such as stack name, region, capabilities, and more². The developer can use the --config-env option to specify which environment to use when deploying the application³. This way, the developer can avoid creating multiple templates or scripts, or manually overriding parameters for each environment.

* B. Create additional AWS SAM templates for each testing and staging environment. Write a custom shell script that uses the sam deploy command and the --template-file flag to

deploy updates to the environments. This is incorrect. This solution will not meet the requirements with the least development effort, because it requires creating and maintaining multiple templates and scripts for each environment. This can introduce duplication, inconsistency, and complexity in the deployment process.

* C. Create one AWS SAM configuration file that has default parameters. Perform updates to the testing and staging environments by using the —parameter-overrides flag in the AWS SAM CLI and the parameters that the updates will override. This is incorrect. This solution will not meet the requirements with the least development effort, because it requires manually specifying and overriding parameters for each environment every time the developer deploys the application. This can be error-prone, tedious, and inefficient.

* D. Use the existing AWS SAM template. Add additional parameters to configure specific attributes for the serverless function and database table resources that are in each environment. Deploy updates to the testing and staging environments by using the sam deploy command. This is incorrect. This solution will not meet the requirements with the least development effort, because it requires modifying the existing template and adding complexity to the resource definitions for each environment. This can also make it difficult to manage and track changes across different environments.

References:

? 1: AWS SAM CLI configuration file - AWS Serverless Application Model

? 2: Configuration file basics - AWS Serverless Application Model

? 3: Specify a configuration file - AWS Serverless Application Model

NEW QUESTION 97

A company runs an application on AWS The application stores data in an Amazon DynamoDB table Some queries are taking a long time to run These slow queries involve an attribute that is not the table's partition key or sort key

The amount of data that the application stores in the DynamoDB table is expected to increase significantly. A developer must increase the performance of the queries.

Which solution will meet these requirements'?

- A. Increase the page size for each request by setting the Limit parameter to be higher than the default value Configure the application to retry any request that exceeds the provisioned throughput.
- B. Create a global secondary index (GSI). Set query attribute to be the partition key of the index
- C. Perform a parallel scan operation by issuing individual scan requests in the parameters specify the segment for the scan requests and the total number of segments for the parallel scan.
- D. Turn on read capacity auto scaling for the DynamoDB tabl
- E. Increase the maximum read capacity units (RCUs).

Answer: B

Explanation:

Creating a global secondary index (GSI) is the best solution to improve the performance of the queries that involve an attribute that is not the table's partition key or sort key. A GSI allows you to define an alternate key for your table and query the data using that key. This way, you can avoid scanning the entire table and reduce the latency and cost of your queries. You should also follow the best practices for designing and using GSIs in DynamoDB¹². References

? Working with Global Secondary Indexes - Amazon DynamoDB

? DynamoDB Performance & Latency - Everything You Need To Know

NEW QUESTION 101

A company has installed smart notes in all Its customer locations. The smart meter's measure power usage at 1minute intervals and send the usage readings to a remote endpoint tot collection. The company needs to create an endpoint that will receive the smart meter readings and store the readings in a database. The company wants to store the location ID and timestamp information.

The company wants to give ls customers low-latency access to their current usage and historical usage on demand The company expects demand to increase significantly. The solution must not impact performance or include downtime write seeing.

When solution will meet these requirements MOST cost-effectively?

- A. Store the smart meter readings in an Amazon RDS databas
- B. Create an index on the location ID and timestamp columns Use the columns to filter on the customers 'data.
- C. Store the smart motor readings m an Amazon DynamoDB table Croato a composite Key oy using the location ID and timestamp column
- D. Use the columns to filter on the customers' data.
- E. Store the smart meter readings in Amazon EastCache for Reds Create a Sorted set key y using the location ID and timestamp column
- F. Use the columns to filter on the customers' data.
- G. Store the smart meter readings m Amazon S3 Parton the data by using the location ID and timestamp column
- H. Use Amazon Athena lo tiler on me customers' data.

Answer: B

Explanation:

The solution that will meet the requirements most cost-effectively is to store the smart meter readings in an Amazon DynamoDB table. Create a composite key by using the location ID and timestamp columns. Use the columns to filter on the customers' data. This way, the company can leverage the scalability, performance, and low latency of DynamoDB to store and retrieve the smart meter readings. The company can also use the composite key to query the data by location ID and timestamp efficiently. The other options either involve more expensive or less scalable services, or do not provide low-latency access to the current usage.

Reference: Working with Queries in DynamoDB

NEW QUESTION 102

A developer has code that is stored in an Amazon S3 bucket. The code must be deployed as an AWS Lambda function across multiple accounts in the same AWS Region as the S3 bucket an AWS CloudFormation template that runs for each account will deploy the Lambda function.

What is the MOST secure way to allow CloudFormation to access the Lambda Code in the S3 bucket?

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

This solution allows the CloudFormation service role to access the S3 bucket from any account, as long as it has the S3 GetObject permission. The bucket policy grants access to any principal with the GetObject permission, which is the least privilege needed to deploy the Lambda code. This is more secure than granting ListBucket permission, which is not required for deploying Lambda code, or using a service-based link, which is not supported for Lambda functions.

Reference: AWS CloudFormation Service Role, Using AWS Lambda with Amazon S3

NEW QUESTION 104

A developer is preparing to begin development of a new version of an application. The previous version of the application is deployed in a production environment. The developer needs to deploy fixes and updates to the current version during the development of the new version of the application. The code for the new version of the application is stored in AWS CodeCommit.

Which solution will meet these requirements?

- A. From the main branch, create a feature branch for production bug fixe
- B. Create a second feature branch from the main branch for development of the new version.
- C. Create a Git tag of the code that is currently deployed in productio
- D. Create a Git tag for the development of the new versio
- E. Push the two tags to the CodeCommit repository.
- F. From the main branch, create a branch of the code that is currently deployed in productio
- G. Apply an IAM policy that ensures no other other users can push or merge to the branch.
- H. Create a new CodeCommit repository for development of the new version of the applicatio
- I. Create a Git tag for the development of the new version.

Answer: A

Explanation:

? A feature branch is a branch that is created from the main branch to work on a specific feature or task¹. Feature branches allow developers to isolate their work from the main branch and avoid conflicts with other changes¹. Feature branches can be merged back to the main branch when the feature or task is completed and tested¹.

? In this scenario, the developer needs to maintain two parallel streams of work: one for fixing and updating the current version of the application that is deployed in production, and another for developing the new version of the application. The developer can use feature branches to achieve this goal.

? The developer can create a feature branch from the main branch for production bug fixes. This branch will contain the code that is currently deployed in production, and any fixes or updates that need to be applied to it. The developer can push this branch to the CodeCommit repository and use it to deploy changes to the production environment.

? The developer can also create a second feature branch from the main branch for development of the new version of the application. This branch will contain the code that is under development for the new version, and any changes or enhancements that are part of it. The developer can push this branch to the CodeCommit repository and use it to test and deploy the new version of the application in a separate environment.

? By using feature branches, the developer can keep the main branch stable and clean, and avoid mixing code from different versions of the application. The developer can also easily switch between branches and merge them when needed.

NEW QUESTION 106

A development team maintains a web application by using a single AWS CloudFormation template. The template defines web servers and an Amazon RDS database. The team uses the Cloud Formation template to deploy the Cloud Formation stack to different environments.

During a recent application deployment, a developer caused the primary development database to be dropped and recreated. The result of this incident was a loss of data. The team needs to avoid accidental database deletion in the future.

Which solutions will meet these requirements? (Choose two.)

- A. Add a CloudFormation Deletion Policy attribute with the Retain value to the database resource.
- B. Update the CloudFormation stack policy to prevent updates to the database.
Modify the database to use a Multi-AZ deployment.
- ☒ C. Create a CloudFormation stack set for the web application and database deployments.
- E. Add a Cloud Formation DeletionPolicy attribute with the Retain value to the stack.

Answer: AB

Explanation:

AWS CloudFormation is a service that enables developers to model and provision AWS resources using templates. The developer can add a CloudFormation Deletion Policy attribute with the Retain value to the database resource. This will prevent the database from being deleted when the stack is deleted or updated. The developer can also update the CloudFormation stack policy to prevent updates to the database. This will prevent accidental changes to the database configuration or properties.

References:

? [What Is AWS CloudFormation? - AWS CloudFormation]

? [DeletionPolicy Attribute - AWS CloudFormation]

? [Protecting Resources During Stack Updates - AWS CloudFormation]

NEW QUESTION 110

A developer is creating a service that uses an Amazon S3 bucket for image uploads. The service will use an AWS Lambda function to create a thumbnail of each image. Each time an image is uploaded, the service needs to send an email notification and create the thumbnail. The developer needs to configure the image processing and email notifications setup.

Which solution will meet these requirements?

- A. Create an Amazon Simple Notification Service (Amazon SNS) topic. Configure S3 event notifications with a destination of the SNS topic. Subscribe the Lambda function to the SNS topic. Create an email notification subscription to the SNS topic.
- B. Create an Amazon Simple Notification Service (Amazon SNS) topic.
- C. Configure S3 event notifications with a destination of the SNS topic.
- D. Subscribe the Lambda function to the SNS topic.
- E. Create an Amazon Simple Queue Service (Amazon SQS) queue. Subscribe the SQS queue to the SNS topic. Create an email notification subscription to the SQS queue.
- F. Create an Amazon Simple Queue Service (Amazon SQS) queue. Configure S3 event notifications with a destination of the SQS queue. Subscribe the Lambda function to the SQS queue. Create an email notification subscription to the SQS queue.
- G. Create an Amazon Simple Queue Service (Amazon SQS) queue.
- H. Send S3 event notifications to Amazon EventBridge.
- I. Create an EventBridge rule that runs the Lambda function when images are uploaded to the S3 bucket. Create an EventBridge rule that sends notifications to the SQS queue. Create an email notification subscription to the SQS queue.

Answer: A

Explanation:

This solution will allow the developer to receive notifications for each image uploaded to the S3 bucket, and also create a thumbnail using the Lambda function. The SNS topic will serve as a trigger for both the Lambda function and the email notification subscription. When an image is uploaded, S3 will send a notification to the SNS topic, which will trigger the Lambda function to create the thumbnail and also send an email notification to the specified email address.

NEW QUESTION 114

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual DVA-C02 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the DVA-C02 Product From:

<https://www.2passeasy.com/dumps/DVA-C02/>

Money Back Guarantee

DVA-C02 Practice Exam Features:

- * DVA-C02 Questions and Answers Updated Frequently
- * DVA-C02 Practice Questions Verified by Expert Senior Certified Staff
- * DVA-C02 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * DVA-C02 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year