

1z0-083 Dumps

Oracle Database Administration II

<https://www.certleader.com/1z0-083-dumps.html>



NEW QUESTION 1

A container database (CDB) contains two pluggable databases PDB1 and PDB2.

The LOCAL_UNDO_ENABLED database property is set to FALSE in the CDB. Data file 24 of PDB2 was deleted and you need to restore and recover it.

The only RMAN backup that exists was created with the BACKUP DATABASE command while connected to CDB\$ROOT.

Which three are true? (Choose three.)

- A. Data file 24 can be recovered only while connected to PDB2.
- B. Data file 24 can be restored and recovered while connected to CDB\$ROOT.
- C. Data file 24 can be restored only while connected to CDB\$ROOT.
- D. Data file 24 can be restored only while connected to PDB2.
- E. Data file 24 can be recovered while connected to PDB2.
- F. Data file 24 can be recovered while connected to CDB\$ROOT.

Answer: BCF

NEW QUESTION 2

Which three are true about Database Point-in-Time Recovery? (Choose three.)

- A. The database must have FLASHBACK DATABASE ON to perform Database Point-in-Time Recovery.
- B. The database must be in MOUNT state when performing Database Point-in-Time Recovery.
- C. Database Point-in-Time Recovery is performed by the Managed Recovery Process (MRP)
- D. The Database must be in ARCHIVELOG mode.
- E. The target point for the recovery must be specified as a time or System Change Number (SCN).
- F. The database must be open RESETLOGS after Database Point-in-Time Recovery.

Answer: BDF

Explanation:

[https://docs.oracle.com/cd/B19306_01/backup.102/b14192/flashptr006.htm#:~:text=Database%20point%2Din%](https://docs.oracle.com/cd/B19306_01/backup.102/b14192/flashptr006.htm#:~:text=Database%20point%2Din%20time)

NEW QUESTION 3

Which two are true about RMAN backups when using a media manager to write backups to tape when there are only two tape drives? (Choose two.)

- A. SBT tape compression can be used even if no RMAN compression is configured.
- B. Any backup set written to the SBT device in this configuration can contain a maximum of two backup pieces.
- C. Any backup written to the SBT device in this configuration can contain a maximum of two backup sets.
- D. SBT tape compression and RMAN backup compression should be used in parallel.
- E. The SBT device should be configured to use PARALLELISM 2 to allow both tape drive to be used simultaneously.

Answer: DE

NEW QUESTION 4

Which two are true about data movement between a non-CDB and a PDB using Data Pump? (Choose two.)

- A. Tablespaces are automatically created as needed while importing full exports in either a non-CDB or a PDB.
- B. Oracle attempts to convert conventional database users to local users when moving schemas from a non-CDB to a PDB.
- C. A new PDB is automatically created when importing a non-CDB into a CDB.
- D. Oracle attempts to convert common users to conventional users when moving schemas from a PDB to a non-CDB.
- E. Moving data from a PDB to a non-CDB is only possible by using transportable tablespace export and import.
- F. Moving data from a non-CDB to a PDB is only possible by using conventional export and import.

Answer: DE

NEW QUESTION 5

Which three are true about backup, restore, and recovery operations done without using Recovery Manager (RMAN)? (Choose three.)

- A. Backing up a database in NOARCHIVELOG mode using O/S utilities requires that the database instance be started and the database be in the MOUNT state.
- B. Backing up a database in ARCHIVELOG mode using O/S utilities requires that the database instance be started and the database be in MOUNT state.
- C. An Oracle database can be restored from backup files copied using O/S utilities.
- D. Oracle data file backups, copied using an O/S utility, can be added to the RMAN catalog as IMAGE COPIES.
- E. Backing up a database in NOARCHIVELOG mode using O/S utilities requires that the database instance be shut down.
- F. Oracle archive log backups, copied using an O/S utility, can be added to the RMAN catalog as a backup set.
- G. Backing up a database in ARCHIVELOG mode using O/S utilities requires that the database instance be started and the database be in OPEN state.

Answer: BDE

NEW QUESTION 6

A container database called CDB1 is OMF-enabled.

PDB_FILE_NAME_CONVERT is not configured in CDB1. PDB1 was unplugged from CDB1 earlier in the week. Examine this command, which will be executed in CDB1:

```
CREATE PLUGGABLE DATABASE pdb1
```

```
USING '/u01/app/oracle/oradata/pdb1.xml' SOURCE_FILE_NAME_CONVERT =
```

```
(' /u01/app/oracle/oradata', '/u02/app/oracle/oradata');
```

Which two are true? (Choose two.)

- A. PDB1 data files already exist in the correct location.
- B. DBMS_PDB.CHECK_PLUG_COMPATIBILITY must be run in CDB1 before executing the command.

- C. PDB_FILE_NAME_CONVERT must be set before executing the command.
- D. /u01/app/oracle/oradata/pdb1.xml does not contain the current locations of data files for PDB1.
- E. PDB1 must be dropped from CDB1.

Answer: AE

NEW QUESTION 7

Which three can be done using Oracle Database Configuration Assistant (DBCA) starting from Oracle Database 19c? (Choose three.)

- A. cloning a remote container database in interactive mode
- B. cloning a remote pluggable database in silent mode
- C. relocating a remote pluggable database in interactive mode
- D. relocating a remote container database in silent mode
- E. cloning a remote container database in silent mode
- F. relocating a remote pluggable database in silent mode
- G. relocating a remote container database in interactive mode

Answer: BEF

NEW QUESTION 8

Examine this configuration:

- CDB1 is an Oracle Database 12c Release 2 database containing pluggable databases PDB\$SEED, PDB1, and PDB2.
- PDB\$SEED is open READ ONLY
- PDB1 is open READ WRITE
- PDB2 is MOUNTED.
- ORACLE_HOME is /u01/app/oracle/product/18.1.0/dbhome_1.

You execute these commands before upgrading the database to the current release:

```
$ . oraenv
ORACLE_SID = [cdb1] ? cdb1
The Oracle base remains unchanged with value /u01/app/oracle

$ $ORACLE_HOME/jdk/bin/java -jar preupgrade.jar TERMINAL TEXT
```

For which databases will fixup scripts be created?

- A. CDB1, PDB\$SEED, PDB1, and PDB2
- B. PDB\$SEED, PDB1, and PDB2 only
- C. CDB1 and PDB\$SEED only
- D. CDB1, PDB1, and PDB2 only
- E. CDB1, PDB\$SEED, and PDB1 only

Answer: E

NEW QUESTION 9

A user complains about poor database performance.

You want to verify if the user's session has waited for certain types of I/O activity. Which view displays all waits waited on by a session at least once?

- A. V\$SESSION_EVENT
- B. V\$SESSTAT
- C. V\$SESSION_WAIT
- D. V\$SESSION_WAIT_CLASS
- E. V\$SESSION

Answer: A

NEW QUESTION 10

Which three are true about managing memory components in an Oracle database instance? (Choose three.)

- A. With Automatic Shared Memory Management, the database instance can increase the Large Pool size by reducing the Shared Pool size.
- B. With Automatic Memory Management, the database instance can increase the System Global Area size by reducing the Program Global Area size.
- C. Automatically tuned and resized System Global Area components will always revert to their initial sizes after an instance restart.
- D. Automatic Memory Management must be used together with locking the System Global Area into physical memory.
- E. With Automatic Shared Memory Management, the database instance can increase the Program Global Area size by reducing the System Global Area size.
- F. On-Line Transaction Processing systems often use less Program Global Area than Decision Support Systems.

Answer: AEF

NEW QUESTION 10

Which three are true about an application container?

- A. It must have an application root PDB.
- B. It can contain multiple applications.
- C. An application PDB can belong to multiple application containers.
- D. Two application containers can share an application seed PDB.
- E. It can contain a single application.

F. It must have an application seed PDB.

Answer: BDE

NEW QUESTION 12

Which three are true about opatchauto? (Choose three.)

- A. It performs a shutdown and then a restart of all processes in both Oracle Grid Infrastructure and Oracle Database home during the patching process.
- B. It must be invoked by a user with root user privileges.
- C. Patches are applied via opatchauto.
- D. Users must always input patch plans to opatchauto.
- E. It requires the Oracle Grid Infrastructure and Oracle Database instances to be shut down before being invoked.
- F. It applies patches in nonrolling mode by default.
- G. It is used to apply interim patches to Oracle Grid Infrastructure and Oracle Database home combinations.

Answer: ABC

NEW QUESTION 15

Which two are true about duplicating pluggable databases (PDBs) with RMAN? (Choose two.)

- A. Two or more PDBs can be duplicated with the same RMAN DUPLICATE command.
- B. All tablespaces belonging to a PDB must be duplicated when duplicating the PDB.
- C. The auxiliary instance is automatically created with ENABLE_PLUGGABLE_DATABASE = TRUE.
- D. A user with SYSDBA or SYSBACKUP must be logged in with RMAN to the PDB to duplicate it.
- E. CDB\$ROOT and PDB\$SEED are automatically duplicated.

Answer: CD

NEW QUESTION 20

Examine this configuration:

- CDB1 is a container database.
- COMMON_USER_PREFIX is C##.
- PDB1 is a pluggable database contained in CDB1.
- APP1_ROOT is an application container contained in CDB1.
- APP1_PDB1 is an application PDB contained in APP1_ROOT.

You execute these commands successfully:

```
$ sqlplus sys/oracle_4U@localhost:1521/cdb1 as sysdba
```

```
SQL> CREATE USER c##user1 identified by oracle_4U container=all;
User created.
```

```
SQL> ALTER SESSION SET CONTAINER=pdb1;
Session altered.
```

```
SQL> CREATE USER p1_user1 identified by oracle_4U;
User Created.
```

```
SQL> ALTER SESSION SET CONTAINER=app1_root;
Session altered.
```

```
SQL> ALTER PLUGGABLE DATABASE APPLICATION app1_cdb1_app BEGIN INSTALL '1.0';
Session altered.
```

```
SQL> CREATE USER app1_user1 IDENTIFIED BY oracle_4U;
User Created.
```

```
SQL> ALTER PLUGGABLE DATABASE APPLICATION app1_cdb1_app END INSTALL '1.0';
Pluggable database altered.
```

Which two are true? (Choose two.)

- A. APP1_USER1 can be created in PDB1.
- B. APP1_USER1 can be created in CDB1.
- C. APP1_USER1 can have different privileges in each Application PDB contained in APP1_ROOT.
- D. C##_APP_USER1 can be created in CDB1.
- E. P1_USER1 can be created in CDB1.
- F. C##_USER1 will have the same privileges and roles granted in all PDBs in CDB1.

Answer: CF

NEW QUESTION 24

Which two are true about common objects? (Choose two.)

- A. They can be created only in CDB\$ROOT.
- B. They can be only metadata-linked in an application container.
- C. They can exist in user-defined schemas only in application containers.
- D. They can exist in CDB\$ROOT and an application root.
- E. They can be extended data-linked in CDB\$ROOT.
- F. They can be created only in an application root.

Answer: CF

NEW QUESTION 29

Which two are true about server-generated alerts? (Choose two.)

- A. Stateful alerts must be created by a DBA after resolving the problem.
- B. Stateless alerts can be purged manually from the alert history.
- C. Stateless alerts can be cleared manually.
- D. Stateless alerts are automatically cleared.
- E. Stateful alerts are purged automatically from the alert history.

Answer: BC

Explanation:

Except for the tablespace space usage metric, which is database related, the other metrics are instance related. Threshold alerts are also referred to as stateful alerts which are automatically cleared when an alert condition clears. Stateful alert appears in DBA_OUTSTANDING_ALERTS and when cleared go to DBA_ALERT_HISTORY. Other server-generated alerts correspond to specific database events such as ORA-* errors, "Snapshot too old" errors, Recovery Area Low on Free Space, Resumable Session Suspended. These are non threshold based alerts, also referred to as stateless alerts. Stateless alerts go directly to the History table. +++ Most alerts (such as "Out of Space") are cleared automatically when the cause of the problem disappears. However, other alerts (such as generic alert log errors) are sent to you for notification and must be acknowledged by you. After taking the corrective measures, you acknowledge an alert by clearing or purging it. Clearing an alert sends the alert to the Alert History which is accessible from Monitoring sub menu. Purging an alert removes it from the Alert History.

NEW QUESTION 31

Examine the command for creating pluggable database PDB2 in container database CDB2.

```
CREATE PLUGGABLE DATABASE pdb2
  ADMIN USER pdb2_adm
  IDENTIFIED BY 123pdb
  ROLES=(CONNECT) ;
```

Select three options, any one of which is required for it to execute successfully. (Choose three.)

- A. Add the FILE_NAME_CONVERT clause to the statement and set the PDB_FILE_NAME_CONVERT parameter.
- B. Add only the CREATE_FILE_DEST clause to the statement.
- C. Set only the PDB_FILE_NAME_CONVERT parameter.
- D. Set the PDB_FILE_NAME_CONVERT parameter and enable OMF.
- E. Enable only OMF.
- F. Add the FILE_NAME_CONVERT clause to the statement and enable OracleManaged Files (OMF)

Answer: BDE

NEW QUESTION 33

A database is configured in ARCHIVELOG mode.

A full RMAN backup exists but no control file backup to trace has been taken. A media failure has occurred. In which two scenarios is incomplete recovery required? (Choose two.)

- A. after losing a SYSAUX tablespace data file
- B. after losing all members of an INACTIVE online redo log group
- C. after losing all members of the CURRENT onlineredo log group
- D. after losing all copies of the control file
- E. after losing an UNDO tablespace that is in use

Answer: BD

NEW QUESTION 37

Which two are true about automatic block repair? (Choose two.)

- A. Automatic block repair can repair blocks with no standby database if DB_BLOCK_CHECKING = TRUE.
- B. Real-Time Query must be enabled on a physical standby database for automatic block repair to be done on that physical standby database.
- C. Real-Time Query must be enabled on a primary database for automatic block repair to be done on any of its physical standby databases.
- D. It is not possible for media corrupt blocks.
- E. Real-Time Query must be enabled on a physical standby database for automatic block repair to be done on its primary database.

Answer: BC

NEW QUESTION 42

While backing up to an SBT channel, you determine that the read phase of your compressed Recovery Manager (RMAN) incremental level 0 backup is a bottleneck.

FORCE LOGGING is enabled for the database.

Which two could improve read performance? (Choose two.)

- A. Increase the size of tape I/O buffers.
- B. Disable FORCE LOGGING for the database.
- C. Increase the size of the database buffer cache.
- D. Enable asynchronous disk I/O.
- E. Increase the level of RMAN multiplexing.

Answer: DE

NEW QUESTION 46

Which two are true about Oracle Optimizer Statistics, their use, and their collection? (Choose two.)

- A. The number of table rows is considered when evaluating the cost of accessing a table using an index.
- B. Index balanced B*Tree height is considered when evaluating the cost of using an index.
- C. The Statistics Advisor can help recommend the best way to gather statistics.
- D. Statistics collected using DBMS_STATS always yield the best optimizer result.
- E. The Statistics Advisor generates actions for all recommendations.

Answer: CD

NEW QUESTION 50

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your 1z0-083 Exam with Our Prep Materials Via below:

<https://www.certleader.com/1z0-083-dumps.html>