



Oracle

Exam Questions 1z0-082

Oracle Database Administration I

NEW QUESTION 1

Table EMPLOYEES contains columns including EMPLOYEE_ID, JOB_ID and SALARY. Only the EMPLOYEE_ID column is indexed. Rows exist for employees 100 and 200. Examine this statement:

```
UPDATE employees
   SET (job_id, salary) =
      (SELECT job_id, salary
       FROM employees
       WHERE employee_id = 200)
 WHERE employee_id = 100;
```

Which two statements are true? (Choose two.)

- A. Employee 100 will have SALARY set to the same value as the SALARY of employee 200
- B. Employee 200 will have JOB_ID set to the same value as the JOB_ID of employee 100
- C. Employee 200 will have SALARY set to the same value as the SALARY of employee 100
- D. Employee 100 will have JOB_ID set to the same value as the JOB_ID of employee 200
- E. Employees 100 and 200 will have the same JOB_ID as before the update command
- F. Employees 100 and 200 will have the same SALARY as before the update command

Answer: AB

NEW QUESTION 2

Examine this command:

```
ALTER DATABASE
   MOVE DATAFILE '/u01/sales1.dbf'
   TO '/u01/sales01.dbf'
 REUSE;
```

Which two statements are true? (Choose two.)

- A. DML may be performed on tables with one or more extents in this data file during the execution of this command.
- B. The tablespace containing SALES1.DBF must be altered READ ONLY before executing the command.
- C. The tablespace containing SALES1.DBF must be altered OFFLINE before executing the command.
- D. If Oracle Managed Files (OMF) is used, then the file is renamed but moved to DB_CREATE_FILE_DEST.
- E. The file is renamed and stored in the same location

Answer: AB

NEW QUESTION 3

Which three statements are true about views in an Oracle database? (Choose three.)

- A. Views can be updated without the need to re-grant privileges on the view
- B. Tables in the defining query of a view must always exist in order to create the view
- C. The WITH CHECK clause prevents certain rows from being displayed when querying the view
- D. Data Manipulation Language (DML) can always be used on views
- E. Inserting one or more rows using a view whose defining query contains a GROUP BY clause will cause an error
- F. Deleting one or more rows using a view whose defining query contains a GROUP BY clause will cause an error
- G. The WITH CHECK clause prevents certain rows from being updated or inserted

Answer: BDE

NEW QUESTION 4

Which three statements are true about the tools used to configure Oracle Net Services? (Choose three.)

- A. The Oracle Net Configuration Assistant is only used when running the Oracle installer
- B. Oracle Net Manager can be used to centrally configure listeners on any database server target
- C. The lsnrctl utility requires a listener.ora file to exist before it is started
- D. Oracle Net Manager can be used to locally configure naming methods on a database server
- E. Enterprise Manager Cloud Control can be used to centrally configure listeners on any managed database server
- F. Enterprise Manager Cloud Control can be used to centrally configure net service names for any databaseserver target

Answer: BDE

NEW QUESTION 5

You execute this query:

```
SELECT TO_CHAR(NEXT_DAY(LAST_DAY(SYSDATE), 'MON'), 'dd "Monday for" fmMonth rrrr') What is the result?
```

- A. It executes successfully but does not return any result
- B. It returns the date for the first Monday of the next month
- C. It generates an error
- D. It returns the date for the last Monday of the current month

Answer: B

NEW QUESTION 6

You have been tasked to create a table for a banking application. One of the columns must meet three requirements:

- Be stored in a format supporting date arithmetic without using conversion functions
- Store a loan period of up to 10 years
- Be used for calculating interest for the number of days the loan remains unpaid Which data type should you use?

- A. INTERVAL YEAR TO MONTH
- B. INTERVAL DAY TO SECOND
- C. TIMESTAMP WITH LOCAL TIMEZONE
- D. TIMESTAMP
- E. TIMESTAMP WITH TIMEZONE

Answer: B

NEW QUESTION 7

Which two statements are true about space-saving features in an Oracle Database? (Choose two.)

- A. Private Temporary Tables (PTTs) store metadata in memory only
- B. An index created with the UNUSABLE attribute has no segment
- C. If they exist for a session, Private Temporary Tables (PTTs) are always dropped at the next COMMIT OR ROLLBACK statement
- D. An index that is altered to be UNUSABLE will retain its segment
- E. A table that is truncated will always have its segment removed

Answer: BC

NEW QUESTION 8

You execute this command:

```
CREATE BIGFILE TABLESPACE big_tbs
    DATAFILE '/u01/oracle/data/big_f1.dbf'
    SIZE 20G;
```

Sufficient storage is available in filesystem /u01.

Which two statements are true about the BIG_TBS tablespace? (Choose two.)

- A. AUTOEXTEND is possible for the datafile
- B. It must be bigger than the largest SMALLFILE tablespace
- C. Additional data files may not be added
- D. It will be a dictionary-managed tablespace by default
- E. It will always have a 32K blocksize

Answer: AB

NEW QUESTION 9

In your data center, Oracle Managed Files (OMF) is used for all databases. All tablespaces are smallfile tablespaces.

SALES_Q1 is a permanent user-defined tablespace in the SALES database.

Examine this command which is about to be issued by a DBA logged in to the SALES database: ALTER TABLESPACE sales_q1 ADD DATAFILE;

Which are two actions, either one of which you could take to ensure that the command executes successfully? (Choose two.)

- A. Ensure that DB_RECOVERY_FILE_DEST and DB_CREATE_FILE_DEST each specify with at least 50 Mb of available space.
- B. Specify a path in the DATAFILE clause of the command specifying a location with at least 100M of available space.
- C. Ensure that DB_CREATE_FILE_DEST specifies a location with at least 100 Mb of available space.
- D. Add the AUTOEXTEND ON clause with NEXT set to 100M.
- E. Ensure that DB_RECOVERY_FILE_DEST and DB_CREATE_FILE_DEST each specify locations with at least 50 Mb of available space.

Answer: BD

NEW QUESTION 10

Which three statements are true about GLOBAL TEMPORARY TABLES? (Choose three.)

- A. A TRUNCATE command issued in a session causes all rows in a GLOBAL TEMPORARY TABLE for the issuing session to be deleted.
- B. GLOBAL TEMPORARY TABLE rows inserted by a session are available to any other session whose user has been granted select on the table.
- C. GLOBAL TEMPORARY TABLE space allocation occurs at session start.
- D. Any GLOBAL TEMPORARY TABLE rows existing at session termination will be deleted.
- E. A GLOBAL TEMPORARY TABLE'S definition is available to multiple sessions.
- F. A DELETE command on a GLOBAL TEMPORARY TABLE cannot be rolled back.

Answer: BCF

NEW QUESTION 10

Examine the description of the BOOKS table:

Name	Null?	Type
-----	-----	-----
TRANSACTION_ID	NOT NULL	VARCHAR2 (6)
TRANSACTION_DATE		DATE
AMOUNT		NUMBER (10, 2)
CUSTOMER_ID		VARCHAR2 (6)

The table has 100 rows.

Examine this sequence of statements issued in a new session:

INSERT INTO books VALUES ('ADV112', 'Adventures of Tom Sawyer', NULL, NULL); SAVEPOINT a;

DELETE FROM books; ROLLBACK TO SAVEPOINT a; ROLLBACK;

Which two statements are true? (Choose two.)

- A. The second ROLLBACK command does nothing
- B. The second ROLLBACK command replays the delete
- C. The first ROLLBACK command restores the 101 rows that were deleted, leaving the inserted row still to be committed
- D. The second ROLLBACK command undoes the insert
- E. The first ROLLBACK command restores the 101 rows that were deleted and commits the inserted row

Answer: DE

NEW QUESTION 12

The SALES_Q1 and USERS tablespaces exist in one of your databases and TEMP is a temporary tablespace. Segment creation is not deferred.

You execute this command:

```
CREATE USER sales
  IDENTIFIED BY sales_123
  DEFAULT TABLESPACE sales_q1
  TEMPORARY TABLESPACE temp
  QUOTA 5M ON users;
```

Which three statements must be true so that the SALES user can create tables in SALES_Q1? (Choose three.)

- A. The sales user must have a quota on the TEMP tablespace
- B. The sales user must have a quota on the SALES_Q1 tablespace to hold the initial extends of all tables they plan to create in their schema
- C. The sales user must have been granted the CREATE SESSION privilege
- D. The sales user must have their quota on the users tablespace removed
- E. The sales user must have a quota on the SALES_Q1 tablespace to hold all the rows to be inserted into any table in their schema
- F. The sales user must have been granted the CREATE TABLE privilege

Answer: BDF

NEW QUESTION 17

Which three statements are true about Oracle synonyms? (Choose three.)

- A. A synonym cannot be created for a PL/SQL package
- B. A synonym can be available to all users
- C. A SEQUENCE can have a synonym
- D. A synonym created by one user can refer to an object belonging to another user
- E. Any user can drop a PUBLIC synonym

Answer: BCD

NEW QUESTION 19

Which three statements are true about undo segments and the use of undo by transactions in an Oracle database instance? (Choose three.)

- A. An undo segment may be used by multiple transactions simultaneously
- B. Undo segments can wrap around to the first extent when a transaction fills the last extent of the undo segment
- C. Undo segments have a minimum of three extents
- D. Undo segments can extend when a transaction fills the last extent of the undo segment
- E. A single transaction may use multiple undo segments simultaneously
- F. Undo segments must be stored in a BIGFILE tablespace
- G. Undo segments must be stored in a SMALLFILE tablespace

Answer: ADG

NEW QUESTION 23

In the SALES database, DEFERRED_SEGMENT_CREATION is TRUE. Examine this command:

```
SQL> CREATE TABLE T1(c1 INT PRIMARY KEY, c2 CLOB);
```

Which segment or segments, if any, are created as a result of executing the command?

- A. T1, an index segment for the primary key, a LOB segment, and a lobindex segment
- B. no segments are created
- C. T1 only

- D. T1 and an index segment created for the primary key only
- E. T1, an index segment for the primary key, and a LOB segment only

Answer: C

NEW QUESTION 25

Which statement is true about aggregate functions?

- A. Aggregate functions can be nested to any number of levels
- B. The AVG function implicitly converts NULLS to zero
- C. Aggregate functions can be used in any clause of a SELECT statement
- D. The MAX and MIN functions can be used on columns with character data types

Answer: A

NEW QUESTION 30

Which three statements are true about a self-join? (Choose three.)

- A. The ON clause must be used
- B. The query must use two different aliases for the table
- C. It must be an equi join
- D. It must be an inner join
- E. The ON clause can be used
- F. It can be an outer join

Answer: BDE

NEW QUESTION 31

Which two statements are true about single row functions? (Choose two.)

- A. MOD : returns the quotient of a division operation
- B. FLOOR : returns the smallest integer greater than or equal to a specified number
- C. TRUNC : can be used to combine any number of values
- D. CONCAT : can be used to combine any number of values
- E. CEIL : can be used for positive and negative numbers

Answer: AC

NEW QUESTION 35

Examine these commands:

```
[oracle@host01 ~]$ sqlplus u1/oracle
SQL> SELECT * FROM emp;

ENO          ENAME          DN
-----
1            Alan           2
2            Ben            2

SQL> exit
[oracle@host01 ~]$ cat emp.dat

3,Curl,4
4,Bob,4
[oracle@host01 ~]$ sqlldr u1/oracle TABLE=emp
```

Which two statements are true about the sqlldr execution? (Choose two.)

- A. It overwrites data in EMP with data in EMP.DAT
- B. It uses the database buffer cache to load data
- C. It generates a log that contains control file entries, which can be used with normal SQL*Loader operations
- D. It generates a sql script that it uses to load data from EMP.DAT to EMP
- E. It appends data from EMP.DAT to EMP

Answer: BD

NEW QUESTION 40

Which two tasks can you perform using DBCA for databases? (Choose two.)

- A. Configure a nonstandard block size for a new database
- B. Register a new database with an available Enterprise Manager Management server
- C. Change the standard block size of an existing database

- D. Configure incremental backups for a new database
- E. Enable flashback database for an existing database

Answer: BC

NEW QUESTION 43

Which two statements are true about views used for viewing tablespace and datafile information? (Choose two.)

- A. Tablespace free space can be viewed in VTABLESPACE
- B. VTABLESPACE displays information that is contained in the controlfile about tablespaces
- C. VTABLESPACE displays information about tablespaces contained in the data dictionary
- D. Tablespace free space can be viewed in DBA_TABLESPACES
- E. A datafile can be renamed when the database is in MOUNT state and the new file name is displayed when querying DBA_DATA_FILES after the database is opened

Answer: BE

NEW QUESTION 44

Examine the description of the EMPLOYEES table:

Name	Null?	Type
-----	-----	-----
EMP_ID	NOT NULL	NUMBER
EMP_NAME		VARCHAR2 (40)
DEPT_ID		NUMBER (2)
SALARY		NUMBER (8, 2)
JOIN_DATE		DATE

Which query is valid?

- A. SELECT dept_id, AVG(MAX(salary)) FROM employees GROUP BY dept_id;
- B. SELECT dept_id, join_date, SUM(salary) FROM employees GROUP BY dept_id;
- C. SELECT dept_id, join_date, SUM(salary) FROM employees GROUP BY dept_id, join_date;
- D. SELECT dept_id, MAX(AVG(salary)) FROM employees GROUP BY dept_id;

Answer: B

NEW QUESTION 49

What is true about non-equijoin statement performance? (Choose two.)

- A. Table aliases can improve performance
- B. The BETWEEN condition always performs better than using the >= and <= conditions
- C. The join syntax used makes no difference to performance
- D. The BETWEEN condition always performs less well than using the >= and <= conditions
- E. The Oracle join syntax performs better than the SQL:1999 compliant ANSI join syntax

Answer: AE

NEW QUESTION 53

View the Exhibit and examine the structure of the PRODUCTS table. Which two tasks require subqueries? (Choose two.)

Table PRODUCTS		
Name	Null?	Type
PROD_ID	NOT NULL	NUMBER(6)
PROD_NAME	NOT NULL	VARCHAR2(50)
PROD_DESC	NOT NULL	VARCHAR2(4000)
PROD_CATEGORY	NOT NULL	VARCHAR2(50)
PROD_CATEGORY_ID	NOT NULL	NUMBER
PROD_UNIT_OF_MEASURE		VARCHAR2(20)
SUPPLIER_ID	NOT NULL	NUMBER(6)
PROD_STATUS	NOT NULL	VARCHAR2(20)
PROD_LIST_PRICE	NOT NULL	NUMBER(8,2)
PROD_MIN_PRICE	NOT NULL	NUMBER(8,2)

- A. Display the number of products whose PROD_LIST_PRICE is more than the average PROD_LIST_PRICE
- B. Display suppliers whose PROD_LIST_PRICE is less than 1000
- C. Display products whose PROD_MIN_PRICE is more than the average PROD_LIST_PRICE of all products, and whose status is orderable
- D. Display the total number of products supplied by supplier 102 which have a product status of obsolete
- E. Display the minimum PROD_LIST_PRICE for each product status

Answer: AC

NEW QUESTION 56

Examine the description of the CUSTOMERS table:

Name	Null?	Type

CUST_ID	NOT NULL	NUMBER
CUST_FIRST_NAME	NOT NULL	VARCHAR2 (20)
CUST_LAST_NAME	NOT NULL	VARCHAR2 (30)
CUST_INCOME_LEVEL		VARCHAR2 (30)
CUST_CREDIT_LIMIT		NUMBER

You want to display details of all customers who reside in cities starting with the letter D followed by at least two characters. Which query can be used?

- A. SELECT * FROM customers WHERE city LIKE 'D_%';
- B. SELECT * FROM customers WHERE city = '%D_%';
- C. SELECT * FROM customers WHERE city LIKE 'D_';
- D. SELECT * FROM customers WHERE city = 'D_%';

Answer: A

NEW QUESTION 57

Which three statements are true about external tables in Oracle 18c and later releases? (Choose three.)

- A. External table files can be used for other external tables in a different database
- B. The ORACLE_LOADER access driver can be used to unload data from a database into an external table
- C. The ORACLE_DATAPUMP access driver can be used to unload data from a database into an external table
- D. They cannot be partitioned
- E. The ORACLE_DATAPUMP access driver can be used to load data into a database from an external table
- F. They support UPDATES but not INSERTs and DELETES

Answer: ABF

NEW QUESTION 59

Which three statements are true about the Oracle Data Dictionary? (Choose three.)

- A. Data dictionary views are created by joins of dictionary base tables and DBA-defined tables
- B. The data dictionary is created and maintained by the database administrator
- C. Views with the same name but different prefixes, such as CDB, DBA, ALL and USER, reference the same base tables from the data dictionary
- D. Base tables can be queried directly
- E. It is owned by the SYSTEM user
- F. Usernames of all users including database administrators are stored in the data dictionary

Answer: CDF

NEW QUESTION 61

A script abc.sql must be executed to perform a job.

A database user HR, who is defined in this database, executes this command:

\$ sqlplus hr/hr@orcl @abc.sql What will happen upon execution?

- A. The command succeeds and HR will be connected to the orcl and abc.sql databases
- B. The command succeeds and HR will be connected to the orcl database instance, and the abc.sql script will be executed
- C. The command fails because the script must refer to the full path name
- D. The command fails and reports an error because @ is used twice

Answer: B

NEW QUESTION 63

In which three situations does a new transaction always start? (Choose three.)

- A. when issuing a SELECT FOR UPDATE statement after a CREATE TABLE AS SELECT statement was issued in the same session
- B. when issuing a TRUNCATE statement after a SELECT statement was issued in the same session
- C. when issuing a CREATE TABLE statement after a SELECT statement was issued in the same session
- D. when issuing the first Data Manipulation Language (DML) statement after a COMMIT OR ROLLBACK statement was issued in the same session
- E. when issuing a CREATE INDEX statement after a CREATE TABLE statement completed successfully in the same session
- F. when issuing a DML statement after a DML statement failed in the same session

Answer: ADF

NEW QUESTION 66

Which two statements are true regarding the UNION and UNION ALL operators? (Choose two.)

- A. Duplicates are eliminated automatically by the UNION ALL operator
- B. The number of columns selected in each SELECT statement must be identical
- C. The names of columns selected in each SELECT statement must be identical
- D. The output is sorted by the UNION ALL operator
- E. NULLS are not ignored during duplicate checking

Answer: BE

NEW QUESTION 70

In one of your databases, user KING is:

- \1. Not a DBA user
- \2. An operating system (OS) user Examine this command and its output:

```
SHOW PARAMETER OS_AUTHENT_PREFIX

NAME                                TYPE                                VALUE
-----                                -                                -
os_authen_prefix                    string                             TRUE
```

What must you do so that KING is authenticated by the OS when connecting to the database instance?

- A. Set OS_AUTHENT_PREFIX to OPS\$
- B. Have the OS administrator add KING to the OSDBA group
- C. Grant DBA to KING
- D. Unset REMOTE_LOGIN_PASSWORDFILE
- E. Alter user KING to be IDENTIFIED EXTERNALLY

Answer: D

NEW QUESTION 73

A database is configured to use automatic undo management with temporary undo enabled. An UPDATE is executed on a temporary table. Where is the UNDO stored?

- A. in the undo tablespace
- B. in the SYSAUX tablespace
- C. in the SGA
- D. in the PGA
- E. in the temporary tablespace

Answer: A

NEW QUESTION 76

Which three statements are true concerning logical and physical database structures? (Choose three.)

- A. All tablespaces may have one or more data files
- B. The extents of a segment must always reside in the same datafile
- C. A smallfile tablespace might be bigger than a bigfile tablespace
- D. A segment can span multiple data files in some tablespaces
- E. A segment's blocks can be of different sizes
- F. A segment might have only one extent
- G. Segments can span multiple tablespaces

Answer: CFG

NEW QUESTION 81

Your database instance is started with a PFILE.

Examine these parameters:

```
NAME                                TYPE                                VALUE
-----                                -                                -
memory_max_target                    big integer                          0
memory_target                        big integer                          0
sga_max_size                         big integer                         2G
sga_target                           big integer                         2G
```

You want to increase the size of the buffer cache.

Free memory is available to increase the size of the buffer cache. You execute the command:

```
SQL> ALTER SYSTEM SET DB_CACHE_SIZE=1024M;
```

What is the outcome?

- A. The value is changed only in the PFILE and takes effect at the next instance startup

- B. The value is changed for the current instance and in the PFILE
- C. It fails because the SCOPE clause is missing
- D. Change is applied to the current instance, but does not persist after instance restart

Answer: D

NEW QUESTION 82

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questons and Answers in PDF Format

1z0-082 Practice Exam Features:

- * 1z0-082 Questions and Answers Updated Frequently
- * 1z0-082 Practice Questions Verified by Expert Senior Certified Staff
- * 1z0-082 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * 1z0-082 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The 1z0-082 Practice Test Here](#)